




For the toughest materials and milling applications

WXL WXS

Volume 3





INDEX | SELECTION CHART

Application	A-brand	Product name	Page	Z	Range	P		H		M	K	N	S	CFRP	GRAPHITE
						~45 HRC	~55 HRC	~60 HRC	~65 HRC	~35 HRC	~350 HB				
		WXL-1,5D-DE NEW SIZES	Page 3	WXL	2	0,1 ~ 12	●	●			●	●	○		
		WXL-2D-DE NEW SIZES	Page 5	WXL	2	0,1 ~ 30	●	●			●	●	○		
		WXL-3D-DE	Page 9	WXL	2	0,1 ~ 20	●	●			●	●	○		
		WXL-4D-DE	Page 11	WXL	2	0,2 ~ 12	●	●			●	●	○		
		WXL-EMS NEW SIZES	Page 13	WXL	4	1 ~ 30	●	●	○		●	●	○		
		WXS-EMS	Page 37	WXS	4/6	1 ~ 30	●	●	●	○	○	○	○		
		WXL-CR-EDS-6	Page 20	WXL	2	0,6 ~ 2,5	●	●	○		●	●	○		
		WXS-(HS)-CRE	Page 35	WXS	5/4	2 ~ 12	●	●	●	●			○		
		WXS-CPR	Page 44	WXS	2/4	0,2 ~ 4	●	●	●	●					
		WXL-LN-EDS NEW SIZES	Page 15	WXL	2	0,1 ~ 12	●	●	○		○	●	○		
		WXL-LN-EMS-6	Page 14	WXL	4	1 ~ 6	●	●	○		○	●	○		
		WXL-EBD NEW SIZES	Page 22	WXL	2	R0,05 ~ R10	●	●	○		●	●	○		
		WXL-HS-EBD NEW	Page 21	WXL	2	R0,1 ~ R6	●	●	○		●	●	○		
		WXS-HS-EBD	page 38	WXS	2	R0,5 ~ R6	●	●	●	○	●	●	○		
		WXL-LN-EBD	Page 24	WXL	2	R0,05 ~ R3	●	●	○		●	●	○		
		WXL-PC-EBD NEW SIZES	Page 31	WXL	2	R0,1 ~ R6	●	●	○		●	●	○		
		WXS-LN-EBD	Page 39	WXS	2	R0,05 ~ R3	○	●	●	○	○	○	○		

WXL-1,5D-DE

Milling | Solid carbide



- Carbide end mill with WXL coating
- For steels, stainless, copper
- 2 flutes, 1.5xD applications, square




EDP	ZEFP	DC	LF	APMX	DCON
3181801	2	0,1	45	0,15	4
3181802	2	0,2	45	0,3	4
3181803	2	0,3	45	0,45	4
3181804	2	0,4	45	0,6	4
3181805	2	0,5	45	0,75	4
3181806	2	0,6	45	0,9	4
3181807	2	0,7	45	1,1	4
3181808	2	0,8	45	1,2	4
3181809	2	0,9	45	1,4	4
3181810	2	1	45	1,5	4
3181811	2	1,1	45	1,7	4
3181812	2	1,2	45	1,8	4
3181813	2	1,3	45	2	4
3181814	2	1,4	45	2,1	4
3181815	2	1,5	45	2,3	4
3181816	2	1,6	45	2,4	4
3181817	2	1,7	45	2,6	4
3181818	2	1,8	45	2,7	4
3181819	2	1,9	45	2,9	4
3181820	2	2	45	3	4
3181821	2	2,1	45	3,2	4
3181822	2	2,2	45	3,3	4
3181823	2	2,3	45	3,5	4
3181824	2	2,4	45	3,6	4
3181825	2	2,5	45	3,8	4
3181826	2	2,6	45	3,9	4
3181827	2	2,7	45	4,1	4
3181828	2	2,8	45	4,2	4
3181829	2	2,9	45	4,4	4
3181830	2	3	45	4,5	6
3181831	2	3,1	45	4,7	6
3181832	2	3,2	45	4,8	6
3181833	2	3,3	45	5	6
3181834	2	3,4	45	5,1	6
3181835	2	3,5	45	5,3	6
3181836	2	3,6	45	5,4	6
3181837	2	3,7	45	5,6	6
3181838	2	3,8	45	5,7	6
3181839	2	3,9	45	5,9	6
3181840	2	4	45	6	6
3181841	2	4,1	50	6,2	6
3181842	2	4,2	50	6,3	6
3181843	2	4,3	50	6,5	6
3181844	2	4,4	50	6,6	6
3181845	2	4,5	50	6,8	6
3181846	2	4,6	50	6,9	6

Milling | Solid carbide



WXL-2D-DE

Milling | Solid carbide



- Carbide end mill with WXL coating
- For steels, stainless, copper
- 2 flutes, 2xD applications, square





EDP	ZEFP	DC	LF	APMX	DCON
3182001	2	0,1	45	0,2	4
3182002	2	0,2	45	0,4	4
3182003	2	0,3	45	0,6	4
3182004	2	0,4	45	0,8	4
3182005	2	0,5	45	1	4
3182006	2	0,6	45	1,2	4
3182007	2	0,7	45	1,4	4
3182008	2	0,8	45	1,6	4
3182009	2	0,9	45	1,8	4
3182010	2	1	45	2	4
3182011	2	1,1	45	2,2	4
3182012	2	1,2	45	2,4	4
3182013	2	1,3	45	2,6	4
3182014	2	1,4	45	2,8	4
3182015	2	1,5	45	3	4
3182016	2	1,6	45	3,2	4
3182017	2	1,7	45	3,4	4
3182018	2	1,8	45	3,6	4
3182019	2	1,9	45	3,8	4
3182020	2	2	45	4	4
3182021	2	2,1	45	4,2	4
3182022	2	2,2	45	4,4	4
3182023	2	2,3	45	4,6	4
3182024	2	2,4	45	4,8	4
3182025	2	2,5	45	5	4
3182026	2	2,6	45	5,2	4
3182027	2	2,7	45	5,4	4
3182028	2	2,8	45	5,6	4
3182029	2	2,9	45	5,8	4
3182030	2	3	45	6	6
3182031	2	3,1	45	6,2	6
3182032	2	3,2	45	6,4	6
3182033	2	3,3	45	6,6	6
3182034	2	3,4	45	6,8	6
3182035	2	3,5	45	7	6
3182036	2	3,6	45	7,2	6
3182037	2	3,7	45	7,4	6
3182038	2	3,8	45	7,6	6
3182039	2	3,9	45	7,8	6
3182040	2	4	45	8	6
3182041	2	4,1	50	8,2	6
3182042	2	4,2	50	8,4	6
3182043	2	4,3	50	8,6	6
3182044	2	4,4	50	8,8	6
3182045	2	4,5	50	9	6
3182046	2	4,6	50	9,2	6

Milling | Solid carbide



WXL-2D-DE

Milling | Solid carbide



- Carbide end mill with WXL coating
- For steels, stainless, copper
- 2 flutes, 2xD applications, square





EDP	ZEFP	DC	LF	APMX	DCON
3182047	2	4,7	50	9,4	6
3182048	2	4,8	50	9,6	6
3182049	2	4,9	50	9,8	6
3182050	2	5	50	10	6
3182051	2	5,1	50	10,2	6
3182052	2	5,2	50	10,4	6
3182053	2	5,3	50	10,6	6
3182054	2	5,4	50	10,8	6
3182055	2	5,5	50	11	6
3182056	2	5,6	50	11,2	6
3182057	2	5,7	50	11,4	6
3182058	2	5,8	50	11,6	6
3182059	2	5,9	50	11,8	6
3182060	2	6	50	12	6
3182061	2	6,1	60	12,2	8
3182062	2	6,2	60	12,4	8
3182063	2	6,3	60	12,6	8
3182064	2	6,4	60	12,8	8
3182065	2	6,5	60	13	8
3182066	2	6,6	60	13,2	8
3182067	2	6,7	60	13,4	8
3182068	2	6,8	60	13,6	8
3182069	2	6,9	60	13,8	8
3182070	2	7	60	14	8
3182071	2	7,1	60	14,2	8
3182072	2	7,2	60	14,4	8
3182073	2	7,3	60	14,6	8
3182074	2	7,4	60	14,8	8
3182075	2	7,5	60	15	8
3182076	2	7,6	60	15,2	8
3182077	2	7,7	60	15,4	8
3182078	2	7,8	60	15,6	8
3182079	2	7,9	60	15,8	8
3182080	2	8	60	16	8
3182081	2	8,1	70	16,2	10
3182082	2	8,2	70	16,4	10
3182083	2	8,3	70	16,6	10
3182084	2	8,4	70	16,8	10
3182085	2	8,5	70	17	10
3182086	2	8,6	70	17,2	10
3182087	2	8,7	70	17,4	10
3182088	2	8,8	70	17,6	10
3182089	2	8,9	70	17,8	10
3182090	2	9	70	18	10
3182091	2	9,1	70	18,2	10
3182092	2	9,2	70	18,4	10

Milling | Solid carbide



WXL-2D-DE

Milling | Solid carbide



- Carbide end mill with WXL coating
- For steels, stainless, copper
- 2 flutes, 2xD applications, square




EDP	ZEFP	DC	LF	APMX	DCON
3182093	2	9,3	70	18,6	10
3182094	2	9,4	70	18,8	10
3182095	2	9,5	70	19	10
3182096	2	9,6	70	19,2	10
3182097	2	9,7	70	19,4	10
3182098	2	9,8	70	19,6	10
3182099	2	9,9	70	19,8	10
3182100	2	10	70	20	10
3182101	2	10,1	75	20,2	12
3182102	2	10,2	75	20,4	12
3182103	2	10,3	75	20,6	12
3182104	2	10,4	75	20,8	12
3182105	2	10,5	75	21	12
3182106	2	10,6	75	21,2	12
3182107	2	10,7	75	21,4	12
3182108	2	10,8	75	21,6	12
3182109	2	10,9	75	21,8	12
3182110	2	11	75	22	12
3182111	2	11,1	75	22,2	12
3182112	2	11,2	75	22,4	12
3182113	2	11,3	75	22,6	12
3182114	2	11,4	75	22,8	12
3182115	2	11,5	75	23	12
3182116	2	11,6	75	23,2	12
3182117	2	11,7	75	23,4	12
3182118	2	11,8	75	23,6	12
3182119	2	11,9	75	23,8	12
3182120	2	12	75	24	12
3182121	2	12,1	85	24,2	12
3182122	2	12,2	85	24,4	12
3182123	2	12,3	85	24,6	12
3182124	2	12,4	85	24,8	12
3182125	2	12,5	85	25	12
3182126	2	12,6	85	25,2	12
3182127	2	12,7	85	25,4	12
3182128	2	12,8	85	25,6	12
3182129	2	12,9	85	25,8	12
3182130	2	13	85	26	12
3182131	2	13,1	85	26,2	12
3182132	2	13,2	85	26,4	12
3182133	2	13,3	85	26,6	12
3182134	2	13,4	85	26,8	12
3182135	2	13,5	85	27	12
3182136	2	13,6	85	27,2	12
3182137	2	13,7	85	27,4	12
3182138	2	13,8	85	27,6	12

Milling | Solid carbide



WXL-3D-DE

Milling | Solid carbide



- Carbide end mill with WXL coating
- For steels, stainless, copper
- 2 flutes, 3xD applications, square





EDP	ZEFP	DC	LF	APMX	DCON
3182401	2	0,1	45	0,3	4
3182402	2	0,2	45	0,6	4
3182403	2	0,3	45	0,9	4
3182404	2	0,4	45	1,2	4
3182405	2	0,5	45	1,5	4
3182406	2	0,6	45	1,8	4
3182407	2	0,7	45	2,1	4
3182408	2	0,8	45	2,4	4
3182409	2	0,9	45	2,7	4
3182410	2	1	45	3	4
3182411	2	1,1	45	3,3	4
3182412	2	1,2	45	3,6	4
3182413	2	1,3	45	3,9	4
3182414	2	1,4	45	4,2	4
3182415	2	1,5	45	4,5	4
3182416	2	1,6	45	4,8	4
3182417	2	1,7	45	5,1	4
3182418	2	1,8	45	5,4	4
3182419	2	1,9	45	5,7	4
3182420	2	2	45	6	4
3182421	2	2,1	45	6,3	4
3182422	2	2,2	45	6,6	4
3182423	2	2,3	45	6,9	4
3182424	2	2,4	45	7,2	4
3182425	2	2,5	45	7,5	4
3182426	2	2,6	45	7,8	4
3182427	2	2,7	45	8,1	4
3182428	2	2,8	45	8,4	4
3182429	2	2,9	45	8,7	4
3182430	2	3	45	9	6
3182431	2	3,1	45	9,3	6
3182432	2	3,2	45	9,6	6
3182433	2	3,3	45	9,9	6
3182434	2	3,4	45	10,2	6
3182435	2	3,5	45	10,5	6
3182436	2	3,6	45	10,8	6
3182437	2	3,7	45	11,1	6
3182438	2	3,8	45	11,4	6
3182439	2	3,9	45	11,7	6
3182440	2	4	50	12	6
3182441	2	4,1	50	12,3	6
3182442	2	4,2	50	12,6	6
3182443	2	4,3	50	12,9	6
3182444	2	4,4	50	13,2	6
3182445	2	4,5	50	13,5	6
3182446	2	4,6	55	13,8	6

Milling | Solid carbide



WXL-3D-DE

Milling | Solid carbide



- Carbide end mill with WXL coating
- For steels, stainless, copper
- 2 flutes, 3xD applications, square





Milling | Solid carbide



EDP	ZEFP	DC	LF	APMX	DCON
3182447	2	4,7	55	14,1	6
3182448	2	4,8	55	14,4	6
3182449	2	4,9	55	14,7	6
3182450	2	5	55	15	6
3182451	2	5,1	55	15,3	6
3182452	2	5,2	55	15,6	6
3182453	2	5,3	55	15,9	6
3182454	2	5,4	55	16,2	6
3182455	2	5,5	60	16,5	6
3182456	2	5,6	60	16,8	6
3182457	2	5,7	60	17,1	6
3182458	2	5,8	60	17,4	6
3182459	2	5,9	60	17,7	6
3182460	2	6	60	18	6
3182465	2	6,5	65	19,5	8
3182470	2	7	65	21	8
3182475	2	7,5	70	22,5	8
3182480	2	8	70	24	8
3182485	2	8,5	70	25,5	10
3182490	2	9	75	27	10
3182495	2	9,5	75	28,5	10
3182500	2	10	80	30	10
3182510	2	11	80	33	12
3182520	2	12	90	36	12
3182560	2	16	110	48	16
3182580	2	18	130	54	16
3182600	2	20	130	60	20

WXL-4D-DE

Milling | Solid carbide



- Carbide end mill with WXL coating
- For steels, stainless, copper
- 2 flutes, 4xD applications, square





EDP	ZEFP	DC	LF	APMX	DCON
3182602	2	0,2	45	0,8	4
3182603	2	0,3	45	1,2	4
3182604	2	0,4	45	1,6	4
3182605	2	0,5	45	2	4
3182606	2	0,6	45	2,4	4
3182607	2	0,7	45	2,8	4
3182608	2	0,8	45	3,2	4
3182609	2	0,9	45	3,6	4
3182610	2	1	45	4	4
3182611	2	1,1	45	4,4	4
3182612	2	1,2	45	4,8	4
3182613	2	1,3	45	5,2	4
3182614	2	1,4	45	5,6	4
3182615	2	1,5	45	6	4
3182616	2	1,6	45	6,4	4
3182617	2	1,7	45	6,8	4
3182618	2	1,8	45	7,2	4
3182619	2	1,9	45	7,6	4
3182620	2	2	45	8	4
3182621	2	2,1	45	8,4	4
3182622	2	2,2	45	8,8	4
3182623	2	2,3	45	9,2	4
3182624	2	2,4	45	9,6	4
3182625	2	2,5	45	10	4
3182626	2	2,6	50	10,4	4
3182627	2	2,7	50	10,8	4
3182628	2	2,8	50	11,2	4
3182629	2	2,9	50	11,6	4
3182630	2	3	50	12	6
3182631	2	3,1	50	12,4	6
3182632	2	3,2	50	12,8	6
3182633	2	3,3	50	13,2	6
3182634	2	3,4	50	13,6	6
3182635	2	3,5	50	14	6
3182636	2	3,6	50	14,4	6
3182637	2	3,7	50	14,8	6
3182638	2	3,8	50	15,2	6
3182639	2	3,9	50	15,6	6
3182640	2	4	55	16	6
3182641	2	4,1	55	16,4	6
3182642	2	4,2	55	16,8	6
3182643	2	4,3	55	17,2	6
3182644	2	4,4	55	17,6	6
3182645	2	4,5	55	18	6
3182646	2	4,6	55	18,4	6
3182647	2	4,7	55	18,8	6

Milling | Solid carbide



WXL-EMS

Milling | Solid carbide



- Carbide end mill with WXL coating
- For high speed milling in steels, stainless and cast iron
- 4 flutes, square





EDP	ZEFP	DC	LF	APMX	DCON
3130510	4	1	40	2,5	4
3130515	4	1,5	40	4	4
3130520	4	2	40	6	4
3130525	4	2,5	40	8	4
3130530	4	3	45	8	6
3130535	4	3,5	45	10	6
3130540	4	4	45	11	6
3130545	4	4,5	45	11	6
3130550	4	5	50	13	6
3130555	4	5,5	50	13	6
3130560	4	6	50	13	6
3130565	4	6,5	60	16	8
3130570	4	7	60	16	8
3130575	4	7,5	60	16	8
3130580	4	8	60	19	8
3130585	4	8,5	70	19	10
3130590	4	9	70	19	10
3130595	4	9,5	70	19	10
3130600	4	10	70	22	10
3130605	4	10,5	75	22	12
3130610	4	11	75	22	12
3130615	4	11,5	75	22	12
3130620	4	12	75	26	12
3130625	4	12,5	85	26	12
3130630	4	13	85	26	12
3130640	4	14	85	26	12
3130650	4	15	90	26	16
3130660	4	16	100	32	16
3130670	4	17	100	32	16
3130680	4	18	100	32	16
3130690	4	19	100	32	20
3130700	4	20	105	38	20
3130710	4	21	105	38	20
3130720	4	22	105	38	20
3130730	4	23	120	45	25
3130740	4	24	120	45	25
3130750	4	25	120	45	25
3130800	4	30	125	45	32

Milling | Solid carbide




WXL-LN-EDS

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC
- 2 flutes, long neck, square
- 199 sizes





EDP	ZEFP	DC	LU	LF	APMX	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3131100	2	0,1	0,3	45	0,15	4	0,09	14,61	0,31	0,32	0,33	0,34	0,37	-
3131101	2	0,1	0,5	45	0,15	4	0,09	14,04	0,53	0,56	0,58	0,61	0,66	-
3131102	2	0,1	1	45	0,15	4	0,09	13,22	1,05	1,1	1,14	1,18	1,28	-
3131201	2	0,2	0,5	45	0,3	4	0,18	14,02	0,52	0,55	0,57	0,6	0,62	0,64
3131202	2	0,2	1	45	0,3	4	0,18	13,19	1,05	1,09	1,13	1,17	1,22	1,27
3131203	2	0,2	1,5	45	0,3	4	0,18	12,45	1,57	1,62	1,68	1,75	1,81	1,89
3131204	2	0,2	2	45	0,3	4	0,18	11,78	2,09	2,16	2,24	2,32	2,41	2,51
3131205	2	0,2	2,5	45	0,3	4	0,18	11,18	2,6	2,69	2,79	2,9	3,01	3,13
3131206	2	0,2	3	45	0,3	4	0,18	10,64	3,12	3,23	3,35	3,47	3,61	3,75
3131207	2	0,2	3,5	45	0,3	4	0,18	10,15	3,64	3,76	3,9	4,05	4,2	4,37
3131208	2	0,2	4	45	0,3	4	0,18	9,71	4,15	4,3	4,45	4,62	4,8	5
3131302	2	0,3	1	45	0,45	4	0,28	13,16	1,03	1,08	1,12	1,16	1,21	1,25
3131303	2	0,3	1,5	45	0,45	4	0,28	12,4	1,56	1,61	1,67	1,74	1,8	1,88
3131304	2	0,3	2	45	0,45	4	0,28	11,73	2,08	2,15	2,23	2,31	2,4	2,5
3131305	2	0,3	2,5	45	0,45	4	0,28	11,12	2,59	2,68	2,78	2,88	3	3,12
3131306	2	0,3	3	45	0,45	4	0,28	10,57	3,11	3,22	3,33	3,46	3,59	3,74
3131308	2	0,3	4	45	0,45	4	0,28	9,62	4,14	4,29	4,44	4,61	4,79	4,98
3131310	2	0,3	5	45	0,45	4	0,28	8,83	5,18	5,36	5,55	5,76	5,98	6,23
3131312	2	0,3	6	45	0,45	4	0,28	8,15	6,21	6,43	6,66	6,91	7,18	7,47
3131318	2	0,3	9	45	0,45	4	0,28	6,63	9,31	9,64	9,98	10,36	10,76	11,2
3131403	2	0,4	1,5	45	0,6	4	0,37	12,4	1,52	1,57	1,63	1,69	1,75	1,82
3131404	2	0,4	2	45	0,6	4	0,37	11,71	2,03	2,1	2,18	2,26	2,35	2,45
3131406	2	0,4	3	45	0,6	4	0,37	10,53	3,07	3,17	3,29	3,41	3,55	3,69
3131408	2	0,4	4	45	0,6	4	0,37	9,56	4,1	4,24	4,4	4,56	4,74	4,93
3131410	2	0,4	5	45	0,6	4	0,37	8,76	5,13	5,31	5,51	5,71	5,93	6,18
3131412	2	0,4	6	45	0,6	4	0,37	8,08	6,17	6,38	6,61	6,86	7,13	7,42
3131414	2	0,4	7	45	0,6	4	0,37	7,49	7,2	7,45	7,72	8,01	8,32	8,66
3131416	2	0,4	8	45	0,6	4	0,37	6,99	8,24	8,52	8,83	9,16	9,52	9,9
3131418	2	0,4	9	45	0,6	4	0,37	6,55	9,27	9,59	9,94	10,31	10,71	11,15
3131420	2	0,4	10	45	0,6	4	0,37	6,16	10,3	10,66	11,05	11,46	11,91	12,39
3131424	2	0,4	12	45	0,6	4	0,37	5,5	12,37	12,8	13,26	13,76	14,3	14,88
3131501	2	0,5	1,5	45	0,7	4	0,45	12,29	1,56	1,61	1,67	1,73	1,8	1,87
3131502	2	0,5	2	45	0,7	4	0,45	11,59	2,07	2,14	2,22	2,31	2,4	2,49
3131503	2	0,5	3	45	0,7	4	0,45	10,4	3,11	3,21	3,33	3,46	3,59	3,74
3131504	2	0,5	4	45	0,7	4	0,45	9,43	4,14	4,28	4,44	4,61	4,78	4,98
3131505	2	0,5	5	45	0,7	4	0,45	8,63	5,17	5,35	5,55	5,75	5,98	6,22
3131506	2	0,5	6	45	0,7	4	0,45	7,95	6,21	6,42	6,66	6,9	7,17	7,47
3131507	2	0,5	7	45	0,7	4	0,45	7,37	7,24	7,49	7,76	8,05	8,37	8,71
3131508	2	0,5	8	45	0,7	4	0,45	6,86	8,27	8,56	8,87	9,2	9,56	9,95
3131509	2	0,5	9	45	0,7	4	0,45	6,43	9,31	9,63	9,98	10,35	10,76	11,19
3131510	2	0,5	10	45	0,7	4	0,45	6,04	10,34	10,7	11,09	11,5	11,95	12,44
3131512	2	0,5	12	45	0,7	4	0,45	5,39	12,41	12,84	13,31	13,8	14,34	14,92
3131515	2	0,5	15	50	0,7	4	0,45	4,65	15,51	16,05	16,63	17,25	17,93	18,65
3131602	2	0,6	2	45	0,9	4	0,55	11,51	2,07	2,14	2,22	2,31	2,4	2,49
3131603	2	0,6	3	45	0,9	4	0,55	10,31	3,11	3,21	3,33	3,46	3,59	3,74
3131604	2	0,6	4	45	0,9	4	0,55	9,33	4,14	4,28	4,44	4,61	4,78	4,98

Milling | Solid carbide




WXL-LN-EDS

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC
- 2 flutes, long neck, square
- 199 sizes





Milling | Solid carbide


EDP	ZEFP	DC	LU	LF	APMX	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3131605	2	0,6	5	45	0,9	4	0,55	8,52	5,17	5,35	5,55	5,75	5,98	6,22
3131606	2	0,6	6	45	0,9	4	0,55	7,84	6,21	6,42	6,66	6,9	7,17	7,47
3131607	2	0,6	7	45	0,9	4	0,55	7,26	7,24	7,49	7,76	8,05	8,37	8,71
3131608	2	0,6	8	45	0,9	4	0,55	6,76	8,27	8,56	8,87	9,2	9,56	9,95
3131610	2	0,6	10	45	0,9	4	0,55	5,94	10,34	10,7	11,09	11,5	11,95	12,44
3131612	2	0,6	12	45	0,9	4	0,55	5,29	12,41	12,84	13,31	13,8	14,34	14,92
3131615	2	0,6	15	50	0,9	4	0,55	4,55	15,51	16,05	16,63	17,25	17,93	18,65
3131618	2	0,6	18	50	0,9	4	0,55	3,99	18,61	19,26	19,96	20,7	21,51	22,38
3131702	2	0,7	2	45	1	4	0,65	11,43	2,07	2,14	2,22	2,31	2,4	2,49
3131704	2	0,7	4	45	1	4	0,65	9,22	4,14	4,28	4,44	4,61	4,78	4,98
3131706	2	0,7	6	45	1	4	0,65	7,73	6,21	6,42	6,66	6,9	7,17	7,47
3131708	2	0,7	8	45	1	4	0,65	6,65	8,27	8,56	8,87	9,2	9,56	9,95
3131710	2	0,7	10	45	1	4	0,65	5,83	10,34	10,7	11,09	11,5	11,95	12,44
3131804	2	0,8	4	45	1,2	4	0,75	9,11	4,14	4,28	4,44	4,61	4,78	4,98
3131806	2	0,8	6	45	1,2	4	0,75	7,61	6,21	6,42	6,66	6,9	7,17	7,47
3131808	2	0,8	8	45	1,2	4	0,75	6,53	8,27	8,56	8,87	9,2	9,56	9,95
3131810	2	0,8	10	45	1,2	4	0,75	5,72	10,34	10,7	11,09	11,5	11,95	12,44
3131812	2	0,8	12	45	1,2	4	0,75	5,09	12,41	12,84	13,31	13,8	14,34	14,92
3131814	2	0,8	14	50	1,2	4	0,75	4,58	14,48	14,98	15,52	16,1	16,73	17,41
3131816	2	0,8	16	50	1,2	4	0,75	4,16	16,54	17,12	17,74	18,4	19,12	19,9
3131820	2	0,8	20	55	1,2	4	0,75	3,52	20,68	21,4	22,17	23	23,9	24,87
3131824	2	0,8	24	60	1,2	4	0,75	3,06	24,81	25,68	26,6	27,6	28,68	29,84
3131904	2	0,9	4	45	1,35	4	0,85	9	4,14	4,28	4,44	4,61	4,78	4,98
3131906	2	0,9	6	45	1,35	4	0,85	7,49	6,21	6,42	6,66	6,9	7,17	7,47
3131908	2	0,9	8	45	1,35	4	0,85	6,41	8,27	8,56	8,87	9,2	9,56	9,95
3131910	2	0,9	10	45	1,35	4	0,85	5,61	10,34	10,7	11,09	11,5	11,95	12,44
3131915	2	0,9	15	50	1,35	4	0,85	4,26	15,51	16,05	16,63	17,25	17,93	18,65
3132003	2	1	3	45	1,5	4	0,95	9,89	3,11	3,21	3,33	3,46	3,59	3,74
3132004	2	1	4	45	1,5	4	0,95	8,88	4,14	4,28	4,44	4,61	4,78	4,98
3132005	2	1	5	45	1,5	4	0,95	8,05	5,17	5,35	5,55	5,75	5,98	6,22
3132006	2	1	6	45	1,5	4	0,95	7,37	6,21	6,42	6,66	6,9	7,17	7,47
3132007	2	1	7	45	1,5	4	0,95	6,79	7,24	7,49	7,76	8,05	8,37	8,71
3132008	2	1	8	45	1,5	4	0,95	6,29	8,27	8,56	8,87	9,2	9,56	9,95
3132009	2	1	9	45	1,5	4	0,95	5,86	9,31	9,63	9,98	10,35	10,76	11,19
3132010	2	1	10	45	1,5	4	0,95	5,49	10,34	10,7	11,09	11,5	11,95	12,44
3132012	2	1	12	45	1,5	4	0,95	4,87	12,41	12,84	13,31	13,8	14,34	14,92
3132014	2	1	14	50	1,5	4	0,95	4,38	14,48	14,98	15,52	16,1	16,73	17,41
3132016	2	1	16	50	1,5	4	0,95	3,97	16,54	17,12	17,74	18,4	19,12	19,9
3132018	2	1	18	55	1,5	4	0,95	3,64	18,61	19,26	19,96	20,7	21,51	22,38
3132020	2	1	20	55	1,5	4	0,95	3,35	20,68	21,4	22,17	23	23,9	24,87
3132022	2	1	22	60	1,5	4	0,95	3,11	22,75	23,54	24,39	25,3	26,29	27,36
3132025	2	1	25	60	1,5	4	0,95	2,81	25,85	26,75	27,71	28,75	29,87	-
3132030	2	1	30	70	1,5	4	0,95	2,41	31,02	32,1	33,25	34,5	-	-
3132204	2	1,2	4	45	1,8	4	1,15	8,54	4,22	4,38	4,54	4,71	4,9	5,09
3132206	2	1,2	6	45	1,8	4	1,15	7,05	6,3	6,52	6,76	7,01	7,29	7,58
3132208	2	1,2	8	45	1,8	4	1,15	6	8,37	8,66	8,98	9,31	9,67	10,07

WXL-LN-EDS

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC
- 2 flutes, long neck, square
- 199 sizes





EDP	ZEFP	DC	LU	LF	APMX	DCON	DN	θ_k	Le ($\alpha=0,5^\circ$)	Le ($\alpha=1^\circ$)	Le ($\alpha=1,5^\circ$)	Le ($\alpha=2^\circ$)	Le ($\alpha=2,5^\circ$)	Le ($\alpha=3^\circ$)
3132210	2	1,2	10	45	1,8	4	1,15	5,22	10,44	10,8	11,19	11,61	12,06	12,55
3132212	2	1,2	12	45	1,8	4	1,15	4,62	12,51	12,94	13,41	13,91	14,45	15,04
3132214	2	1,2	14	50	1,8	4	1,15	4,14	14,57	15,08	15,63	16,21	16,84	17,53
3132216	2	1,2	16	50	1,8	4	1,15	3,76	16,64	17,22	17,84	18,51	19,23	20,01
3132220	2	1,2	20	55	1,8	4	1,15	3,16	20,77	21,5	22,28	23,11	24,01	24,99
3132406	2	1,4	6	45	2,1	4	1,35	6,77	6,3	6,52	6,76	7,01	7,29	7,58
3132408	2	1,4	8	45	2,1	4	1,35	5,73	8,37	8,66	8,98	9,31	9,67	10,07
3132410	2	1,4	10	45	2,1	4	1,35	4,97	10,44	10,8	11,19	11,61	12,06	12,55
3132412	2	1,4	12	45	2,1	4	1,35	4,39	12,51	12,94	13,41	13,91	14,45	15,04
3132414	2	1,4	14	50	2,1	4	1,35	3,92	14,57	15,08	15,63	16,21	16,84	17,53
3132416	2	1,4	16	50	2,1	4	1,35	3,55	16,64	17,22	17,84	18,51	19,23	20,01
3132422	2	1,4	22	60	2,1	4	1,35	2,76	22,84	23,64	24,49	25,41	26,4	-
3132504	2	1,5	4	45	2,3	4	1,45	8,12	4,22	4,38	4,54	4,71	4,9	5,09
3132506	2	1,5	6	45	2,3	4	1,45	6,62	6,3	6,52	6,76	7,01	7,29	7,58
3132508	2	1,5	8	45	2,3	4	1,45	5,59	8,37	8,66	8,98	9,31	9,67	10,07
3132510	2	1,5	10	45	2,3	4	1,45	4,84	10,44	10,8	11,19	11,61	12,06	12,55
3132512	2	1,5	12	45	2,3	4	1,45	4,26	12,51	12,94	13,41	13,91	14,45	15,04
3132514	2	1,5	14	50	2,3	4	1,45	3,81	14,57	15,08	15,63	16,21	16,84	17,53
3132516	2	1,5	16	50	2,3	4	1,45	3,45	16,64	17,22	17,84	18,51	19,23	20,01
3132518	2	1,5	18	55	2,3	4	1,45	3,14	18,71	19,36	20,06	20,81	21,62	22,5
3132520	2	1,5	20	55	2,3	4	1,45	2,89	20,77	21,5	22,28	23,11	24,01	-
3132525	2	1,5	25	60	2,3	4	1,45	2,4	25,94	26,85	27,82	28,86	-	-
3132530	2	1,5	30	70	2,3	4	1,45	2,06	31,11	32,2	33,36	34,61	-	-
3132538	2	1,5	38	80	2,3	4	1,45	1,67	39,38	40,75	42,22	-	-	-
3132540	2	1,5	40	80	2,3	4	1,45	1,6	41,45	42,89	44,44	-	-	-
3132545	2	1,5	45	80	2,3	4	1,45	1,44	46,62	48,24	-	-	-	-
3132606	2	1,6	6	45	2,4	4	1,55	6,47	6,3	6,52	6,76	7,01	7,29	7,58
3132608	2	1,6	8	45	2,4	4	1,55	5,45	8,37	8,66	8,98	9,31	9,67	10,07
3132610	2	1,6	10	45	2,4	4	1,55	4,71	10,44	10,8	11,19	11,61	12,06	12,55
3132612	2	1,6	12	45	2,4	4	1,55	4,14	12,51	12,94	13,41	13,91	14,45	15,04
3132614	2	1,6	14	50	2,4	4	1,55	3,7	14,57	15,08	15,63	16,21	16,84	17,53
3132616	2	1,6	16	50	2,4	4	1,55	3,34	16,64	17,22	17,84	18,51	19,23	20,01
3132618	2	1,6	18	55	2,4	4	1,55	3,04	18,71	19,36	20,06	20,81	21,62	22,5
3132620	2	1,6	20	55	2,4	4	1,55	2,8	20,77	21,5	22,28	23,11	24,01	-
3132806	2	1,8	6	45	2,7	4	1,75	5,96	6,42	6,77	7,1	7,39	7,68	7,99
3132808	2	1,8	8	45	2,7	4	1,75	5,01	8,53	8,96	9,34	9,69	10,07	10,48
3132810	2	1,8	10	45	2,7	4	1,75	4,33	10,64	11,13	11,56	11,99	12,46	12,97
3132812	2	1,8	12	45	2,7	4	1,75	3,81	12,74	13,29	13,78	14,29	14,85	15,45
3132814	2	1,8	14	50	2,7	4	1,75	3,4	14,83	15,44	15,99	16,59	17,24	17,94
3132816	2	1,8	16	50	2,7	4	1,75	3,07	16,92	17,58	18,21	18,89	19,63	20,43
3132818	2	1,8	18	55	2,7	4	1,75	2,79	19,01	19,71	20,43	21,19	22,02	-
3132820	2	1,8	20	55	2,7	4	1,75	2,57	21,09	21,85	22,64	23,49	24,41	-
3132825	2	1,8	25	60	2,7	4	1,75	2,13	26,28	27,2	28,18	29,24	-	-
3133006	2	2	6	45	3	4	1,95	5,62	6,42	6,77	7,1	7,39	7,68	7,99
3133008	2	2	8	45	3	4	1,95	4,7	8,53	8,96	9,34	9,69	10,07	10,48
3133010	2	2	10	45	3	4	1,95	4,04	10,64	11,13	11,56	11,99	12,46	12,97

Milling | Solid carbide




WXL-LN-EDS

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC
- 2 flutes, long neck, square
- 199 sizes





EDP	ZEFP	DC	LU	LF	APMX	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3133012	2	2	12	45	3	4	1,95	3,54	12,74	13,29	13,78	14,29	14,85	15,45
3133014	2	2	14	50	3	4	1,95	3,15	14,83	15,44	15,99	16,59	17,24	17,94
3133016	2	2	16	50	3	4	1,95	2,84	16,92	17,58	18,21	18,89	19,63	-
3133018	2	2	18	55	3	4	1,95	2,58	19,01	19,71	20,43	21,19	22,02	-
3133020	2	2	20	55	3	4	1,95	2,37	21,09	21,85	22,64	23,49	-	-
3133025	2	2	25	60	3	4	1,95	1,96	26,28	27,2	28,18	-	-	-
3133030	2	2	30	70	3	4	1,95	1,68	31,45	32,55	33,73	-	-	-
3133035	2	2	35	80	3	4	1,95	1,46	36,62	37,9	-	-	-	-
3133040	2	2	40	90	3	4	1,95	1,3	41,79	43,25	-	-	-	-
3133050	2	2	50	100	3	4	1,95	1,06	52,13	53,94	-	-	-	-
3133060	2	2	60	110	3	4	1,95	0,89	62,46	-	-	-	-	-
3133508	2	2,5	8	45	3,7	4	2,4	3,86	8,47	8,87	9,22	9,57	9,94	10,35
3133510	2	2,5	10	45	3,7	4	2,4	3,27	10,57	11,03	11,44	11,87	12,33	12,83
3133512	2	2,5	12	45	3,7	4	2,4	2,84	12,66	13,18	13,66	14,17	14,72	-
3133514	2	2,5	14	50	3,7	4	2,4	2,51	14,75	15,32	15,88	16,47	17,11	-
3133516	2	2,5	16	55	3,7	4	2,4	2,25	16,83	17,46	18,09	18,77	-	-
3133518	2	2,5	18	55	3,7	4	2,4	2,03	18,91	19,6	20,31	21,07	-	-
3133520	2	2,5	20	60	3,7	4	2,4	1,86	20,99	21,74	22,52	-	-	-
3133525	2	2,5	25	70	3,7	4	2,4	1,53	26,17	27,09	28,07	-	-	-
3133530	2	2,5	30	80	3,7	4	2,4	1,3	31,34	32,44	-	-	-	-
3133540	2	2,5	40	90	3,7	4	2,4	1	41,68	-	-	-	-	-
3133550	2	2,5	50	100	3,7	4	2,4	0,81	52,02	-	-	-	-	-
3134008	2	3	8	45	4,5	6	2,85	6,19	8,42	8,79	9,13	9,47	9,84	10,24
3134010	2	3	10	45	4,5	6	2,85	5,41	10,51	10,95	11,35	11,77	12,23	12,73
3134012	2	3	12	45	4,5	6	2,85	4,81	12,6	13,09	13,56	14,07	14,62	15,21
3134014	2	3	14	50	4,5	6	2,85	4,32	14,68	15,23	15,78	16,37	17,01	17,7
3134016	2	3	16	55	4,5	6	2,85	3,93	16,76	17,37	18	18,67	19,4	20,18
3134018	2	3	18	55	4,5	6	2,85	3,6	18,84	19,51	20,21	20,97	21,79	22,67
3134020	2	3	20	60	4,5	6	2,85	3,32	20,91	21,65	22,43	23,27	24,18	25,16
3134025	2	3	25	65	4,5	6	2,85	2,79	26,09	27	27,97	29,02	30,15	-
3134030	2	3	30	80	4,5	6	2,85	2,4	31,25	32,34	33,51	34,77	-	-
3134035	2	3	35	90	4,5	6	2,85	2,1	36,42	37,69	39,05	40,52	-	-
3134040	2	3	40	90	4,5	6	2,85	1,87	41,59	43,04	44,6	-	-	-
3134050	2	3	50	100	4,5	6	2,85	1,54	51,93	53,74	55,68	-	-	-
3135012	2	4	12	50	6	6	3,85	3,58	12,6	13,09	13,56	14,07	14,62	15,21
3135016	2	4	16	60	6	6	3,85	2,87	16,76	17,37	18	18,67	19,4	-
3135020	2	4	20	60	6	6	3,85	2,39	20,91	21,65	22,43	23,27	-	-
3135025	2	4	25	70	6	6	3,85	1,98	26,09	27	27,97	-	-	-
3135030	2	4	30	80	6	6	3,85	1,69	31,25	32,34	33,51	-	-	-
3135035	2	4	35	90	6	6	3,85	1,47	36,42	37,69	-	-	-	-
3135040	2	4	40	90	6	6	3,85	1,3	41,59	43,04	-	-	-	-
3135045	2	4	45	100	6	6	3,85	1,17	46,76	48,39	-	-	-	-
3135050	2	4	50	100	6	6	3,85	1,06	51,93	53,74	-	-	-	-
3135060	2	4	60	110	6	6	3,85	0,9	62,26	-	-	-	-	-
3136016	2	5	16	60	7,5	6	4,85	1,58	16,76	17,37	18	-	-	-
3136020	2	5	20	70	7,5	6	4,85	1,3	20,91	21,65	-	-	-	-

Milling | Solid carbide




WXL-LN-EDS

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC
- 2 flutes, long neck, square
- 199 sizes





EDP	ZEFP	DC	LU	LF	APMX	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)
3136025	2	5	25	70	7,5	6	4,85	1,06	26,09	27	-
3136030	2	5	30	90	7,5	6	4,85	0,89	31,25	-	-
3136035	2	5	35	90	7,5	6	4,85	0,77	36,42	-	-
3136040	2	5	40	100	7,5	6	4,85	0,68	41,59	-	-
3136050	2	5	50	110	7,5	6	4,85	0,55	51,93	-	-
3136060	2	5	60	120	7,5	6	4,85	0,46	-	-	-
3137020	2	6	20	80	9	6	5,85	-	-	-	-
3137030	2	6	30	90	9	6	5,85	-	-	-	-
3137040	2	6	40	100	9	6	5,85	-	-	-	-
3137050	2	6	50	110	9	6	5,85	-	-	-	-
3137060	2	6	60	120	9	6	5,85	-	-	-	-
3138040	2	8	40	110	12	8	7,85	-	-	-	-
3139050	2	10	50	125	15	10	9,85	-	-	-	-
3140060	2	12	60	140	18	12	11,9	-	-	-	-

Milling | Solid carbide




WXL-CR-EDS-6

Milling | Solid carbide



- Carbide end mill with WXL coating
- For general applications
- 2 flutes, corner radius
- Shank diameter 6

Material compatibility icons: P (~45 HRC), P (~55 HRC), M (~35 HRC), K (~350 HB), N, S, H (~60 HRC).



Properties: CARBIDE, WXL coating, 30° angle, SHRINK FIT, 0~-0.015 tolerance, P.57 grade.



EDP	ZEFP	DC	RE	LU	LF	APMX	DCON	DN	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
48144060	2	0,6	0,1	1,8	50	0,9	6	0,55	1,86	1,92	1,99	2,07	2,15	2,23
48144080	2	0,8	0,1	2,4	50	1,2	6	0,75	2,48	2,56	2,66	2,76	2,86	2,98
48144100	2	1	0,1	2,5	50	1,5	6	0,95	2,58	2,67	2,77	2,85	2,98	3,1
48144120	2	1,2	0,1	3	50	1,8	6	1,15	3,1	3,2	3,32	3,45	3,58	3,72
48144150	2	1,5	0,1	3,8	50	2,3	6	1,45	3,92	4,06	4,21	4,36	4,54	4,72
48144180	2	1,8	0,1	4,5	50	2,7	6	1,75	4,62	4,81	4,98	5,17	5,37	5,59
48144200	2	2	0,1	5	50	3	6	1,95	5,16	5,34	5,54	5,74	5,97	6,21
48144250	2	2,5	0,1	5	50	3,7	6	2,4	5,16	5,34	5,54	5,74	5,97	6,21

Milling | Solid carbide



WXL-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For high speed milling in steels, stainless and cast iron
- 2 flutes, ball nose





EDP	ZEFP	DC	RE	LF	APMX	DCON
3105010	2	0,1	0,05	40	0,2	4
3105020	2	0,2	0,1	40	0,4	4
3105030	2	0,3	0,15	40	0,6	4
3106030	2	0,3	0,15	50	0,6	6
3105040	2	0,4	0,2	40	0,8	4
3106040	2	0,4	0,2	50	0,8	6
3105050	2	0,5	0,25	40	1,1	4
3106050	2	0,5	0,25	50	1,1	6
3105060	2	0,6	0,3	40	1,1	4
3106060	2	0,6	0,3	50	1,1	6
3106710	2	0,7	0,35	40	1,5	4
3105080	2	0,8	0,4	40	2	4
3106080	2	0,8	0,4	50	2	6
3106720	2	0,9	0,45	50	2,2	4
3105100	2	1	0,5	50	1,5	4
3105101	2	1	0,5	50	2,5	4
3106100	2	1	0,5	60	2,5	6
3106730	2	1,1	0,55	50	2,7	4
3105120	2	1,2	0,6	50	3	4
3106740	2	1,3	0,65	50	3,2	4
3105140	2	1,4	0,7	50	3,5	4
3105150	2	1,5	0,75	50	2	4
3105151	2	1,5	0,75	50	4	4
3106150	2	1,5	0,75	50	4	6
3105160	2	1,6	0,8	50	4	4
3106750	2	1,7	0,85	50	4,2	4
3106760	2	1,8	0,9	50	4,5	4
3106770	2	1,9	0,95	50	4,7	4
3105200	2	2	1	50	3	4
3105201	2	2	1	50	6	4
3106200	2	2	1	50	5	6
3106780	2	2,1	1,05	50	4,8	6
3106790	2	2,2	1,1	50	4,9	6
3106800	2	2,3	1,15	50	5	6
3106810	2	2,4	1,2	50	5,1	6
3105250	2	2,5	1,25	50	3	4
3105251	2	2,5	1,25	50	6	4
3106250	2	2,5	1,25	60	6	6
3106820	2	2,6	1,3	50	5,2	6
3106830	2	2,7	1,35	50	5,4	6
3106840	2	2,8	1,4	60	5,6	6
3106850	2	2,9	1,45	60	5,8	6
3105300	2	3	1,5	60	4,5	4
3106300	2	3	1,5	60	4,5	6
3106301	2	3	1,5	60	8	6
3106350	2	3,5	1,75	70	8	6

Milling | Solid carbide



WXL-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For high speed milling in steels, stainless and cast iron
- 2 flutes, ball nose





EDP	ZEFP	DC	RE	LF	APMX	DCON
3105400	2	4	2	60	8	4
3106400	2	4	2	70	6	6
3106401	2	4	2	70	8	6
3106860	2	4,5	2,25	80	8	6
3106500	2	5	2,5	80	8	6
3106501	2	5	2,5	80	10	6
3106502	2	5	2,5	80	12	6
3106870	2	5,5	2,75	80	10	6
3106600	2	6	3	90	10	6
3106601	2	6	3	90	12	6
3106880	2	6,5	3,25	90	13	6
3106610	2	7	3,5	90	14	6
3106890	2	7,5	3,75	90	14	6
3106620	2	8	4	100	12	8
3106621	2	8	4	100	14	8
3106900	2	8,5	4,25	100	16	8
3106630	2	9	4,5	100	18	8
3106910	2	9,5	4,75	100	18	8
3106640	2	10	5	100	15	10
3106641	2	10	5	100	18	10
3106650	2	11	5,5	100	22	10
3106660	2	12	6	110	18	12
3106661	2	12	6	110	22	12
3106920	2	13	6,5	110	24	12
3106670	2	14	7	110	26	12
3106930	2	15	7,5	110	28	12
3106680	2	16	8	140	30	16
3106690	2	18	9	140	34	16
3106700	2	20	10	160	38	20

Milling | Solid carbide




WXL-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC and stainless
- 2 flutes, long neck, ball nose
- 284 sizes





EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3110103	2	0,1	0,05	0,3	45	0,08	7,5	4	0,085	14,46	0,34	0,35	0,36	0,37	0,38	0,4
3110105	2	0,1	0,05	0,5	45	0,08	7,7	4	0,085	14,1	0,54	0,56	0,58	0,6	0,62	0,64
3110203	2	0,2	0,1	0,3	45	0,16	7,3	4	0,18	14,59	0,3	0,31	0,32	0,33	0,34	0,35
3110205	2	0,2	0,1	0,5	45	0,16	7,5	4	0,18	14,44	0,53	0,55	0,57	0,59	0,61	0,63
3120205	2	0,2	0,1	0,5	50	0,16	11,3	6	0,18	14,16	0,53	0,55	0,57	0,59	0,61	0,63
3110207	2	0,2	0,1	0,75	45	0,16	7,8	4	0,18	13,72	0,79	0,82	0,85	0,88	0,91	0,94
3110210	2	0,2	0,1	1	45	0,16	8	4	0,18	13,31	1,05	1,09	1,13	1,17	1,21	1,26
3120210	2	0,2	0,1	1	50	0,16	11,8	6	0,18	13,85	1,05	1,09	1,13	1,17	1,21	1,26
3110212	2	0,2	0,1	1,25	45	0,16	8,3	4	0,18	12,92	1,31	1,36	1,41	1,46	1,51	1,57
3110215	2	0,2	0,1	1,5	45	0,16	8,5	4	0,18	12,56	1,57	1,63	1,68	1,74	1,81	1,88
3120215	2	0,2	0,1	1,5	50	0,16	12,3	6	0,18	13,3	1,57	1,63	1,68	1,74	1,81	1,88
3110217	2	0,2	0,1	1,75	45	0,16	8,8	4	0,18	12,21	1,83	1,9	1,96	2,03	2,11	2,19
3110220	2	0,2	0,1	2	45	0,16	9	4	0,18	11,88	2,09	2,16	2,24	2,32	2,4	2,5
3120220	2	0,2	0,1	2	50	0,16	12,8	6	0,18	12,8	2,09	2,16	2,24	2,32	2,4	2,5
3110225	2	0,2	0,1	2,5	45	0,16	9,5	4	0,18	11,28	2,61	2,7	2,79	2,89	3	3,12
3110230	2	0,2	0,1	3	45	0,16	10	4	0,18	10,73	3,13	3,23	3,35	3,47	3,6	3,74
3110305	2	0,3	0,15	0,5	45	0,24	7,3	4	0,28	14,22	0,52	0,54	0,56	0,58	0,6	0,62
3110306	2	0,3	0,15	0,6	45	0,24	7,4	4	0,28	14,03	0,63	0,65	0,68	0,7	0,72	0,75
3110307	2	0,3	0,15	0,75	45	0,24	7,6	4	0,28	13,77	0,79	0,82	0,85	0,87	0,9	0,93
3110310	2	0,3	0,15	1	45	0,24	7,8	4	0,28	13,34	1,05	1,09	1,12	1,16	1,2	1,24
3120310	2	0,3	0,15	1	50	0,24	11,6	6	0,28	13,88	1,05	1,09	1,12	1,16	1,2	1,24
3110312	2	0,3	0,15	1,25	45	0,24	8,1	4	0,28	12,94	1,31	1,36	1,4	1,45	1,5	1,55
3110315	2	0,3	0,15	1,5	45	0,24	8,3	4	0,28	12,57	1,57	1,63	1,68	1,74	1,8	1,87
3120315	2	0,3	0,15	1,5	50	0,24	12,1	6	0,28	13,33	1,57	1,63	1,68	1,74	1,8	1,87
3110317	2	0,3	0,15	1,75	45	0,24	8,6	4	0,28	12,21	1,83	1,89	1,96	2,02	2,1	2,18
3110320	2	0,3	0,15	2	45	0,24	8,8	4	0,28	11,87	2,09	2,16	2,23	2,31	2,4	2,49
3120320	2	0,3	0,15	2	50	0,24	12,6	6	0,28	12,81	2,09	2,16	2,23	2,31	2,4	2,49
3110322	2	0,3	0,15	2,25	45	0,24	9,1	4	0,28	11,56	2,35	2,43	2,51	2,6	2,69	2,8
3110325	2	0,3	0,15	2,5	45	0,24	9,3	4	0,28	11,25	2,61	2,69	2,79	2,89	2,99	3,11
3120325	2	0,3	0,15	2,5	50	0,24	13,1	6	0,28	12,34	2,61	2,69	2,79	2,89	2,99	3,11
3110327	2	0,3	0,15	2,75	45	0,24	9,6	4	0,28	10,97	2,87	2,96	3,06	3,17	3,29	3,42
3110330	2	0,3	0,15	3	45	0,24	9,8	4	0,28	10,69	3,13	3,23	3,34	3,46	3,59	3,73
3120330	2	0,3	0,15	3	50	0,24	13,6	6	0,28	11,89	3,13	3,23	3,34	3,46	3,59	3,73
3110335	2	0,3	0,15	3,5	45	0,24	10,3	4	0,28	10,19	3,64	3,76	3,9	4,04	4,19	4,35
3110340	2	0,3	0,15	4	45	0,24	10,8	4	0,28	9,72	4,16	4,3	4,45	4,61	4,78	4,97
3110345	2	0,3	0,15	4,5	45	0,24	11,3	4	0,28	9,3	4,68	4,83	5	5,19	5,38	5,59
3110350	2	0,3	0,15	5	45	0,24	11,8	4	0,28	8,91	5,19	5,37	5,56	5,76	5,98	6,22
3110405	2	0,4	0,2	0,5	45	0,3	7,1	4	0,37	14,3	0,52	0,53	0,55	0,56	0,58	0,6
3110407	2	0,4	0,2	0,75	45	0,3	7,4	4	0,37	13,83	0,78	0,8	0,83	0,85	0,88	0,91
3110410	2	0,4	0,2	1	45	0,3	7,6	4	0,37	13,39	1,04	1,07	1,11	1,14	1,18	1,22
3120410	2	0,4	0,2	1	50	0,3	11,4	6	0,37	13,93	1,04	1,07	1,11	1,14	1,18	1,22
3110415	2	0,4	0,2	1,5	45	0,3	8,1	4	0,37	12,59	1,56	1,61	1,66	1,72	1,77	1,84
3120415	2	0,4	0,2	1,5	50	0,3	11,9	6	0,37	13,36	1,56	1,61	1,66	1,72	1,77	1,84
3110420	2	0,4	0,2	2	45	0,3	8,6	4	0,37	11,88	2,08	2,14	2,21	2,29	2,37	2,46
3120420	2	0,4	0,2	2	50	0,3	12,4	6	0,37	12,83	2,08	2,14	2,21	2,29	2,37	2,46
3110425	2	0,4	0,2	2,5	45	0,3	9,1	4	0,37	11,24	2,6	2,68	2,77	2,87	2,97	3,08

Milling | Solid carbide




WXL-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC and stainless
- 2 flutes, long neck, ball nose
- 284 sizes





EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3120425	2	0,4	0,2	2,5	50	0,3	12,9	6	0,37	12,35	2,6	2,68	2,77	2,87	2,97	3,08
3110430	2	0,4	0,2	3	45	0,3	9,6	4	0,37	10,67	3,11	3,21	3,32	3,44	3,57	3,7
3120430	2	0,4	0,2	3	50	0,3	13,4	6	0,37	11,9	3,11	3,21	3,32	3,44	3,57	3,7
3110435	2	0,4	0,2	3,5	45	0,3	10,1	4	0,37	10,15	3,63	3,75	3,88	4,02	4,16	4,33
3110440	2	0,4	0,2	4	45	0,3	10,6	4	0,37	9,68	4,15	4,28	4,43	4,59	4,76	4,95
3120440	2	0,4	0,2	4	50	0,3	14,4	6	0,37	11,09	4,15	4,28	4,43	4,59	4,76	4,95
3110445	2	0,4	0,2	4,5	45	0,3	11,1	4	0,37	9,25	4,66	4,82	4,99	5,17	5,36	5,57
3110450	2	0,4	0,2	5	45	0,3	11,6	4	0,37	8,86	5,18	5,35	5,54	5,74	5,96	6,19
3120450	2	0,4	0,2	5	50	0,3	15,4	6	0,37	10,38	5,18	5,35	5,54	5,74	5,96	6,19
3110455	2	0,4	0,2	5,5	45	0,3	12,1	4	0,37	8,5	5,7	5,89	6,09	6,32	6,55	6,81
3110460	2	0,4	0,2	6	45	0,3	12,6	4	0,37	8,16	6,21	6,42	6,65	6,89	7,15	7,43
3120460	2	0,4	0,2	6	50	0,3	16,4	6	0,37	9,76	6,21	6,42	6,65	6,89	7,15	7,43
3110510	2	0,5	0,25	1	45	0,4	7,6	4	0,45	13,45	1,03	1,06	1,09	1,12	1,15	1,19
3110515	2	0,5	0,25	1,5	45	0,4	8,1	4	0,45	12,62	1,55	1,59	1,64	1,69	1,75	1,81
3120515	2	0,5	0,25	1,5	50	0,4	11,9	6	0,45	13,4	1,55	1,59	1,64	1,69	1,75	1,81
3110520	2	0,5	0,25	2	45	0,4	8,6	4	0,45	11,89	2,06	2,13	2,2	2,27	2,35	2,43
3120520	2	0,5	0,25	2	50	0,4	12,4	6	0,45	12,86	2,06	2,13	2,2	2,27	2,35	2,43
3110525	2	0,5	0,25	2,5	45	0,4	9,1	4	0,45	11,23	2,58	2,66	2,75	2,84	2,94	3,05
3120525	2	0,5	0,25	2,5	50	0,4	12,9	6	0,45	12,36	2,58	2,66	2,75	2,84	2,94	3,05
3110530	2	0,5	0,25	3	45	0,4	9,6	4	0,45	10,65	3,1	3,2	3,3	3,42	3,54	3,68
3120530	2	0,5	0,25	3	50	0,4	13,4	6	0,45	11,9	3,1	3,2	3,3	3,42	3,54	3,68
3110535	2	0,5	0,25	3,5	45	0,4	10,1	4	0,45	10,12	3,61	3,73	3,86	3,99	4,14	4,3
3110540	2	0,5	0,25	4	45	0,4	10,6	4	0,45	9,64	4,13	4,27	4,41	4,57	4,74	4,92
3120540	2	0,5	0,25	4	50	0,4	14,4	6	0,45	11,08	4,13	4,27	4,41	4,57	4,74	4,92
3110545	2	0,5	0,25	4,5	45	0,4	11,1	4	0,45	9,2	4,65	4,8	4,97	5,14	5,33	5,54
3110550	2	0,5	0,25	5	45	0,4	11,6	4	0,45	8,8	5,17	5,34	5,52	5,72	5,93	6,16
3120550	2	0,5	0,25	5	50	0,4	15,4	6	0,45	10,36	5,17	5,34	5,52	5,72	5,93	6,16
3110555	2	0,5	0,25	5,5	45	0,4	12,1	4	0,45	8,43	5,68	5,87	6,07	6,29	6,53	6,78
3110560	2	0,5	0,25	6	45	0,4	12,6	4	0,45	8,1	6,2	6,41	6,63	6,87	7,13	7,41
3120560	2	0,5	0,25	6	50	0,4	16,4	6	0,45	9,73	6,2	6,41	6,63	6,87	7,13	7,41
3110570	2	0,5	0,25	7	45	0,4	13,6	4	0,45	7,49	7,23	7,48	7,74	8,02	8,32	8,65
3110580	2	0,5	0,25	8	45	0,4	14,6	4	0,45	6,98	8,27	8,55	8,85	9,17	9,52	9,89
3120580	2	0,5	0,25	8	50	0,4	18,4	6	0,45	8,67	8,27	8,55	8,85	9,17	9,52	9,89
3110590	2	0,5	0,25	9	45	0,4	15,6	4	0,45	6,52	9,3	9,62	9,95	10,32	10,71	11,14
3110600	2	0,5	0,25	10	45	0,4	16,6	4	0,45	6,13	10,33	10,68	11,06	11,47	11,9	12,38
3110610	2	0,6	0,3	1	45	0,5	7,4	4	0,55	13,49	1,03	1,05	1,08	1,11	1,14	1,18
3110615	2	0,6	0,3	1,5	45	0,5	7,9	4	0,55	12,64	1,55	1,59	1,64	1,69	1,74	1,8
3120615	2	0,6	0,3	1,5	50	0,5	11,7	6	0,55	13,42	1,55	1,59	1,64	1,69	1,74	1,8
3110620	2	0,6	0,3	2	45	0,5	8,4	4	0,55	11,88	2,06	2,12	2,19	2,26	2,34	2,42
3120620	2	0,6	0,3	2	50	0,5	12,2	6	0,55	12,87	2,06	2,12	2,19	2,26	2,34	2,42
3110625	2	0,6	0,3	2,5	45	0,5	8,9	4	0,55	11,21	2,58	2,66	2,74	2,84	2,94	3,04
3120625	2	0,6	0,3	2,5	50	0,5	12,7	6	0,55	12,37	2,58	2,66	2,74	2,84	2,94	3,04
3110630	2	0,6	0,3	3	45	0,5	9,4	4	0,55	10,61	3,1	3,19	3,3	3,41	3,53	3,66
3120630	2	0,6	0,3	3	50	0,5	13,2	6	0,55	11,9	3,1	3,19	3,3	3,41	3,53	3,66
3110635	2	0,6	0,3	3,5	45	0,5	9,9	4	0,55	10,07	3,61	3,73	3,85	3,99	4,13	4,29
3110640	2	0,6	0,3	4	45	0,5	10,4	4	0,55	9,58	4,13	4,26	4,41	4,56	4,73	4,91

Milling | Solid carbide




WXL-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC and stainless
- 2 flutes, long neck, ball nose
- 284 sizes





EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3120640	2	0,6	0,3	4	50	0,5	14,2	6	0,55	11,06	4,13	4,26	4,41	4,56	4,73	4,91
3110645	2	0,6	0,3	4,5	45	0,5	10,9	4	0,55	9,13	4,65	4,8	4,96	5,14	5,32	5,53
3110650	2	0,6	0,3	5	45	0,5	11,4	4	0,55	8,73	5,16	5,33	5,51	5,71	5,92	6,15
3120650	2	0,6	0,3	5	50	0,5	15,2	6	0,55	10,33	5,16	5,33	5,51	5,71	5,92	6,15
3110655	2	0,6	0,3	5,5	45	0,5	11,9	4	0,55	8,36	5,68	5,87	6,07	6,29	6,52	6,77
3110660	2	0,6	0,3	6	45	0,5	12,4	4	0,55	8,02	6,2	6,4	6,62	6,86	7,12	7,39
3120660	2	0,6	0,3	6	50	0,5	16,2	6	0,55	9,69	6,2	6,4	6,62	6,86	7,12	7,39
3110665	2	0,6	0,3	6,5	45	0,5	12,9	4	0,55	7,7	6,71	6,94	7,18	7,44	7,71	8,02
3110670	2	0,6	0,3	7	45	0,5	13,4	4	0,55	7,41	7,23	7,47	7,73	8,01	8,31	8,64
3110675	2	0,6	0,3	7,5	45	0,5	13,9	4	0,55	7,14	7,75	8,01	8,29	8,59	8,91	9,26
3110680	2	0,6	0,3	8	45	0,5	14,4	4	0,55	6,89	8,26	8,54	8,84	9,16	9,51	9,88
3120680	2	0,6	0,3	8	50	0,5	18,2	6	0,55	8,62	8,26	8,54	8,84	9,16	9,51	9,88
3110685	2	0,6	0,3	8,5	45	0,5	14,9	4	0,55	6,66	8,78	9,08	9,39	9,74	10,1	10,5
3110690	2	0,6	0,3	9	45	0,5	15,4	4	0,55	6,44	9,3	9,61	9,95	10,31	10,7	11,12
3110695	2	0,6	0,3	9,5	45	0,5	15,9	4	0,55	6,23	9,81	10,15	10,5	10,89	11,3	11,75
3110700	2	0,6	0,3	10	45	0,5	16,4	4	0,55	6,04	10,33	10,68	11,06	11,46	11,9	12,37
3120700	2	0,6	0,3	10	50	0,5	20,2	6	0,55	7,76	10,33	10,68	11,06	11,46	11,9	12,37
3110711	2	0,6	0,3	11	45	0,5	17,4	4	0,55	5,69	11,37	11,75	12,16	12,61	13,09	13,61
3110712	2	0,6	0,3	12	45	0,5	18,4	4	0,55	5,38	12,4	12,82	13,27	13,76	14,28	14,85
3110820	2	0,8	0,4	2	45	0,6	8,1	4	0,75	11,86	2,06	2,12	2,18	2,25	2,32	2,4
3120820	2	0,8	0,4	2	50	0,6	11,8	6	0,75	12,9	2,06	2,12	2,18	2,25	2,32	2,4
3110830	2	0,8	0,4	3	45	0,6	9,1	4	0,75	10,52	3,09	3,19	3,29	3,4	3,51	3,64
3120830	2	0,8	0,4	3	50	0,6	12,8	6	0,75	11,89	3,09	3,19	3,29	3,4	3,51	3,64
3110840	2	0,8	0,4	4	45	0,6	10,1	4	0,75	9,45	4,13	4,26	4,4	4,55	4,71	4,88
3120840	2	0,8	0,4	4	50	0,6	13,8	6	0,75	11,02	4,13	4,26	4,4	4,55	4,71	4,88
3110850	2	0,8	0,4	5	45	0,6	11,1	4	0,75	8,58	5,16	5,33	5,5	5,7	5,9	6,13
3120850	2	0,8	0,4	5	50	0,6	14,8	6	0,75	10,27	5,16	5,33	5,5	5,7	5,9	6,13
3110860	2	0,8	0,4	6	45	0,6	12,1	4	0,75	7,85	6,19	6,4	6,61	6,85	7,1	7,37
3120860	2	0,8	0,4	6	50	0,6	15,8	6	0,75	9,62	6,19	6,4	6,61	6,85	7,1	7,37
3110870	2	0,8	0,4	7	45	0,6	13,1	4	0,75	7,24	7,23	7,47	7,72	8	8,29	8,61
3110880	2	0,8	0,4	8	45	0,6	14,1	4	0,75	6,71	8,26	8,54	8,83	9,15	9,49	9,86
3120880	2	0,8	0,4	8	50	0,6	17,8	6	0,75	8,53	8,26	8,54	8,83	9,15	9,49	9,86
3110890	2	0,8	0,4	9	45	0,6	15,1	4	0,75	6,25	9,29	9,6	9,94	10,3	10,68	11,1
3110900	2	0,8	0,4	10	45	0,6	16,1	4	0,75	5,86	10,33	10,67	11,05	11,45	11,88	12,34
3120900	2	0,8	0,4	10	50	0,6	19,8	6	0,75	7,66	10,33	10,67	11,05	11,45	11,88	12,34
3110912	2	0,8	0,4	12	45	0,6	18,1	4	0,75	5,2	12,4	12,81	13,26	13,75	14,27	14,83
3111025	2	1	0,5	2,5	45	0,8	8,2	4	0,95	11,09	2,57	2,64	2,72	2,81	2,9	3
3111030	2	1	0,5	3	45	0,8	8,7	4	0,95	10,43	3,09	3,18	3,28	3,38	3,49	3,62
3121030	2	1	0,5	3	50	0,8	12,4	6	0,95	11,88	3,09	3,18	3,28	3,38	3,49	3,62
3111040	2	1	0,5	4	45	0,8	9,7	4	0,95	9,32	4,12	4,25	4,39	4,53	4,69	4,86
3121040	2	1	0,5	4	50	0,8	13,4	6	0,95	10,98	4,12	4,25	4,39	4,53	4,69	4,86
3111050	2	1	0,5	5	45	0,8	10,7	4	0,95	8,41	5,16	5,32	5,49	5,68	5,88	6,1
3121050	2	1	0,5	5	50	0,8	14,4	6	0,95	10,21	5,16	5,32	5,49	5,68	5,88	6,1
3111060	2	1	0,5	6	45	0,8	11,7	4	0,95	7,67	6,19	6,39	6,6	6,83	7,08	7,35
3121060	2	1	0,5	6	50	0,8	15,4	6	0,95	9,54	6,19	6,39	6,6	6,83	7,08	7,35
3111070	2	1	0,5	7	45	0,8	12,7	4	0,95	7,05	7,22	7,46	7,71	7,98	8,27	8,59

Milling | Solid carbide




WXL-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC and stainless
- 2 flutes, long neck, ball nose
- 284 sizes





EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3121070	2	1	0,5	7	50	0,8	16,4	6	0,95	8,95	7,22	7,46	7,71	7,98	8,27	8,59
3111080	2	1	0,5	8	45	0,8	13,7	4	0,95	6,52	8,26	8,53	8,82	9,13	9,47	9,83
3121080	2	1	0,5	8	50	0,8	17,4	6	0,95	8,43	8,26	8,53	8,82	9,13	9,47	9,83
3111090	2	1	0,5	9	45	0,8	14,7	4	0,95	6,06	9,29	9,6	9,93	10,28	10,66	11,08
3111100	2	1	0,5	10	45	0,8	15,7	4	0,95	5,66	10,33	10,67	11,04	11,43	11,86	12,32
3121100	2	1	0,5	10	50	0,8	19,4	6	0,95	7,55	10,33	10,67	11,04	11,43	11,86	12,32
3111112	2	1	0,5	12	45	0,8	17,7	4	0,95	5,01	12,39	12,81	13,25	13,73	14,25	14,81
3121112	2	1	0,5	12	50	0,8	21,4	6	0,95	6,83	12,39	12,81	13,25	13,73	14,25	14,81
3111114	2	1	0,5	14	50	0,8	19,7	4	0,95	4,49	14,46	14,95	15,47	16,03	16,64	17,29
3121114	2	1	0,5	14	60	0,8	23,4	6	0,95	6,24	14,46	14,95	15,47	16,03	16,64	17,29
3111116	2	1	0,5	16	50	0,8	21,7	4	0,95	4,06	16,53	17,09	17,69	18,33	19,03	19,78
3121116	2	1	0,5	16	60	0,8	25,4	6	0,95	5,74	16,53	17,09	17,69	18,33	19,03	19,78
3111118	2	1	0,5	18	55	0,8	23,7	4	0,95	3,71	18,59	19,23	19,9	20,63	21,41	22,26
3111120	2	1	0,5	20	55	0,8	25,7	4	0,95	4,95	20,66	21,36	22,12	22,93	23,8	24,75
3121120	2	1	0,5	20	60	0,8	29,4	6	0,95	3,42	20,66	21,36	22,12	22,93	23,8	24,75
3121122	2	1	0,5	22	60	0,8	31,4	6	0,95	4,63	22,73	23,5	24,33	25,23	26,19	27,24
3111240	2	1,2	0,6	4	45	1	9,4	4	1,15	9,07	4,19	4,34	4,48	4,62	4,78	4,95
3111260	2	1,2	0,6	6	45	1	11,4	4	1,15	7,41	6,27	6,48	6,69	6,92	7,17	7,44
3121260	2	1,2	0,6	6	50	1	15,2	6	1,15	9,4	6,27	6,48	6,69	6,92	7,17	7,44
3111280	2	1,2	0,6	8	45	1	13,4	4	1,15	6,26	8,35	8,62	8,91	9,22	9,56	9,93
3121280	2	1,2	0,6	8	50	1	17,1	6	1,15	8,28	8,35	8,62	8,91	9,22	9,56	9,93
3111300	2	1,2	0,6	10	45	1	15,4	4	1,15	5,42	10,42	10,76	11,13	11,52	11,95	12,41
3121300	2	1,2	0,6	10	50	1	19,2	6	1,15	7,39	10,42	10,76	11,13	11,52	11,95	12,41
3111312	2	1,2	0,6	12	45	1	17,4	4	1,15	4,78	12,49	12,9	13,34	13,82	14,34	14,9
3121312	2	1,2	0,6	12	50	1	21,2	6	1,15	6,68	12,49	12,9	13,34	13,82	14,34	14,9
3111314	2	1,2	0,6	14	50	1	19,4	4	1,15	4,27	14,55	15,04	15,56	16,12	16,73	17,38
3111316	2	1,2	0,6	16	50	1	21,4	4	1,15	3,86	16,62	17,18	17,78	18,42	19,12	19,87
3121316	2	1,2	0,6	16	60	1	25,2	6	1,15	5,6	16,62	17,18	17,78	18,42	19,12	19,87
3111318	2	1,2	0,6	18	55	1	23,4	4	1,15	3,52	18,69	19,32	19,99	20,72	21,51	22,36
3111320	2	1,2	0,6	20	60	1	25,4	4	1,15	3,24	20,75	21,46	22,21	23,02	23,9	24,84
3111324	2	1,2	0,6	24	60	1	29,4	4	1,15	2,79	24,89	25,74	26,64	27,62	28,68	-
3111480	2	1,4	0,7	8	45	1,1	13,1	4	1,35	6,04	8,35	8,61	8,9	9,21	9,54	9,9
3111512	2	1,4	0,7	12	45	1,1	17,1	4	1,35	4,57	12,48	12,89	13,33	13,81	14,32	14,87
3111516	2	1,4	0,7	16	50	1,1	21,1	4	1,35	3,67	16,62	17,17	17,77	18,41	19,1	19,85
3111530	2	1,5	0,75	3	45	1,2	7,9	4	1,45	10,01	3,13	3,25	3,35	3,45	3,56	3,67
3111540	2	1,5	0,75	4	45	1,2	8,9	4	1,45	8,8	4,18	4,33	4,46	4,6	4,75	4,92
3111560	2	1,5	0,75	6	45	1,2	10,9	4	1,45	7,08	6,27	6,47	6,68	6,9	7,14	7,4
3121560	2	1,5	0,75	6	50	1,2	14,6	6	1,45	9,26	6,27	6,47	6,68	6,9	7,14	7,4
3111580	2	1,5	0,75	8	45	1,2	12,9	4	1,45	5,92	8,34	8,61	8,9	9,2	9,53	9,89
3121580	2	1,5	0,75	8	50	1,2	16,6	6	1,45	8,11	8,34	8,61	8,9	9,2	9,53	9,89
3111600	2	1,5	0,75	10	45	1,2	14,9	4	1,45	5,09	10,41	10,75	11,11	11,5	11,92	12,38
3121600	2	1,5	0,75	10	50	1,2	18,6	6	1,45	7,21	10,41	10,75	11,11	11,5	11,92	12,38
3111612	2	1,5	0,75	12	45	1,2	16,9	4	1,45	4,46	12,48	12,89	13,33	13,8	14,31	14,86
3121612	2	1,5	0,75	12	50	1,2	20,6	6	1,45	6,49	12,48	12,89	13,33	13,8	14,31	14,86
3111614	2	1,5	0,75	14	50	1,2	18,9	4	1,45	3,96	14,55	15,03	15,55	16,1	16,7	17,35
3111616	2	1,5	0,75	16	55	1,2	20,9	4	1,45	3,57	16,62	17,17	17,76	18,4	19,09	19,83

Milling | Solid carbide




WXL-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC and stainless
- 2 flutes, long neck, ball nose
- 284 sizes





EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3121616	2	1,5	0,75	16	60	1,2	24,6	6	1,45	5,4	16,62	17,17	17,76	18,4	19,09	19,83
3111618	2	1,5	0,75	18	55	1,2	22,9	4	1,45	3,25	18,68	19,31	19,98	20,7	21,48	22,32
3111620	2	1,5	0,75	20	55	1,2	24,9	4	1,45	2,98	20,75	21,45	22,19	23	23,87	-
3121620	2	1,5	0,75	20	60	1,2	28,6	6	1,45	4,63	20,75	21,45	22,19	23	23,87	24,81
3111622	2	1,5	0,75	22	55	1,2	26,9	4	1,45	2,75	22,82	23,59	24,41	25,3	26,26	-
3111630	2	1,5	0,75	30	65	1,2	34,9	4	1,45	2,1	31,09	32,14	33,28	34,5	-	-
3111640	2	1,6	0,8	4	45	1,3	8,7	4	1,55	8,7	4,18	4,33	4,46	4,59	4,74	4,91
3111680	2	1,6	0,8	8	45	1,3	12,7	4	1,55	5,8	8,34	8,61	8,89	9,19	9,52	9,88
3111712	2	1,6	0,8	12	45	1,3	16,7	4	1,55	4,34	12,48	12,89	13,32	13,79	14,3	14,85
3111716	2	1,6	0,8	16	50	1,3	20,7	4	1,55	3,47	16,61	17,16	17,76	18,39	19,08	19,82
3111720	2	1,6	0,8	20	55	1,3	24,7	4	1,55	2,89	20,75	21,44	22,19	22,99	23,86	-
3111880	2	1,8	0,9	8	45	1,4	12,6	4	1,75	5,38	8,48	8,88	9,23	9,56	9,9	10,27
3111912	2	1,8	0,9	12	45	1,4	16,6	4	1,75	4,02	12,69	13,22	13,68	14,16	14,68	15,24
3111916	2	1,8	0,9	16	50	1,4	20,6	4	1,75	3,2	16,88	17,51	18,11	18,76	19,46	20,21
3111920	2	1,8	0,9	20	55	1,4	24,6	4	1,75	2,66	21,05	21,79	22,55	23,36	24,24	-
3112030	2	2	1	3	45	1,5	7,3	4	1,95	9,1	3,16	3,31	3,47	3,64	3,8	3,96
3112040	2	2	1	4	45	1,6	8,3	4	1,95	7,87	4,23	4,44	4,66	4,86	5,06	5,26
3122040	2	2	1	4	50	1,6	12	6	1,95	10,32	4,23	4,44	4,66	4,86	5,06	5,26
3112060	2	2	1	6	45	1,6	10,3	4	1,95	6,19	6,36	6,67	6,96	7,23	7,49	7,76
3122060	2	2	1	6	50	1,6	14	6	1,95	8,77	6,36	6,67	6,96	7,23	7,49	7,76
3112080	2	2	1	8	45	1,6	12,3	4	1,95	5,1	8,48	8,87	9,22	9,55	9,88	10,24
3122080	2	2	1	8	50	1,6	16	6	1,95	7,61	8,48	8,87	9,22	9,55	9,88	10,24
3112100	2	2	1	10	45	1,6	14,3	4	1,95	4,33	10,59	11,05	11,45	11,85	12,27	12,73
3122100	2	2	1	10	50	1,6	18	6	1,95	6,73	10,59	11,05	11,45	11,85	12,27	12,73
3112112	2	2	1	12	45	1,6	16,3	4	1,95	3,77	12,69	13,21	13,67	14,15	14,66	15,22
3122112	2	2	1	12	50	1,6	20	6	1,95	6,03	12,69	13,21	13,67	14,15	14,66	15,22
3112114	2	2	1	14	50	1,6	18,3	4	1,95	3,33	14,78	15,36	15,89	16,45	17,05	17,7
3112116	2	2	1	16	50	1,6	20,3	4	1,95	2,98	16,88	17,51	18,1	18,75	19,44	-
3122116	2	2	1	16	60	1,6	24	6	1,95	4,98	16,88	17,51	18,1	18,75	19,44	20,19
3112118	2	2	1	18	55	1,6	22,3	4	1,95	2,7	18,96	19,65	20,32	21,04	21,83	-
3112120	2	2	1	20	55	1,6	24,3	4	1,95	2,47	21,05	21,78	22,54	23,34	-	-
3122120	2	2	1	20	65	1,6	28	6	1,95	4,25	21,05	21,78	22,54	23,34	24,22	25,16
3112122	2	2	1	22	60	1,6	26,3	4	1,95	2,27	23,13	23,92	24,75	25,64	-	-
3112125	2	2	1	25	65	1,6	29,3	4	1,95	2,03	26,24	27,13	28,08	29,09	-	-
3122125	2	2	1	25	70	1,6	33	6	1,95	3,58	26,24	27,13	28,08	29,09	30,19	31,38
3112130	2	2	1	30	70	1,6	34,3	4	1,95	1,73	31,42	32,48	33,62	-	-	-
3122130	2	2	1	30	75	1,6	38	6	1,95	3,1	31,42	32,48	33,62	34,84	36,16	37,59
3112135	2	2	1	35	75	1,6	39,3	4	1,95	1,5	36,59	37,83	39,16	-	-	-
3122135	2	2	1	35	80	1,6	43	6	1,95	2,73	36,59	37,83	39,16	40,59	42,14	-
3112140	2	2	1	40	80	1,6	44,3	4	1,95	1,33	41,76	43,18	-	-	-	-
3112560	2	2,5	1,25	6	45	2	9,1	4	2,35	5,46	6,26	6,51	6,75	6,99	7,21	7,46
3112600	2	2,5	1,25	10	50	2	13,1	4	2,35	3,63	10,46	10,85	11,21	11,59	11,99	12,43
3112615	2	2,5	1,25	15	55	2	18,1	4	2,35	2,55	15,67	16,21	16,75	17,34	17,96	-
3112620	2	2,5	1,25	20	60	2	23,1	4	2,35	1,97	20,87	21,56	22,3	-	-	-
3112625	2	2,5	1,25	25	65	2	28,1	4	2,35	1,6	26,04	26,91	27,84	-	-	-
3112630	2	2,5	1,25	30	70	2	33,1	4	2,35	1,35	31,21	32,26	-	-	-	-

Milling | Solid carbide




WXL-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC and stainless
- 2 flutes, long neck, ball nose
- 284 sizes





EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3112635	2	2,5	1,25	35	70	2	38,1	4	2,35	1,17	36,38	37,61	-	-	-	-
3113060	2	3	1,5	6	45	2,4	8,2	4	2,85	4,29	6,25	6,49	6,72	6,95	7,17	7,4
3123059	2	3	1,5	6	45	2,4	-	3	2,85	-	-	-	-	-	-	-
3123060	2	3	1,5	6	50	2,4	11,9	6	2,85	8,17	6,25	6,49	6,72	6,95	7,17	7,4
3123080	2	3	1,5	8	50	2,4	13,9	6	2,85	6,88	8,35	8,67	8,97	9,25	9,55	9,88
3123100	2	3	1,5	10	50	2,4	15,9	6	2,85	5,94	10,44	10,83	11,19	11,55	11,94	12,37
3123112	2	3	1,5	12	55	2,4	17,9	6	2,85	5,22	12,53	12,98	13,4	13,85	14,33	14,86
3123114	2	3	1,5	14	55	2,4	19,9	6	2,85	4,66	14,62	15,13	15,62	16,15	16,72	17,34
3123115	2	3	1,5	15	55	2,4	20,9	6	2,85	4,42	15,66	16,2	16,73	17,3	17,92	18,59
3123116	2	3	1,5	16	55	2,4	21,9	6	2,85	4,21	16,7	17,26	17,84	18,45	19,11	19,83
3123120	2	3	1,5	20	60	2,4	25,9	6	2,85	3,52	20,86	21,54	22,27	23,05	23,89	24,8
3123125	2	3	1,5	25	65	2,4	30,9	6	2,85	2,92	26,04	26,89	27,81	28,8	29,86	-
3123130	2	3	1,5	30	70	2,4	35,9	6	2,85	2,5	31,2	32,24	33,35	34,55	-	-
3123135	2	3	1,5	35	80	2,4	40,9	6	2,85	2,18	36,37	37,59	38,89	40,3	-	-
3123140	2	3	1,5	40	85	2,4	45,9	6	2,85	1,94	41,54	42,94	44,43	-	-	-
3123600	2	3,5	1,75	10	60	2,8	15	6	3,35	5,4	10,43	10,81	11,16	11,51	11,9	12,31
3123615	2	3,5	1,75	15	60	2,8	20	6	3,35	3,93	15,65	16,18	16,7	17,26	17,87	18,53
3123620	2	3,5	1,75	20	65	2,8	25	6	3,35	3,08	20,85	21,53	22,24	23,01	23,84	24,74
3123625	2	3,5	1,75	25	65	2,8	30	6	3,35	2,54	26,03	26,87	27,78	28,76	29,82	-
3123630	2	3,5	1,75	30	70	2,8	35	6	3,35	2,16	31,2	32,22	33,32	34,51	-	-
3123635	2	3,5	1,75	35	80	2,8	40	6	3,35	1,88	36,36	37,57	38,87	-	-	-
3123640	2	3,5	1,75	40	90	2,8	45	6	3,35	1,66	41,53	42,92	44,41	-	-	-
3123645	2	3,5	1,75	45	90	2,8	50	6	3,35	1,49	46,7	48,27	-	-	-	-
3114080	2	4	2	8	55	3,2	-	4	3,85	-	-	-	-	-	-	-
3124080	2	4	2	8	60	3,2	12,1	6	3,85	5,67	8,33	8,63	8,91	9,18	9,46	9,77
3124100	2	4	2	10	60	3,2	14,1	6	3,85	4,74	10,42	10,79	11,13	11,48	11,85	12,25
3124112	2	4	2	12	60	3,2	16,1	6	3,85	4,07	12,51	12,95	13,35	13,78	14,24	14,74
3124114	2	4	2	14	60	3,2	18,1	6	3,85	3,57	14,6	15,09	15,57	16,08	16,63	17,22
3124115	2	4	2	15	60	3,2	19,1	6	3,85	3,36	15,64	16,16	16,67	17,23	17,82	18,47
3124116	2	4	2	16	60	3,2	20,1	6	3,85	3,18	16,68	17,23	17,78	18,38	19,02	19,71
3124120	2	4	2	20	65	3,2	24,1	6	3,85	2,6	20,84	21,51	22,22	22,98	23,8	-
3124125	2	4	2	25	70	3,2	29,1	6	3,85	2,12	26,02	26,86	27,76	28,72	-	-
3124130	2	4	2	30	80	3,2	34,1	6	3,85	1,79	31,19	32,21	33,3	-	-	-
3124135	2	4	2	35	80	3,2	39,1	6	3,85	1,55	36,36	37,55	38,84	-	-	-
3124140	2	4	2	40	90	3,2	44,1	6	3,85	1,36	41,52	42,9	-	-	-	-
3124145	2	4	2	45	90	3,2	49,1	6	3,85	1,22	46,69	48,25	-	-	-	-
3124150	2	4	2	50	100	3,2	54,1	6	3,85	1,1	51,86	53,6	-	-	-	-
3125100	2	5	2,5	10	65	5	12,2	6	4,85	2,96	10,4	10,75	11,08	11,4	11,75	-
3125115	2	5	2,5	15	70	5	17,2	6	4,85	1,96	15,62	16,13	16,62	-	-	-
3125120	2	5	2,5	20	70	5	22,2	6	4,85	1,46	20,82	21,47	-	-	-	-
3125125	2	5	2,5	25	70	5	27,2	6	4,85	1,16	26	26,82	-	-	-	-
3125130	2	5	2,5	30	80	5	32,2	6	4,85	0,97	31,17	-	-	-	-	-
3125135	2	5	2,5	35	80	5	37,2	6	4,85	0,83	36,34	-	-	-	-	-
3125140	2	5	2,5	40	90	5	42,2	6	4,85	0,72	41,51	-	-	-	-	-
3125145	2	5	2,5	45	100	5	47,2	6	4,85	0,64	46,68	-	-	-	-	-
3125150	2	5	2,5	50	100	5	52,2	6	4,85	0,58	51,84	-	-	-	-	-

Milling | Solid carbide



WXL-PC-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC
- 2 flutes, ball nose, pencil neck
- 152 sizes




EDP	ZEFP	DC	RE	θn	LU	LF	APMX	LH	DCON	DN	DNX	Type
3170051	2	0,4	0,2	0,5	2	45	0,3	9	4	0,38	0,41	1
3170052	2	0,4	0,2	0,5	3	45	0,3	9,9	4	0,38	0,43	1
3170053	2	0,4	0,2	0,5	4	45	0,3	10,9	4	0,38	0,44	1
3170061	2	0,4	0,2	1	4	45	0,3	10,8	4	0,38	0,5	1
3170054	2	0,4	0,2	0,5	5	45	0,3	11,9	4	0,38	0,46	1
3170062	2	0,4	0,2	1	5	45	0,3	11,7	4	0,38	0,53	1
3170055	2	0,4	0,2	0,5	6	45	0,3	12,8	4	0,38	0,47	1
3170063	2	0,4	0,2	1	6	45	0,3	12,7	4	0,38	0,57	1
3170091	2	0,6	0,3	0,5	2	45	0,5	9	4	0,58	0,61	1
3170092	2	0,6	0,3	0,5	4	45	0,5	10,9	4	0,58	0,64	1
3170101	2	0,6	0,3	1	4	45	0,5	10,8	4	0,58	0,69	1
3170093	2	0,6	0,3	0,5	6	45	0,5	12,8	4	0,58	0,67	1
3170102	2	0,6	0,3	1	6	45	0,5	12,6	4	0,58	0,76	1
3170094	2	0,6	0,3	0,5	8	45	0,5	14,8	4	0,58	0,7	1
3170103	2	0,6	0,3	1	8	45	0,5	14,5	4	0,58	0,83	1
3170095	2	0,6	0,3	0,5	10	45	0,5	16,7	4	0,58	0,74	1
3170104	2	0,6	0,3	1	10	45	0,5	16,4	4	0,58	0,9	1
3170096	2	0,6	0,3	0,5	12	45	0,5	18,7	4	0,58	0,77	1
3170105	2	0,6	0,3	1	12	45	0,5	18,2	4	0,58	0,97	1
3170097	2	0,6	0,3	0,5	16	50	0,5	22,5	4	0,58	0,84	1
3170106	2	0,6	0,3	1	16	50	0,5	22	4	0,58	1,11	1
3170111	2	0,8	0,4	0,5	4	45	0,6	10,5	4	0,78	0,84	1
3170112	2	0,8	0,4	0,5	6	45	0,6	12,5	4	0,78	0,87	1
3170113	2	0,8	0,4	0,5	8	45	0,6	14,4	4	0,78	0,9	1
3170121	2	0,8	0,4	1	8	45	0,6	14,1	4	0,78	1,02	1
3170114	2	0,8	0,4	0,5	12	45	0,6	18,3	4	0,78	0,97	1
3170122	2	0,8	0,4	1	12	45	0,6	17,9	4	0,78	1,16	1
3170123	2	0,8	0,4	1	16	50	0,6	21,6	4	0,78	1,3	1
3170131	2	1	0,5	0,5	6	45	0,63	12,2	4	0,95	1,03	3
3170132	2	1	0,5	0,5	8	45	0,63	14,1	4	0,95	1,07	3
3170151	2	1	0,5	1,5	8	45	0,63	13,5	4	0,95	1,31	3
3170133	2	1	0,5	0,5	10	45	0,63	16	4	0,95	1,1	3
3170152	2	1	0,5	1,5	10	45	0,63	15,4	4	0,95	1,41	3
3170134	2	1	0,5	0,5	12	45	0,63	18	4	0,95	1,14	3
3170153	2	1	0,5	1,5	12	45	0,63	17,2	4	0,95	1,52	3
3170135	2	1	0,5	0,5	16	50	0,63	21,8	4	0,95	1,21	3
3170154	2	1	0,5	1,5	16	50	0,63	20,8	4	0,95	1,73	3
3170136	2	1	0,5	0,5	18	55	0,63	23,8	4	0,95	1,24	3
3170137	2	1	0,5	0,5	20	55	0,63	25,7	4	0,95	1,28	3
3170155	2	1	0,5	1,5	20	55	0,63	24,4	4	0,95	1,94	3
3170138	2	1	0,5	0,5	25	60	0,63	30,5	4	0,95	1,37	3
3170156	2	1	0,5	1,5	25	60	0,63	28,9	4	0,95	2,2	3
3170139	2	1	0,5	0,5	30	65	0,63	35,4	4	0,95	1,45	3
3170157	2	1	0,5	1,5	30	65	0,63	33,4	4	0,95	2,46	3
3170140	2	1	0,5	0,5	35	70	0,63	40,2	4	0,95	1,54	3
3170141	2	1	0,5	1	10	45	0,63	15,7	4	0,95	1,26	3

Milling | Solid carbide




WXL-PC-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC
- 2 flutes, ball nose, pencil neck
- 152 sizes





Milling | Solid carbide

EDP	ZEFP	DC	RE	θn	LU	LF	APMX	LH	DCON	DN	DNX	Type
3170142	2	1	0,5	1	16	50	0,63	21,3	4	0,95	1,47	3
3170143	2	1	0,5	1	20	55	0,63	25	4	0,95	1,61	3
3170144	2	1	0,5	1	25	60	0,63	29,7	4	0,95	1,78	3
3170145	2	1	0,5	1	30	65	0,63	34,4	4	0,95	1,96	3
3170146	2	1	0,5	1	35	70	0,63	39,1	4	0,95	2,13	3
3170158	2	1	0,5	1,5	35	70	0,63	37,9	4	0,95	2,72	3
3170147	2	1	0,5	1	40	80	0,63	43,7	4	0,95	2,31	3
3170161	2	1	0,5	2	45	80	0,63	-	4	0,95	-	2
3170148	2	1	0,5	1	50	90	0,63	53,1	4	0,95	2,66	3
3170149	2	1	0,5	1	60	100	0,63	62,4	4	0,95	3	3
3170150	2	1	0,5	1	70	110	0,63	71,8	4	0,95	3,35	3
3170211	2	1,5	0,75	0,5	8	45	0,95	13,2	4	1,42	1,53	3
3170212	2	1,5	0,75	0,5	10	45	0,95	15,2	4	1,42	1,57	3
3170221	2	1,5	0,75	1	10	45	0,95	14,8	4	1,42	1,71	3
3170230	2	1,5	0,75	1,5	10	45	0,95	14,5	4	1,42	1,87	3
3170213	2	1,5	0,75	0,5	12	45	0,95	17,1	4	1,42	1,6	3
3170222	2	1,5	0,75	1	12	45	0,95	16,7	4	1,42	1,79	3
3170231	2	1,5	0,75	1,5	12	45	0,95	16,3	4	1,42	1,97	3
3170214	2	1,5	0,75	0,5	16	55	0,95	21	4	1,42	1,67	3
3170223	2	1,5	0,75	1	16	55	0,95	20,4	4	1,42	1,93	3
3170232	2	1,5	0,75	1,5	16	55	0,95	19,9	4	1,42	2,18	3
3170215	2	1,5	0,75	0,5	20	55	0,95	24,8	4	1,42	1,74	3
3170224	2	1,5	0,75	1	20	55	0,95	24,2	4	1,42	2,07	3
3170233	2	1,5	0,75	1,5	20	55	0,95	23,5	4	1,42	2,39	3
3170216	2	1,5	0,75	0,5	25	60	0,95	29,7	4	1,42	1,83	3
3170225	2	1,5	0,75	1	25	60	0,95	28,9	4	1,42	2,24	3
3170234	2	1,5	0,75	1,5	25	60	0,95	28	4	1,42	2,65	3
3170217	2	1,5	0,75	0,5	30	65	0,95	34,5	4	1,42	1,92	3
3170226	2	1,5	0,75	1	30	65	0,95	33,5	4	1,42	2,41	3
3170235	2	1,5	0,75	1,5	30	65	0,95	32,6	4	1,42	2,91	3
3170218	2	1,5	0,75	0,5	35	70	0,95	39,4	4	1,42	2	3
3170227	2	1,5	0,75	1	35	70	0,95	38,2	4	1,42	2,59	3
3170236	2	1,5	0,75	1,5	35	70	0,95	37,1	4	1,42	3,17	3
3170241	2	1,5	0,75	2	38,6	70	0,95	-	4	1,42	-	2
3170271	2	2	1	0,5	8	45	1,26	12,3	4	1,93	2,04	3
3170272	2	2	1	0,5	10	45	1,26	14,2	4	1,93	2,07	3
3170273	2	2	1	0,5	12	45	1,26	16,2	4	1,93	2,11	3
3170274	2	2	1	0,5	16	50	1,26	20	4	1,93	2,18	3
3170291	2	2	1	1,5	16	50	1,26	19	4	1,93	2,67	3
3170275	2	2	1	0,5	20	55	1,26	23,9	4	1,93	2,25	3
3170276	2	2	1	0,5	25	65	1,26	28,7	4	1,93	2,33	3
3170277	2	2	1	0,5	30	70	1,26	33,6	4	1,93	2,42	3
3170278	2	2	1	0,5	35	75	1,26	38,4	4	1,93	2,51	3
3170279	2	2	1	0,5	40	80	1,26	43,2	4	1,93	2,6	3
3170281	2	2	1	1	16	50	1,26	19,5	4	1,93	2,43	3
3170282	2	2	1	1	20	55	1,26	23,3	4	1,93	2,57	3

WXL-PC-EBD

Milling | Solid carbide



- Carbide end mill with WXL coating
- For hardened steels up to 52 HRC
- 2 flutes, ball nose, pencil neck
- 152 sizes





EDP	ZEFP	DC	RE	θn	LU	LF	APMX	LH	DCON	DN	DNX	Type
3170292	2	2	1	1,5	20	55	1,26	22,6	4	1,93	2,88	3
3170283	2	2	1	1	25	65	1,26	27,9	4	1,93	2,74	3
3170293	2	2	1	1,5	25	65	1,26	27,1	4	1,93	3,15	3
3170284	2	2	1	1	30	70	1,26	32,6	4	1,93	2,91	3
3170294	2	2	1	1,5	30	70	1,26	31,6	4	1,93	3,41	3
3170301	2	2	1	2	31,5	70	1,26	-	4	1,93	-	2
3170285	2	2	1	1	35	75	1,26	37,3	4	1,93	3,09	3
3170295	2	2	1	1,5	35	75	1,26	36,1	4	1,93	3,67	3
3170286	2	2	1	1	40	80	1,26	41,9	4	1,93	3,26	3
3170296	2	2	1	1,5	41,4	80	1,26	-	4	1,93	-	2
3170287	2	2	1	1	50	90	1,26	55	6	1,93	3,61	3
3170288	2	2	1	1	60	100	1,26	64,4	6	1,93	3,96	3
3170289	2	2	1	1	70	110	1,26	73,7	6	1,93	4,31	3
3170321	2	3	1,5	0,5	8	50	2,4	14,1	6	2,95	3,05	1
3170322	2	3	1,5	0,5	10	50	2,4	16,1	6	2,95	3,08	1
3170323	2	3	1,5	0,5	12	55	2,4	18	6	2,95	3,12	1
3170324	2	3	1,5	0,5	16	55	2,4	21,9	6	2,95	3,18	1
3170325	2	3	1,5	0,5	20	60	2,4	25,8	6	2,95	3,25	1
3170331	2	3	1,5	1	20	60	2,4	25,1	6	2,95	3,55	1
3170341	2	3	1,5	1,5	20	60	2,4	24,5	6	2,95	3,85	1
3170326	2	3	1,5	0,5	25	65	2,4	30,6	6	2,95	3,34	1
3170332	2	3	1,5	1	25	65	2,4	29,8	6	2,95	3,73	1
3170342	2	3	1,5	1,5	25	65	2,4	29	6	2,95	4,11	1
3170327	2	3	1,5	0,5	30	70	2,4	35,4	6	2,95	3,42	1
3170333	2	3	1,5	1	30	70	2,4	34,5	6	2,95	3,9	1
3170343	2	3	1,5	1,5	30	70	2,4	33,6	6	2,95	4,37	1
3170328	2	3	1,5	0,5	35	80	2,4	40,3	6	2,95	3,51	1
3170334	2	3	1,5	1	35	80	2,4	39,2	6	2,95	4,07	1
3170344	2	3	1,5	1,5	35	80	2,4	38,1	6	2,95	4,64	1
3170329	2	3	1,5	0,5	40	85	2,4	45,1	6	2,95	3,6	1
3170335	2	3	1,5	1	40	85	2,4	43,8	6	2,95	4,25	1
3170345	2	3	1,5	1,5	40	85	2,4	42,6	6	2,95	4,9	1
3170351	2	3	1,5	2	47,5	100	2,4	-	6	2,95	-	2
3170330	2	3	1,5	0,5	50	90	2,4	54,8	6	2,95	3,77	1
3170336	2	3	1,5	1	50	90	2,4	53,2	6	2,95	4,6	1
3170346	2	3	1,5	1,5	50	90	2,4	51,6	6	2,95	5,42	1
3170337	2	3	1,5	1	60	100	2,4	62,5	6	2,95	4,95	1
3170347	2	3	1,5	1,5	62,5	100	2,4	-	6	2,95	-	2
3170338	2	3	1,5	1	70	110	2,4	71,9	6	2,95	5,3	1
3170371	2	4	2	1	20	65	3,2	23,4	6	3,93	4,5	1
3170372	2	4	2	1	30	80	3,2	32,7	6	3,93	4,85	1
3170373	2	4	2	1	40	90	3,2	42,1	6	3,93	5,2	1
3170381	2	4	2	1,5	44,2	80	3,2	-	6	3,93	-	2
3170391	2	4	2	2	34	80	3,2	-	6	3,93	-	2
3170374	2	4	2	1	50	100	3,2	55,1	8	3,93	5,55	1
3170375	2	4	2	1	60	110	3,2	64,5	8	3,93	5,9	1

Milling | Solid carbide




WXS-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXS coating
- For hardened steels up to 65 HRC and stainless steels
- 2 flutes, long neck, ball nose
- 189 sizes





EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3050100	2	0,1	0,05	0,3	45	0,08	7,5	4	0,09	14,51	0,31	0,32	0,33	0,34	0,35	0,36
3050101	2	0,1	0,05	0,5	45	0,08	7,7	4	0,09	14,31	0,42	0,44	0,45	0,47	0,48	0,5
3050201	2	0,2	0,1	0,5	45	0,16	7,5	4	0,18	14,16	0,53	0,55	0,57	0,59	0,61	0,63
3049921	2	0,2	0,1	0,75	45	0,16	7,8	4	0,18	13,72	0,79	0,82	0,85	0,88	0,91	0,94
3050202	2	0,2	0,1	1	45	0,16	8	4	0,18	13,31	1,05	1,09	1,13	1,17	1,21	1,26
3049922	2	0,2	0,1	1,25	45	0,16	8,3	4	0,18	12,92	1,31	1,36	1,41	1,46	1,51	1,57
3050203	2	0,2	0,1	1,5	45	0,16	8,5	4	0,18	12,56	1,57	1,63	1,68	1,74	1,81	1,88
3049923	2	0,2	0,1	1,75	45	0,16	8,8	4	0,18	12,21	1,83	1,9	1,96	2,03	2,11	2,19
3050204	2	0,2	0,1	2	45	0,16	9	4	0,18	11,88	2,09	2,16	2,24	2,32	2,4	2,5
3050205	2	0,2	0,1	2,5	45	0,16	9,5	4	0,18	11,28	2,61	2,7	2,79	2,89	3	3,12
3050206	2	0,2	0,1	3	45	0,16	10	4	0,18	10,73	3,13	3,23	3,35	3,47	3,6	3,74
3050301	2	0,3	0,15	0,6	45	0,24	7,4	4	0,28	14,03	0,63	0,65	0,68	0,7	0,72	0,75
3050302	2	0,3	0,15	1	45	0,24	7,8	4	0,28	13,34	1,05	1,09	1,12	1,16	1,2	1,24
3049932	2	0,3	0,15	1,25	45	0,24	8,1	4	0,28	12,94	1,31	1,36	1,4	1,45	1,5	1,55
3050303	2	0,3	0,15	1,5	45	0,24	8,3	4	0,28	12,57	1,57	1,63	1,68	1,74	1,8	1,87
3049933	2	0,3	0,15	1,75	45	0,24	8,6	4	0,28	12,21	1,83	1,89	1,96	2,02	2,1	2,18
3050304	2	0,3	0,15	2	45	0,24	8,8	4	0,28	11,87	2,09	2,16	2,23	2,31	2,4	2,49
3049934	2	0,3	0,15	2,25	45	0,24	9,1	4	0,28	11,56	2,35	2,43	2,51	2,6	2,69	2,8
3050305	2	0,3	0,15	2,5	45	0,24	9,3	4	0,28	11,25	2,61	2,69	2,79	2,89	2,99	3,11
3050306	2	0,3	0,15	3	45	0,24	9,8	4	0,28	10,69	3,13	3,23	3,34	3,46	3,59	3,73
3050307	2	0,3	0,15	3,5	45	0,24	10,3	4	0,28	10,19	3,64	3,76	3,9	4,04	4,19	4,35
3050308	2	0,3	0,15	4	45	0,24	10,8	4	0,28	9,72	4,16	4,3	4,45	4,61	4,78	4,97
3050309	2	0,3	0,15	4,5	45	0,24	11,3	4	0,28	9,3	4,68	4,83	5	5,19	5,38	5,59
3050310	2	0,3	0,15	5	45	0,24	11,8	4	0,28	8,91	5,19	5,37	5,56	5,76	5,98	6,22
3050401	2	0,4	0,2	0,8	45	0,3	7,4	4	0,37	13,74	0,83	0,86	0,88	0,91	0,94	0,97
3050402	2	0,4	0,2	1	45	0,3	7,6	4	0,37	13,39	1,04	1,07	1,11	1,14	1,18	1,22
3050403	2	0,4	0,2	1,5	45	0,3	8,1	4	0,37	12,59	1,56	1,61	1,66	1,72	1,77	1,84
3050404	2	0,4	0,2	2	45	0,3	8,6	4	0,37	11,88	2,08	2,14	2,21	2,29	2,37	2,46
3050405	2	0,4	0,2	2,5	45	0,3	9,1	4	0,37	11,24	2,6	2,68	2,77	2,87	2,97	3,08
3050406	2	0,4	0,2	3	45	0,3	9,6	4	0,37	10,67	3,11	3,21	3,32	3,44	3,57	3,7
3050407	2	0,4	0,2	3,5	45	0,3	10,1	4	0,37	10,15	3,63	3,75	3,88	4,02	4,16	4,33
3050408	2	0,4	0,2	4	45	0,3	10,6	4	0,37	9,68	4,15	4,28	4,43	4,59	4,76	4,95
3050409	2	0,4	0,2	4,5	45	0,3	11,1	4	0,37	9,25	4,66	4,82	4,99	5,17	5,36	5,57
3050410	2	0,4	0,2	5	45	0,3	11,6	4	0,37	8,86	5,18	5,35	5,54	5,74	5,96	6,19
3050411	2	0,4	0,2	5,5	45	0,3	12,1	4	0,37	8,5	5,7	5,89	6,09	6,32	6,55	6,81
3050412	2	0,4	0,2	6	45	0,3	12,6	4	0,37	8,16	6,21	6,42	6,65	6,89	7,15	7,43
3050500	2	0,5	0,25	1	45	0,4	7,6	4	0,45	13,45	1,03	1,06	1,09	1,12	1,15	1,19
3050501	2	0,5	0,25	1,5	45	0,4	8,1	4	0,45	12,62	1,55	1,59	1,64	1,69	1,75	1,81
3050502	2	0,5	0,25	2	45	0,4	8,6	4	0,45	11,89	2,06	2,13	2,2	2,27	2,35	2,43
3049952	2	0,5	0,25	2,5	45	0,4	9,1	4	0,45	11,23	2,58	2,66	2,75	2,84	2,94	3,05
3050503	2	0,5	0,25	3	45	0,4	9,6	4	0,45	10,65	3,1	3,2	3,3	3,42	3,54	3,68
3049953	2	0,5	0,25	3,5	45	0,4	10,1	4	0,45	10,12	3,61	3,73	3,86	3,99	4,14	4,3
3050504	2	0,5	0,25	4	45	0,4	10,6	4	0,45	9,64	4,13	4,27	4,41	4,57	4,74	4,92
3049954	2	0,5	0,25	4,5	45	0,4	11,1	4	0,45	9,2	4,65	4,8	4,97	5,14	5,33	5,54
3050505	2	0,5	0,25	5	45	0,4	11,6	4	0,45	8,8	5,17	5,34	5,52	5,72	5,93	6,16
3049955	2	0,5	0,25	5,5	45	0,4	12,1	4	0,45	8,43	5,68	5,87	6,07	6,29	6,53	6,78

Milling | Solid carbide




WXS-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXS coating
- For hardened steels up to 65 HRC and stainless steels
- 2 flutes, long neck, ball nose
- 189 sizes





Milling | Solid carbide


EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3050506	2	0,5	0,25	6	45	0,4	12,6	4	0,45	8,1	6,2	6,41	6,63	6,87	7,13	7,41
3050507	2	0,5	0,25	7	45	0,4	13,6	4	0,45	7,49	7,23	7,48	7,74	8,02	8,32	8,65
3050508	2	0,5	0,25	8	45	0,4	14,6	4	0,45	6,98	8,27	8,55	8,85	9,17	9,52	9,89
3050509	2	0,5	0,25	9	45	0,4	15,6	4	0,45	6,52	9,3	9,62	9,95	10,32	10,71	11,14
3050510	2	0,5	0,25	10	45	0,4	16,6	4	0,45	6,13	10,33	10,68	11,06	11,47	11,9	12,38
3050601	2	0,6	0,3	1,2	45	0,5	7,6	4	0,55	13,14	1,24	1,27	1,3	1,34	1,38	1,43
3050602	2	0,6	0,3	2	45	0,5	8,4	4	0,55	11,88	2,06	2,12	2,19	2,26	2,34	2,42
3049962	2	0,6	0,3	2,5	45	0,5	8,9	4	0,55	11,21	2,58	2,66	2,74	2,84	2,94	3,04
3050603	2	0,6	0,3	3	45	0,5	9,4	4	0,55	10,61	3,1	3,19	3,3	3,41	3,53	3,66
3049963	2	0,6	0,3	3,5	45	0,5	9,9	4	0,55	10,07	3,61	3,73	3,85	3,99	4,13	4,29
3050604	2	0,6	0,3	4	45	0,5	10,4	4	0,55	9,58	4,13	4,26	4,41	4,56	4,73	4,91
3049964	2	0,6	0,3	4,5	45	0,5	10,9	4	0,55	9,13	4,65	4,8	4,96	5,14	5,32	5,53
3050605	2	0,6	0,3	5	45	0,5	11,4	4	0,55	8,73	5,16	5,33	5,51	5,71	5,92	6,15
3049965	2	0,6	0,3	5,5	45	0,5	11,9	4	0,55	8,36	5,68	5,87	6,07	6,29	6,52	6,77
3050606	2	0,6	0,3	6	45	0,5	12,4	4	0,55	8,02	6,2	6,4	6,62	6,86	7,12	7,39
3049966	2	0,6	0,3	6,5	45	0,5	12,9	4	0,55	7,7	6,71	6,94	7,18	7,44	7,71	8,02
3050607	2	0,6	0,3	7	45	0,5	13,4	4	0,55	7,41	7,23	7,47	7,73	8,01	8,31	8,64
3049967	2	0,6	0,3	7,5	45	0,5	13,9	4	0,55	7,14	7,75	8,01	8,29	8,59	8,91	9,26
3050608	2	0,6	0,3	8	45	0,5	14,4	4	0,55	6,89	8,26	8,54	8,84	9,16	9,51	9,88
3049968	2	0,6	0,3	8,5	45	0,5	14,9	4	0,55	6,66	8,78	9,08	9,39	9,74	10,1	10,5
3050609	2	0,6	0,3	9	45	0,5	15,4	4	0,55	6,44	9,3	9,61	9,95	10,31	10,7	11,12
3049969	2	0,6	0,3	9,5	45	0,5	15,9	4	0,55	6,23	9,81	10,15	10,5	10,89	11,3	11,75
3050610	2	0,6	0,3	10	45	0,5	16,4	4	0,55	6,04	10,33	10,68	11,06	11,46	11,9	12,37
3050611	2	0,6	0,3	11	50	0,5	17,4	4	0,55	5,69	11,37	11,75	12,16	12,61	13,09	13,61
3050612	2	0,6	0,3	12	50	0,5	18,4	4	0,55	5,38	12,4	12,82	13,27	13,76	14,28	14,85
3050802	2	0,8	0,4	2	45	0,6	8,1	4	0,75	11,86	2,06	2,12	2,18	2,25	2,32	2,4
3050803	2	0,8	0,4	3	45	0,6	9,1	4	0,75	10,52	3,09	3,19	3,29	3,4	3,51	3,64
3050804	2	0,8	0,4	4	45	0,6	10,1	4	0,75	9,45	4,13	4,26	4,4	4,55	4,71	4,88
3050805	2	0,8	0,4	5	45	0,6	11,1	4	0,75	8,58	5,16	5,33	5,5	5,7	5,9	6,13
3050806	2	0,8	0,4	6	45	0,6	12,1	4	0,75	7,85	6,19	6,4	6,61	6,85	7,1	7,37
3050807	2	0,8	0,4	7	45	0,6	13,1	4	0,75	7,24	7,23	7,47	7,72	8	8,29	8,61
3050808	2	0,8	0,4	8	45	0,6	14,1	4	0,75	6,71	8,26	8,54	8,83	9,15	9,49	9,86
3050810	2	0,8	0,4	10	45	0,6	16,1	4	0,75	5,86	10,33	10,67	11,05	11,45	11,88	12,34
3050812	2	0,8	0,4	12	50	0,6	18,1	4	0,75	5,2	12,4	12,81	13,26	13,75	14,27	14,83
3051002	2	1	0,5	2	45	0,8	7,7	4	0,95	11,84	2,06	2,11	2,17	2,23	2,3	2,37
3051003	2	1	0,5	3	45	0,8	8,7	4	0,95	10,43	3,09	3,18	3,28	3,38	3,49	3,62
3051004	2	1	0,5	4	45	0,8	9,7	4	0,95	9,32	4,12	4,25	4,39	4,53	4,69	4,86
3051005	2	1	0,5	5	45	0,8	10,7	4	0,95	8,41	5,16	5,32	5,49	5,68	5,88	6,1
3051006	2	1	0,5	6	45	0,8	11,7	4	0,95	7,67	6,19	6,39	6,6	6,83	7,08	7,35
3051007	2	1	0,5	7	45	0,8	12,7	4	0,95	7,05	7,22	7,46	7,71	7,98	8,27	8,59
3051008	2	1	0,5	8	45	0,8	13,7	4	0,95	6,52	8,26	8,53	8,82	9,13	9,47	9,83
3051009	2	1	0,5	9	45	0,8	14,7	4	0,95	6,06	9,29	9,6	9,93	10,28	10,66	11,08
3051010	2	1	0,5	10	45	0,8	15,7	4	0,95	5,66	10,33	10,67	11,04	11,43	11,86	12,32
3051012	2	1	0,5	12	45	0,8	17,7	4	0,95	5,01	12,39	12,81	13,25	13,73	14,25	14,81
3051014	2	1	0,5	14	50	0,8	19,7	4	0,95	4,49	14,46	14,95	15,47	16,03	16,64	17,29
3051016	2	1	0,5	16	50	0,8	21,7	4	0,95	4,06	16,53	17,09	17,69	18,33	19,03	19,78

WXS-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXS coating
- For hardened steels up to 65 HRC and stainless steels
- 2 flutes, long neck, ball nose
- 189 sizes





EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3051018	2	1	0,5	18	55	0,8	23,7	4	0,95	3,71	18,59	19,23	19,9	20,63	21,41	22,26
3051020	2	1	0,5	20	55	0,8	25,7	4	0,95	3,42	20,66	21,36	22,12	22,93	23,8	24,75
3051022	2	1	0,5	22	60	0,8	27,7	4	0,95	3,17	22,73	23,5	24,33	25,23	26,19	27,24
3051202	2	1,2	0,6	2,4	45	1	7,8	4	1,15	11,03	2,51	2,61	2,7	2,78	2,87	2,96
3051204	2	1,2	0,6	4	45	1	9,4	4	1,15	9,07	4,19	4,34	4,48	4,62	4,78	4,95
3051206	2	1,2	0,6	6	45	1	11,4	4	1,15	7,41	6,27	6,48	6,69	6,92	7,17	7,44
3051208	2	1,2	0,6	8	45	1	13,4	4	1,15	6,26	8,35	8,62	8,91	9,22	9,56	9,93
3051210	2	1,2	0,6	10	45	1	15,4	4	1,15	5,42	10,42	10,76	11,13	11,52	11,95	12,41
3051212	2	1,2	0,6	12	45	1	17,4	4	1,15	4,78	12,49	12,9	13,34	13,82	14,34	14,9
3051214	2	1,2	0,6	14	50	1	19,4	4	1,15	4,27	14,55	15,04	15,56	16,12	16,73	17,38
3051216	2	1,2	0,6	16	50	1	21,4	4	1,15	3,86	16,62	17,18	17,78	18,42	19,12	19,87
3051218	2	1,2	0,6	18	55	1	23,4	4	1,15	3,52	18,69	19,32	19,99	20,72	21,51	22,36
3051220	2	1,2	0,6	20	55	1	25,4	4	1,15	3,24	20,75	21,46	22,21	23,02	23,9	24,84
3051503	2	1,5	0,75	3	45	1,2	7,9	4	1,45	10,01	3,13	3,25	3,35	3,45	3,56	3,67
3051504	2	1,5	0,75	4	45	1,2	8,9	4	1,45	8,8	4,18	4,33	4,46	4,6	4,75	4,92
3051506	2	1,5	0,75	6	45	1,2	10,9	4	1,45	7,08	6,27	6,47	6,68	6,9	7,14	7,4
3051508	2	1,5	0,75	8	45	1,2	12,9	4	1,45	5,92	8,34	8,61	8,9	9,2	9,53	9,89
3051510	2	1,5	0,75	10	45	1,2	14,9	4	1,45	5,09	10,41	10,75	11,11	11,5	11,92	12,38
3051512	2	1,5	0,75	12	45	1,2	16,9	4	1,45	4,46	12,48	12,89	13,33	13,8	14,31	14,86
3051514	2	1,5	0,75	14	50	1,2	18,9	4	1,45	3,96	14,55	15,03	15,55	16,1	16,7	17,35
3051516	2	1,5	0,75	16	50	1,2	20,9	4	1,45	3,57	16,62	17,17	17,76	18,4	19,09	19,83
3051518	2	1,5	0,75	18	55	1,2	22,9	4	1,45	3,25	18,68	19,31	19,98	20,7	21,48	22,32
3051520	2	1,5	0,75	20	55	1,2	24,9	4	1,45	2,98	20,75	21,45	22,19	23	23,87	-
3051522	2	1,5	0,75	22	60	1,2	26,9	4	1,45	2,75	22,82	23,59	24,41	25,3	26,26	-
3051530	2	1,5	0,75	30	70	1,2	34,9	4	1,45	2,1	31,09	32,14	33,28	34,5	-	-
3051608	2	1,6	0,8	8	45	1,3	12,7	4	1,55	5,8	8,34	8,61	8,89	9,19	9,52	9,88
3051612	2	1,6	0,8	12	45	1,3	16,7	4	1,55	4,34	12,48	12,89	13,32	13,79	14,3	14,85
3051616	2	1,6	0,8	16	50	1,3	20,7	4	1,55	3,47	16,61	17,16	17,76	18,39	19,08	19,82
3051620	2	1,6	0,8	20	55	1,3	24,7	4	1,55	2,89	20,75	21,44	22,19	22,99	23,86	-
3052004	2	2	1	4	45	1,6	8,3	4	1,95	7,87	4,23	4,44	4,66	4,86	5,06	5,26
3052006	2	2	1	6	45	1,6	10,3	4	1,95	6,19	6,36	6,67	6,96	7,23	7,49	7,76
3052008	2	2	1	8	45	1,6	12,3	4	1,95	5,1	8,48	8,87	9,22	9,55	9,88	10,24
3052010	2	2	1	10	45	1,6	14,3	4	1,95	4,33	10,59	11,05	11,45	11,85	12,27	12,73
3052012	2	2	1	12	45	1,6	16,3	4	1,95	3,77	12,69	13,21	13,67	14,15	14,66	15,22
3052014	2	2	1	14	50	1,6	18,3	4	1,95	3,33	14,78	15,36	15,89	16,45	17,05	17,7
3052016	2	2	1	16	50	1,6	20,3	4	1,95	2,98	16,88	17,51	18,1	18,75	19,44	-
3052018	2	2	1	18	55	1,6	22,3	4	1,95	2,7	18,96	19,65	20,32	21,04	21,83	-
3052020	2	2	1	20	55	1,6	24,3	4	1,95	2,47	21,05	21,78	22,54	23,34	-	-
3052022	2	2	1	22	60	1,6	26,3	4	1,95	2,27	23,13	23,92	24,75	25,64	-	-
3052025	2	2	1	25	65	1,6	29,3	4	1,95	2,03	26,24	27,13	28,08	29,09	-	-
3052030	2	2	1	30	70	1,6	34,3	4	1,95	1,73	31,42	32,48	33,62	-	-	-
3052035	2	2	1	35	70	1,6	39,3	4	1,95	1,5	36,59	37,83	39,16	-	-	-
3052040	2	2	1	40	80	1,6	44,3	4	1,95	1,33	41,76	43,18	-	-	-	-
3052510	2	2,5	1,25	10	45	2	13,1	4	2,35	3,63	10,46	10,85	11,21	11,59	11,99	12,43
3052515	2	2,5	1,25	15	50	2	18,1	4	2,35	2,55	15,67	16,21	16,75	17,34	17,96	-
3052520	2	2,5	1,25	20	55	2	23,1	4	2,35	1,97	20,87	21,56	22,3	-	-	-

Milling | Solid carbide




WXS-LN-EBD

Milling | Solid carbide



- Carbide end mill with WXS coating
- For hardened steels up to 65 HRC and stainless steels
- 2 flutes, long neck, ball nose
- 189 sizes





EDP	ZEFP	DC	RE	LU	LF	APMX	LH	DCON	DN	θk	Le (α=0,5°)	Le (α=1°)	Le (α=1,5°)	Le (α=2°)	Le (α=2,5°)	Le (α=3°)
3052525	2	2,5	1,25	25	65	2	28,1	4	2,35	1,6	26,04	26,91	27,84	-	-	-
3052530	2	2,5	1,25	30	70	2	33,1	4	2,35	1,35	31,21	32,26	-	-	-	-
3052535	2	2,5	1,25	35	70	2	38,1	4	2,35	1,17	36,38	37,61	-	-	-	-
3053006	2	3	1,5	6	50	2,4	11,9	6	2,85	8,17	6,25	6,49	6,72	6,95	7,17	7,4
3053008	2	3	1,5	8	50	2,4	13,9	6	2,85	6,88	8,35	8,67	8,97	9,25	9,55	9,88
3053010	2	3	1,5	10	50	2,4	15,9	6	2,85	5,94	10,44	10,83	11,19	11,55	11,94	12,37
3053012	2	3	1,5	12	55	2,4	17,9	6	2,85	5,22	12,53	12,98	13,4	13,85	14,33	14,86
3053014	2	3	1,5	14	55	2,4	19,9	6	2,85	4,66	14,62	15,13	15,62	16,15	16,72	17,34
3053015	2	3	1,5	15	55	2,4	20,9	6	2,85	4,42	15,66	16,2	16,73	17,3	17,92	18,59
3053016	2	3	1,5	16	55	2,4	21,9	6	2,85	4,21	16,7	17,26	17,84	18,45	19,11	19,83
3053020	2	3	1,5	20	60	2,4	25,9	6	2,85	3,52	20,86	21,54	22,27	23,05	23,89	24,8
3053025	2	3	1,5	25	65	2,4	30,9	6	2,85	2,92	26,04	26,89	27,81	28,8	29,86	-
3053030	2	3	1,5	30	70	2,4	35,9	6	2,85	2,5	31,2	32,24	33,35	34,55	-	-
3053035	2	3	1,5	35	80	2,4	40,9	6	2,85	2,18	36,37	37,59	38,89	40,3	-	-
3053040	2	3	1,5	40	90	2,4	45,9	6	2,85	1,94	41,54	42,94	44,43	-	-	-
3053515	2	3,5	1,75	15	55	2,8	20	6	3,35	3,93	15,65	16,18	16,7	17,26	17,87	18,53
3053520	2	3,5	1,75	20	60	2,8	25	6	3,35	3,08	20,85	21,53	22,24	23,01	23,84	24,74
3053525	2	3,5	1,75	25	65	2,8	30	6	3,35	2,54	26,03	26,87	27,78	28,76	29,82	-
3053530	2	3,5	1,75	30	70	2,8	35	6	3,35	2,16	31,2	32,22	33,32	34,51	-	-
3053535	2	3,5	1,75	35	80	2,8	40	6	3,35	1,88	36,36	37,57	38,87	-	-	-
3053540	2	3,5	1,75	40	90	2,8	45	6	3,35	1,66	41,53	42,92	44,41	-	-	-
3053545	2	3,5	1,75	45	90	2,8	50	6	3,35	1,49	46,7	48,27	-	-	-	-
3054008	2	4	2	8	55	3,2	12,1	6	3,85	5,67	8,33	8,63	8,91	9,18	9,46	9,77
3054010	2	4	2	10	60	3,2	14,1	6	3,85	4,74	10,42	10,79	11,13	11,48	11,85	12,25
3054012	2	4	2	12	60	3,2	16,1	6	3,85	4,07	12,51	12,95	13,35	13,78	14,24	14,74
3054015	2	4	2	15	60	3,2	19,1	6	3,85	3,36	15,64	16,16	16,67	17,23	17,82	18,47
3054016	2	4	2	16	60	3,2	20,1	6	3,85	3,18	16,68	17,23	17,78	18,38	19,02	19,71
3054020	2	4	2	20	65	3,2	24,1	6	3,85	2,6	20,84	21,51	22,22	22,98	23,8	-
3054025	2	4	2	25	70	3,2	29,1	6	3,85	2,12	26,02	26,86	27,76	28,72	-	-
3054030	2	4	2	30	80	3,2	34,1	6	3,85	1,79	31,19	32,21	33,3	-	-	-
3054035	2	4	2	35	80	3,2	39,1	6	3,85	1,55	36,36	37,55	38,84	-	-	-
3054040	2	4	2	40	90	3,2	44,1	6	3,85	1,36	41,52	42,9	-	-	-	-
3054045	2	4	2	45	90	3,2	49,1	6	3,85	1,22	46,69	48,25	-	-	-	-
3054050	2	4	2	50	100	3,2	54,1	6	3,85	1,1	51,86	53,6	-	-	-	-
3055010	2	5	2,5	10	60	4	12,2	6	4,85	2,96	10,4	10,75	11,08	11,4	11,75	-
3055015	2	5	2,5	15	60	4	17,2	6	4,85	1,96	15,62	16,13	16,62	-	-	-
3055020	2	5	2,5	20	70	4	22,2	6	4,85	1,46	20,82	21,47	-	-	-	-
3055025	2	5	2,5	25	70	4	27,2	6	4,85	1,16	26	26,82	-	-	-	-
3055030	2	5	2,5	30	80	4	32,2	6	4,85	0,97	31,17	-	-	-	-	-
3055035	2	5	2,5	35	80	4	37,2	6	4,85	0,83	36,34	-	-	-	-	-
3055040	2	5	2,5	40	90	4	42,2	6	4,85	0,72	41,51	-	-	-	-	-
3055045	2	5	2,5	45	100	4	47,2	6	4,85	0,64	46,68	-	-	-	-	-
3055050	2	5	2,5	50	100	4	52,2	6	4,85	0,58	51,84	-	-	-	-	-
3056012	2	6	3	12	60	4,8	-	6	5,85	-	-	-	-	-	-	-
3056020	2	6	3	20	70	4,8	-	6	5,85	-	-	-	-	-	-	-
3056025	2	6	3	25	70	4,8	-	6	5,85	-	-	-	-	-	-	-

Milling | Solid carbide




WXS-CPR

Milling | Solid carbide



Type 1



Type 2

- Carbide end mill with WXS coating
- For hardened steels up to 65 HRC and stainless steels
- 2 flutes, long and pencil neck, corner radius, for mould & die
- 247 sizes





EDP	ZEFP	DC	RE	θn	LU	LF	APMX	LH	DCON	DN	DNX	Type
3100201	2	0,2	0,05	0	0,5	50	0,15	7,6	4	0,18	-	1
3100202	2	0,2	0,05	0	1	50	0,15	8,1	4	0,18	-	1
3100203	2	0,2	0,05	1	1	50	0,15	8,2	4	0,18	0,22	2
3100204	2	0,2	0,05	1	2	50	0,15	9,1	4	0,18	0,26	2
3100301	2	0,3	0,05	0	1	50	0,25	7,9	4	0,28	-	1
3100302	2	0,3	0,05	0	2	50	0,25	8,9	4	0,28	-	1
3100303	2	0,3	0,05	1	2	50	0,25	9	4	0,28	0,35	2
3100304	2	0,3	0,05	1	3	50	0,25	9,9	4	0,28	0,39	2
3100401	2	0,4	0,05	0	1	50	0,3	8,1	4	0,37	-	1
3100402	2	0,4	0,05	0	1,5	50	0,3	8,6	4	0,37	-	1
3100403	2	0,4	0,05	0	2	50	0,3	9,1	4	0,37	-	1
3100404	2	0,4	0,05	0	3	50	0,3	10,1	4	0,37	-	1
3100405	2	0,4	0,05	0	4	50	0,3	11,1	4	0,37	-	1
3100409	2	0,4	0,05	1	3	50	0,3	9,7	4	0,37	0,48	2
3100410	2	0,4	0,05	1	4	50	0,3	10,7	4	0,37	0,51	2
3100406	2	0,4	0,1	0	2	50	0,3	9,1	4	0,37	-	1
3100407	2	0,4	0,1	0	3	50	0,3	10,1	4	0,37	-	1
3100408	2	0,4	0,1	0	4	50	0,3	11,1	4	0,37	-	1
3100415	2	0,4	0,1	1	3	50	0,3	9,7	4	0,37	0,48	2
3100416	2	0,4	0,1	1	4	50	0,3	10,7	4	0,37	0,51	2
3100501	2	0,5	0,05	0	1	50	0,4	8,1	4	0,46	-	1
3100502	2	0,5	0,05	0	2	50	0,4	9,1	4	0,46	-	1
3100503	2	0,5	0,05	0	3	50	0,4	10,1	4	0,46	-	1
3100504	2	0,5	0,05	0	4	50	0,4	11,1	4	0,46	-	1
3100505	2	0,5	0,05	0	5	50	0,4	12,1	4	0,46	-	1
3100506	2	0,5	0,05	0	6	50	0,4	13,1	4	0,46	-	1
3100513	2	0,5	0,05	1	3	50	0,4	9,5	4	0,46	0,58	2
3100514	2	0,5	0,05	1	5	50	0,4	11,4	4	0,46	0,64	2
3100515	2	0,5	0,05	1	8	50	0,4	14,2	4	0,46	0,75	2
3100516	2	0,5	0,05	1	10	50	0,4	16,1	4	0,46	0,81	2
3100517	2	0,5	0,05	1	12	50	0,4	18	4	0,46	0,88	2
3100507	2	0,5	0,1	0	1	50	0,4	8,1	4	0,46	-	1
3100508	2	0,5	0,1	0	2	50	0,4	9,1	4	0,46	-	1
3100509	2	0,5	0,1	0	3	50	0,4	10,1	4	0,46	-	1
3100510	2	0,5	0,1	0	4	50	0,4	11,1	4	0,46	-	1
3100511	2	0,5	0,1	0	5	50	0,4	12,1	4	0,46	-	1
3100512	2	0,5	0,1	0	6	50	0,4	13,1	4	0,46	-	1
3100527	2	0,5	0,1	1	3	50	0,4	9,5	4	0,46	0,58	2
3100528	2	0,5	0,1	1	5	50	0,4	11,4	4	0,46	0,64	2
3100529	2	0,5	0,1	1	8	50	0,4	14,2	4	0,46	0,75	2
3100530	2	0,5	0,1	1	10	50	0,4	16,1	4	0,46	0,81	2
3100531	2	0,5	0,1	1	12	50	0,4	18	4	0,46	0,88	2
3100601	2	0,6	0,1	0	2	50	0,48	8,9	4	0,55	-	1
3100602	2	0,6	0,1	0	4	50	0,48	10,9	4	0,55	-	1
3100603	2	0,6	0,1	0	6	50	0,48	12,9	4	0,55	-	1
3100806	2	0,8	0,05	1	5	50	0,65	11,2	4	0,75	0,93	2

Milling | Solid carbide




WXS-CPR

Milling | Solid carbide



Type 1



Type 2

- Carbide end mill with WXS coating
- For hardened steels up to 65 HRC and stainless steels
- 2 flutes, long and pencil neck, corner radius, for mould & die
- 247 sizes






EDP	ZEFP	DC	RE	θn	LU	LF	APMX	LH	DCON	DN	DNX	Type
3100807	2	0,8	0,05	1	8	50	0,65	14	4	0,75	1,04	2
3100801	2	0,8	0,1	0	4	50	0,65	10,5	4	0,75	-	1
3100802	2	0,8	0,1	0	6	50	0,65	12,5	4	0,75	-	1
3100810	2	0,8	0,1	1	5	50	0,65	11,2	4	0,75	0,93	2
3100811	2	0,8	0,1	1	8	50	0,65	14	4	0,75	1,04	2
3100803	2	0,8	0,2	0	4	50	0,65	10,5	4	0,75	-	1
3100804	2	0,8	0,2	0	6	50	0,65	12,5	4	0,75	-	1
3100805	2	0,8	0,2	0	8	50	0,65	14,5	4	0,75	-	1
3100814	2	0,8	0,2	1	5	50	0,65	11,2	4	0,75	0,93	2
3100815	2	0,8	0,2	1	8	50	0,65	14	4	0,75	1,04	2
3101001	2	1	0,05	0	4	50	0,8	10,1	4	0,94	-	1
3101002	2	1	0,05	0	6	50	0,8	12,1	4	0,94	-	1
3101003	2	1	0,05	0	8	50	0,8	14,1	4	0,94	-	1
3101004	2	1	0,05	0	10	50	0,8	16,1	4	0,94	-	1
3101005	2	1	0,05	0	12	50	0,8	18,1	4	0,94	-	1
3101023	2	1	0,05	1	6	50	0,8	11,8	4	0,94	1,16	2
3101024	2	1	0,05	1	10	60	0,8	15,5	4	0,94	1,29	2
3101025	2	1	0,05	1	15	60	0,8	20,2	4	0,94	1,46	2
3101026	2	1	0,05	1	20	60	0,8	24,9	4	0,94	1,61	2
3101027	2	1	0,05	1	25	70	0,8	29,6	4	0,94	1,79	2
3101028	2	1	0,05	1	30	80	0,8	34,3	4	0,94	1,96	2
3101029	2	1	0,05	1	35	80	0,8	39	4	0,94	2,13	2
3101006	2	1	0,1	0	4	50	0,8	10,1	4	0,94	-	1
3101007	2	1	0,1	0	6	50	0,8	12,1	4	0,94	-	1
3101008	2	1	0,1	0	8	50	0,8	14,1	4	0,94	-	1
3101009	2	1	0,1	0	10	50	0,8	16,1	4	0,94	-	1
3101010	2	1	0,1	0	12	50	0,8	18,1	4	0,94	-	1
3101032	2	1	0,1	1	6	50	0,8	11,8	4	0,94	1,16	2
3101033	2	1	0,1	1	10	60	0,8	15,5	4	0,94	1,29	2
3101034	2	1	0,1	1	15	60	0,8	20,2	4	0,94	1,46	2
3101035	2	1	0,1	1	20	60	0,8	24,9	4	0,94	1,61	2
3101036	2	1	0,1	1	25	70	0,8	29,6	4	0,94	1,79	2
3101037	2	1	0,1	1	30	80	0,8	34,3	4	0,94	1,96	2
3101038	2	1	0,1	1	35	80	0,8	39	4	0,94	2,13	2
3101011	2	1	0,2	0	4	50	0,8	10,1	4	0,94	-	1
3101012	2	1	0,2	0	6	50	0,8	12,1	4	0,94	-	1
3101013	2	1	0,2	0	8	50	0,8	14,1	4	0,94	-	1
48253108	2	1	0,2	0	8	50	0,8	17,9	6	0,94	-	1
3101014	2	1	0,2	0	10	50	0,8	16,1	4	0,94	-	1
3101015	2	1	0,2	0	12	50	0,8	18,1	4	0,94	-	1
3101016	2	1	0,2	0	16	60	0,8	22,1	4	0,94	-	1
3101017	2	1	0,2	0	20	60	0,8	26,1	4	0,94	-	1
3101041	2	1	0,2	1	6	50	0,8	11,8	4	0,94	1,16	2
3101042	2	1	0,2	1	10	60	0,8	15,5	4	0,94	1,29	2
3101043	2	1	0,2	1	15	60	0,8	20,2	4	0,94	1,46	2
3101044	2	1	0,2	1	20	60	0,8	24,9	4	0,94	1,61	2

Milling | Solid carbide



WXS-CPR

Milling | Solid carbide



- Carbide end mill with WXS coating
- For hardened steels up to 65 HRC and stainless steels
- 2 flutes, long and pencil neck, corner radius, for mould & die
- 247 sizes







Milling | Solid carbide

EDP	ZEFP	DC	RE	θn	LU	LF	APMX	LH	DCON	DN	DNX	Type
3101045	2	1	0,2	1	25	70	0,8	29,6	4	0,94	1,79	2
3101046	2	1	0,2	1	30	80	0,8	34,3	4	0,94	1,96	2
3101047	2	1	0,2	1	35	80	0,8	39	4	0,94	2,13	2
3101018	2	1	0,3	0	4	50	0,8	10,1	4	0,94	-	1
3101019	2	1	0,3	0	6	50	0,8	12,1	4	0,94	-	1
3101020	2	1	0,3	0	8	50	0,8	14,1	4	0,94	-	1
3101021	2	1	0,3	0	10	50	0,8	16,1	4	0,94	-	1
3101022	2	1	0,3	0	12	50	0,8	18,1	4	0,94	-	1
3101050	2	1	0,3	1	6	50	0,8	11,8	4	0,94	1,16	2
3101051	2	1	0,3	1	10	60	0,8	15,5	4	0,94	1,29	2
3101052	2	1	0,3	1	15	60	0,8	20,2	4	0,94	1,46	2
3101053	2	1	0,3	1	20	60	0,8	24,9	4	0,94	1,61	2
3101054	2	1	0,3	1	25	70	0,8	29,6	4	0,94	1,79	2
3101055	2	1	0,3	1	30	80	0,8	34,3	4	0,94	1,96	2
3101056	2	1	0,3	1	35	80	0,8	39	4	0,94	2,13	2
3101201	2	1,2	0,2	0	6	50	1	11,7	4	1,14	-	1
3101202	2	1,2	0,2	0	8	50	1	13,7	4	1,14	-	1
3101203	2	1,2	0,2	0	10	50	1	15,7	4	1,14	-	1
3101204	2	1,2	0,3	0	6	50	1	11,7	4	1,14	-	1
3101205	2	1,2	0,3	0	8	50	1	13,7	4	1,14	-	1
3101206	2	1,2	0,3	0	10	50	1	15,7	4	1,14	-	1
3101511	2	1,5	0,1	1	10	60	1,2	14,6	4	1,43	1,78	2
3101512	2	1,5	0,1	1	15	60	1,2	19,3	4	1,43	1,94	2
3101513	2	1,5	0,1	1	20	60	1,2	24	4	1,43	2,1	2
3101514	2	1,5	0,1	1	25	70	1,2	28,7	4	1,43	2,27	2
3101515	2	1,5	0,1	1	30	80	1,2	33,4	4	1,43	2,45	2
3101501	2	1,5	0,2	0	6	50	1,2	11,1	4	1,43	-	1
3101502	2	1,5	0,2	0	8	50	1,2	13,1	4	1,43	-	1
3101503	2	1,5	0,2	0	10	50	1,2	15,1	4	1,43	-	1
3101504	2	1,5	0,2	0	12	50	1,2	17,1	4	1,43	-	1
3101505	2	1,5	0,2	0	16	50	1,2	21,1	4	1,43	-	1
3101518	2	1,5	0,2	1	10	60	1,2	14,6	4	1,43	1,78	2
3101519	2	1,5	0,2	1	15	60	1,2	19,3	4	1,43	1,94	2
3101520	2	1,5	0,2	1	20	60	1,2	24	4	1,43	2,1	2
3101521	2	1,5	0,2	1	25	70	1,2	28,7	4	1,43	2,27	2
3101522	2	1,5	0,2	1	30	80	1,2	33,4	4	1,43	2,45	2
3101506	2	1,5	0,3	0	6	50	1,2	11,1	4	1,43	-	1
3101507	2	1,5	0,3	0	8	50	1,2	13,1	4	1,43	-	1
3101508	2	1,5	0,3	0	10	50	1,2	15,1	4	1,43	-	1
3101509	2	1,5	0,3	0	12	50	1,2	17,1	4	1,43	-	1
3101510	2	1,5	0,3	0	16	50	1,2	21,1	4	1,43	-	1
3101525	2	1,5	0,3	1	10	60	1,2	14,6	4	1,43	1,78	2
3101526	2	1,5	0,3	1	15	60	1,2	19,3	4	1,43	1,94	2
3101527	2	1,5	0,3	1	20	60	1,2	24	4	1,43	2,1	2
3101528	2	1,5	0,3	1	25	70	1,2	28,7	4	1,43	2,27	2
3101529	2	1,5	0,3	1	30	80	1,2	33,4	4	1,43	2,45	2

WXS-CPR

Milling | Solid carbide



- Carbide end mill with WXS coating
- For hardened steels up to 65 HRC and stainless steels
- 2 flutes, long and pencil neck, corner radius, for mould & die
- 247 sizes





EDP	ZEFP	DC	RE	θn	LU	LF	APMX	LH	DCON	DN	DNX	Type
3102001	2	2	0,1	0	8	50	1,6	12,22	4	1,92	-	1
3102002	2	2	0,1	0	10	50	1,6	14,2	4	1,92	-	1
3102003	2	2	0,1	0	12	50	1,6	16,2	4	1,92	-	1
3102004	2	2	0,1	0	16	60	1,6	20,2	4	1,92	-	1
3102005	2	2	0,1	0	20	60	1,6	24,2	4	1,92	-	1
3102006	2	2	0,1	0	25	70	1,6	29,2	4	1,92	-	1
3102025	2	2	0,1	1	15	60	1,6	18,4	4	1,92	2,43	2
3102026	2	2	0,1	1	20	60	1,6	23,1	4	1,92	2,58	2
3102027	2	2	0,1	1	25	70	1,6	27,8	4	1,92	2,76	2
3102028	2	2	0,1	1	30	80	1,6	32,5	4	1,92	2,93	2
3102029	2	2	0,1	1	40	80	1,6	41,8	4	1,92	3,27	2
3102030	2	2	0,1	1	50	100	1,6	51,1	4	1,92	3,62	2
3102007	2	2	0,2	0	8	50	1,6	12,2	4	1,92	-	1
3102008	2	2	0,2	0	10	50	1,6	14,2	4	1,92	-	1
3102009	2	2	0,2	0	12	50	1,6	16,2	4	1,92	-	1
3102010	2	2	0,2	0	16	60	1,6	20,2	4	1,92	-	1
3102011	2	2	0,2	0	20	60	1,6	24,2	4	1,92	-	1
3102012	2	2	0,2	0	25	70	1,6	29,2	4	1,92	-	1
3102033	2	2	0,2	1	15	60	1,6	18,4	4	1,92	2,43	2
3102034	2	2	0,2	1	20	60	1,6	23,1	4	1,92	2,58	2
3102035	2	2	0,2	1	25	70	1,6	27,8	4	1,92	2,76	2
3102036	2	2	0,2	1	30	80	1,6	32,5	4	1,92	2,93	2
3102037	2	2	0,2	1	40	80	1,6	41,8	4	1,92	3,27	2
3102038	2	2	0,2	1	50	100	1,6	51,1	4	1,92	3,62	2
3102013	2	2	0,3	0	8	50	1,6	12,2	4	1,92	-	1
3102014	2	2	0,3	0	10	50	1,6	14,2	4	1,92	-	1
3102015	2	2	0,3	0	12	50	1,6	16,2	4	1,92	-	1
3102016	2	2	0,3	0	16	60	1,6	20,2	4	1,92	-	1
3102017	2	2	0,3	0	20	60	1,6	24,2	4	1,92	-	1
3102018	2	2	0,3	0	25	70	1,6	29,2	4	1,92	-	1
3102041	2	2	0,3	1	15	60	1,6	18,4	4	1,92	2,43	2
3102042	2	2	0,3	1	20	60	1,6	23,1	4	1,92	2,58	2
3102043	2	2	0,3	1	25	70	1,6	27,8	4	1,92	2,76	2
3102044	2	2	0,3	1	30	80	1,6	32,5	4	1,92	2,93	2
3102045	2	2	0,3	1	40	80	1,6	41,8	4	1,92	3,27	2
3102046	2	2	0,3	1	50	100	1,6	51,1	4	1,92	3,62	2
3102019	2	2	0,5	0	8	50	1,6	12,2	4	1,92	-	1
3102020	2	2	0,5	0	10	50	1,6	14,2	4	1,92	-	1
3102021	2	2	0,5	0	12	50	1,6	16,2	4	1,92	-	1
3102022	2	2	0,5	0	16	60	1,6	20,2	4	1,92	-	1
3102023	2	2	0,5	0	20	60	1,6	24,2	4	1,92	-	1
3102024	2	2	0,5	0	25	70	1,6	29,2	4	1,92	-	1
3102049	2	2	0,5	1	15	60	1,6	18,4	4	1,92	2,43	2
3102050	2	2	0,5	1	20	60	1,6	23,1	4	1,92	2,58	2
3102051	2	2	0,5	1	25	70	1,6	27,8	4	1,92	2,76	2
3102052	2	2	0,5	1	30	80	1,6	32,5	4	1,92	2,93	2

Milling | Solid carbide




WXS-CPR

Milling | Solid carbide



Type 1



Type 2


- Carbide end mill with WXS coating
- For hardened steels up to 65 HRC and stainless steels
- 2 flutes, long and pencil neck, corner radius, for mould & die
- 247 sizes



EDP	ZEFP	DC	RE	θn	LU	LF	APMX	LH	DCON	DN	DNX	Type
3102053	2	2	0,5	1	40	80	1,6	41,8	4	1,92	3,27	2
3102054	2	2	0,5	1	50	100	1,6	51,1	4	1,92	3,62	2
3102501	2	2,5	0,2	0	10	50	2,2	13,2	4	2,4	-	1
3102502	2	2,5	0,2	0	20	60	2,2	23,2	4	2,4	-	1
3102503	2	2,5	0,2	0	30	70	2,2	33,2	4	2,4	-	1
3102504	2	2,5	0,5	0	10	50	2,2	13,2	4	2,4	-	1
3102505	2	2,5	0,5	0	20	60	2,2	23,2	4	2,4	-	1
3102506	2	2,5	0,5	0	30	70	2,2	33,2	4	2,4	-	1
3103001	2	3	0,2	0	8	60	2,5	13,9	6	2,85	-	1
3103002	2	3	0,2	0	12	60	2,5	17,9	6	2,85	-	1
3103003	2	3	0,2	0	16	60	2,5	21,9	6	2,85	-	1
3103004	2	3	0,2	0	20	70	2,5	25,9	6	2,85	-	1
3103005	2	3	0,2	0	25	70	2,5	30,9	6	2,85	-	1
3103006	2	3	0,2	0	30	70	2,5	35,9	6	2,85	-	1
3103007	2	3	0,2	0	35	80	2,5	40,9	6	2,85	-	1
3103020	2	3	0,2	1	15	60	2,5	20,3	6	2,85	3,4	2
3103021	2	3	0,2	1	20	60	2,5	25	6	2,85	3,55	2
3103022	2	3	0,2	1	30	80	2,5	34,4	6	2,85	3,9	2
3103023	2	3	0,2	1	40	80	2,5	43,8	6	2,85	4,24	2
3103024	2	3	0,2	1	50	100	2,5	53,1	6	2,85	4,59	2
3103025	2	3	0,2	1	60	110	2,5	62,5	6	2,85	4,94	2
3103008	2	3	0,3	0	12	60	2,5	17,9	6	2,85	-	1
3103009	2	3	0,3	0	16	60	2,5	21,9	6	2,85	-	1
3103010	2	3	0,3	0	20	70	2,5	25,9	6	2,85	-	1
3103011	2	3	0,3	0	25	70	2,5	30,9	6	2,85	-	1
3103012	2	3	0,3	0	30	70	2,5	35,9	6	2,85	-	1
3103013	2	3	0,3	0	35	80	2,5	40,9	6	2,85	-	1
3103014	2	3	0,5	0	12	60	2,5	17,9	6	2,85	-	1
3103015	2	3	0,5	0	16	60	2,5	21,9	6	2,85	-	1
3103016	2	3	0,5	0	20	70	2,5	25,9	6	2,85	-	1
3103017	2	3	0,5	0	25	70	2,5	30,9	6	2,85	-	1
3103018	2	3	0,5	0	30	70	2,5	35,9	6	2,85	-	1
3103019	2	3	0,5	0	35	80	2,5	40,9	6	2,85	-	1
3103026	2	3	0,5	1	15	60	2,5	20,3	6	2,85	3,4	2
3103027	2	3	0,5	1	20	60	2,5	25	6	2,85	3,55	2
3103028	2	3	0,5	1	30	80	2,5	34,4	6	2,85	3,9	2
3103029	2	3	0,5	1	40	80	2,5	43,8	6	2,85	4,24	2
3103030	2	3	0,5	1	50	100	2,5	53,1	6	2,85	4,59	2
3103031	2	3	0,5	1	60	110	2,5	62,5	6	2,85	4,94	2
3104001	4	4	0,2	0	16	60	4	20,1	6	3,84	-	1
3104002	4	4	0,2	0	20	60	4	24,1	6	3,84	-	1
3104003	4	4	0,2	0	25	70	4	29,1	6	3,84	1	1
3104004	4	4	0,2	0	30	70	4	34,1	6	3,84	1	1
3104005	4	4	0,2	0	40	90	4	44,1	6	3,84	1	1
3104006	4	4	0,2	0	50	100	4	54,1	6	3,84	1	1
3104007	4	4	0,3	0	16	60	4	20,1	6	3,84	1	1

Milling | Solid carbide






CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-1,5D-DE

Slotting

Ø	Cu		~32 HRC FC250 • SS400 • S55C • NAK55		33~41 HRC SKT • SKD61 • NAK80 • HPM1 • DH		42~50 HRC SKT • SKD61 • NAK80 • HPM1 • DH	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
0,1	50.000	120	40.000	80	40.000	75	40.000	38
0,2	50.000	170	40.000	110	40.000	90	40.000	45
0,3	50.000	210	40.000	140	40.000	100	40.000	70
0,4	50.000	230	40.000	150	40.000	110	34.500	75
0,5	50.000	250	38.500	150	31.000	110	27.500	75
0,6	50.000	280	33.500	150	24.500	110	21.000	75
0,7	50.000	310	30.000	150	21.500	110	18.500	75
0,8	50.000	360	27.000	150	19.500	110	17.000	80
0,9	50.000	400	23.500	150	17.000	110	15.000	80
1	50.000	430	22.000	150	15.500	110	13.500	80
1,1	50.000	420	20.000	150	14.000	110	12.500	80
1,2	50.000	420	18.500	150	13.500	110	11.500	80
1,3	47.000	410	17.500	150	12.500	110	11.000	80
1,4	44.000	410	16.000	150	11.500	110	10.000	80
1,5	40.000	400	15.500	150	11.000	110	9.900	80
1,6	39.000	400	15.000	150	10.500	110	9.400	80
1,7	36.500	400	14.000	150	9.900	110	8.800	80
1,8	34.500	400	13.500	160	9.400	110	8.500	80
1,9	32.500	400	12.500	160	8.800	110	7.900	85
2	30.000	380	12.000	160	8.700	110	7.900	90
2,1	29.000	410	11.500	170	8.300	110	7.400	90
2,2	28.000	410	11.000	170	8.200	110	7.200	90
2,3	27.500	410	11.000	180	8.000	110	7.000	90
2,4	26.000	430	10.500	180	7.900	110	6.900	90
2,5	24.500	430	10.500	200	7.600	110	6.600	90
2,6	23.500	470	9.800	200	7.400	125	6.300	90
2,7	23.000	470	9.500	200	7.100	125	6.100	90
2,8	22.000	470	9.100	210	6.900	125	5.800	95
2,9	21.500	470	8.800	210	6.700	125	5.700	95
3	21.000	540	8.900	230	6.800	130	5.700	100
3,1	20.000	550	8.700	240	6.700	130	5.600	100
3,2	19.500	560	8.400	240	6.500	145	5.400	105
3,3	19.000	560	8.100	250	6.300	145	5.200	105
3,4	18.000	560	7.900	250	6.100	145	5.100	105
3,5	18.000	560	7.800	250	6.000	155	5.000	105
3,6	17.500	580	7.600	270	5.900	155	4.900	110
3,7	16.500	580	7.400	270	5.700	155	4.700	110
3,8	16.000	590	7.300	280	5.700	155	4.600	110
3,9	15.500	590	7.100	280	5.500	160	4.500	110
4	15.500	600	7.000	280	5.500	160	4.500	115
4,1	15.500	640	6.900	290	5.400	160	4.400	115
4,2	15.000	640	6.800	290	5.300	160	4.400	115
4,3	14.000	640	6.700	310	5.200	160	4.300	115
4,4	14.000	670	6.600	320	5.100	170	4.200	125
4,5	14.000	670	6.600	320	5.100	170	4.200	125
4,6	13.500	700	6.500	330	4.900	170	4.100	125
4,7	13.500	700	6.500	350	4.900	170	4.100	125
4,8	13.500	710	6.400	350	4.800	170	4.100	125
4,9	13.500	710	6.300	360	4.700	170	4.000	125
5	12.500	720	6.200	370	4.600	170	3.900	130
5,1	12.500	720	6.100	370	4.500	170	3.900	130
5,2	12.000	720	6.000	370	4.400	170	3.800	130
5,3	12.000	720	5.900	370	4.400	170	3.800	130
5,4	11.500	720	5.800	370	4.300	170	3.600	130
5,5	11.500	720	5.700	370	4.200	170	3.500	130
5,6	11.500	720	5.600	370	4.100	170	3.500	130
5,7	11.000	720	5.500	370	4.000	170	3.400	130
5,8	11.000	710	5.400	370	3.900	170	3.300	130
5,9	10.500	710	5.300	370	3.800	170	3.300	130
6	10.000	710	5.200	370	3.800	170	3.200	130

Max cutting depth		D < 1	0,1D
		1 ≤ D ≤ 3	0,3D
		3 ≤ D	0,5D

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant properties.

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions


WXL-2D-DE

Slotting

Ø	Cu		~32 HRC FC250 • SS400 • S55C • NAK55		33~41 HRC SKT • SKD61 • NAK80 • HPM1 • DH		42~50 HRC SKT • SKD61 • NAK80 • HPM1 • DH	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
0,1	50.000	100	32.000	70	32.000	60	32.000	30
0,2	50.000	140	32.000	90	32.000	75	32.000	35
0,3	50.000	170	32.000	110	32.000	80	32.000	55
0,4	50.000	190	32.000	120	32.000	90	27.500	60
0,5	50.000	200	31.000	120	25.000	90	22.000	60
0,6	50.000	230	27.000	120	19.500	90	17.000	60
0,7	50.000	250	24.000	120	17.000	90	15.000	60
0,8	50.000	290	21.500	120	15.500	90	13.500	65
0,9	49.000	320	19.000	120	13.500	90	12.000	65
1	47.500	350	17.500	120	12.500	90	11.000	65
1,1	43.000	340	16.000	120	11.500	90	9.900	65
1,2	40.500	340	15.000	120	10.500	90	9.300	65
1,3	38.000	330	14.000	120	9.900	90	8.700	65
1,4	35.000	330	13.000	120	9.200	90	8.100	65
1,5	32.000	320	12.500	120	8.900	90	7.900	65
1,6	31.000	320	12.000	120	8.500	90	7.500	65
1,7	29.000	320	11.000	120	7.900	90	7.000	65
1,8	28.000	320	10.500	130	7.500	90	6.800	68
1,9	26.000	320	10.000	130	7.100	90	6.300	68
2	24.000	310	9.700	130	7.000	90	6.300	70
2,1	23.000	330	9.300	140	6.600	90	5.900	70
2,2	22.500	330	9.000	140	6.500	90	5.700	70
2,3	22.000	330	8.800	150	6.400	90	5.600	70
2,4	20.500	350	8.600	150	6.300	90	5.500	70
2,5	20.000	350	8.200	160	6.100	90	5.300	70
2,6	19.000	380	7.900	160	5.900	100	5.000	70
2,7	18.000	380	7.600	160	5.700	100	4.900	70
2,8	17.500	380	7.300	170	5.500	100	4.700	75
2,9	17.000	380	7.100	170	5.300	100	4.500	75
3	16.000	400	6.900	170	5.300	100	4.400	75
3,1	15.500	410	6.700	180	5.100	100	4.300	75
3,2	15.000	420	6.500	180	5.000	110	4.200	80
3,3	14.500	420	6.300	190	4.800	110	4.000	80
3,4	14.000	420	6.100	190	4.600	110	3.900	80
3,5	14.000	420	6.000	190	4.600	120	3.800	80
3,6	13.500	430	5.900	200	4.500	120	3.700	85
3,7	12.500	430	5.700	200	4.400	120	3.600	85
3,8	12.500	440	5.600	210	4.400	120	3.600	85
3,9	12.000	440	5.500	210	4.200	125	3.500	85
4	12.000	450	5.400	210	4.200	125	3.500	90
4,1	11.500	480	5.300	220	4.100	125	3.400	90
4,2	11.500	480	5.300	220	4.100	125	3.300	90
4,3	11.000	480	5.200	230	4.000	125	3.300	90
4,4	11.000	500	5.100	240	3.900	130	3.200	95
4,5	10.500	500	5.100	240	3.900	130	3.200	95
4,6	10.500	520	5.000	250	3.800	130	3.200	95
4,7	10.500	520	5.000	260	3.800	130	3.100	95
4,8	10.500	530	4.900	260	3.700	130	3.100	95
4,9	10.000	530	4.900	270	3.600	130	3.100	95
5	9.500	540	4.800	270	3.500	130	3.000	100
5,1	9.500	540	4.700	270	3.500	130	3.000	100
5,2	9.300	540	4.600	270	3.400	130	2.900	100
5,3	9.200	540	4.600	270	3.400	130	2.900	100
5,4	9.000	540	4.500	270	3.300	130	2.800	100
5,5	8.800	540	4.400	270	3.200	130	2.700	100
5,6	8.700	540	4.300	270	3.100	130	2.600	100
5,7	8.500	540	4.200	270	3.100	130	2.600	100
5,8	8.400	530	4.200	270	3.000	130	2.600	100
5,9	8.200	530	4.100	270	2.900	130	2.500	100
6	7.900	530	4.000	270	2.900	130	2.500	100
6,5	7.500	530	3.700	270	2.700	130	2.300	100
7	6.900	530	3.400	270	2.500	130	2.100	100
7,5	6.400	530	3.200	270	2.300	130	2.000	100
8	5.900	520	3.000	260	2.200	125	1.900	100
8,5	5.600	520	2.800	260	2.000	125	1.700	100
9	5.300	510	2.600	260	1.900	125	1.500	100
9,5	5.100	510	2.500	260	1.800	125	1.400	95
10	4.700	500	2.400	250	1.700	125	1.500	95
11	4.400	500	2.200	250	1.600	125	1.100	95
12	4.000	510	2.000	250	1.400	125	1.200	95
16	3.000	400	1.500	200	1.100	115	800	80
18	2.700	360	1.300	180	900	100	700	70
20	2.400	300	1.200	150	800	90	600	60

Milling | Endmills

Cutting conditions



D < 1	0,1D
1 ≤ D ≤ 3	0,3D
3 ≤ D	0,5D

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant properties.

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions


WXL-3D-DE

Slotting



Ø	Cu		~32 HRC FC250 • SS400 • S55C • NAK55		33~41 HRC SKT • SKD61 • NAK80 • HPM1 • DH		42~50 HRC SKT • SKD61 • NAK80 • HPM1 • DH	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
0,1	50.000	100	32.000	70	32.000	60	32.000	30
0,2	50.000	140	32.000	90	32.000	75	32.000	35
0,3	50.000	170	32.000	110	32.000	80	32.000	55
0,4	50.000	190	32.000	120	32.000	90	27.500	60
0,5	50.000	200	31.000	120	25.000	90	22.000	60
0,6	50.000	230	27.000	120	19.500	90	17.000	60
0,7	50.000	250	24.000	120	17.000	90	15.000	60
0,8	50.000	290	21.500	120	15.500	90	13.500	65
0,9	49.000	320	19.000	120	13.500	90	12.000	65
1	47.500	350	17.500	120	12.500	90	11.000	65
1,1	43.000	340	16.000	120	11.500	90	9.900	65
1,2	40.500	340	15.000	120	10.500	90	9.300	65
1,3	38.000	330	14.000	120	9.900	90	8.700	65
1,4	35.000	330	13.000	120	9.200	90	8.100	65
1,5	32.000	320	12.500	120	8.900	90	7.900	65
1,6	31.000	320	12.000	120	8.500	90	7.500	65
1,7	29.000	320	11.000	120	7.900	90	7.000	65
1,8	28.000	320	10.500	130	7.500	90	6.800	68
1,9	26.000	320	10.000	130	7.100	90	6.300	68
2	24.000	310	9.700	130	7.000	90	6.300	70
2,1	23.000	330	9.300	140	6.600	90	5.900	70
2,2	22.500	330	9.000	140	6.500	90	5.700	70
2,3	22.000	330	8.800	150	6.400	90	5.600	70
2,4	20.500	350	8.600	150	6.300	90	5.500	70
2,5	20.000	350	8.200	160	6.100	90	5.300	70
2,6	19.000	380	7.900	160	5.900	100	5.000	70
2,7	18.000	380	7.600	160	5.700	100	4.900	70
2,8	17.500	380	7.300	170	5.500	100	4.700	75
2,9	17.000	380	7.100	170	5.300	100	4.500	75
3	16.000	400	6.900	170	5.300	100	4.400	75
3,1	15.500	410	6.700	180	5.100	100	4.300	75
3,2	15.000	420	6.500	180	5.000	110	4.200	80
3,3	14.500	420	6.300	190	4.800	110	4.000	80
3,4	14.000	420	6.100	190	4.600	110	3.900	80
3,5	14.000	420	6.000	190	4.600	120	3.800	80
3,6	13.500	430	5.900	200	4.500	120	3.700	85
3,7	12.500	430	5.700	200	4.400	120	3.600	85
3,8	12.500	440	5.600	210	4.400	120	3.600	85
3,9	12.000	440	5.500	210	4.200	125	3.500	85
4	12.000	450	5.400	210	4.200	125	3.500	90
4,1	11.500	480	5.300	220	4.100	125	3.400	90
4,2	11.500	480	5.300	220	4.100	125	3.300	90
4,3	11.000	480	5.200	230	4.000	125	3.300	90
4,4	11.000	500	5.100	240	3.900	130	3.200	95
4,5	10.500	500	5.100	240	3.900	130	3.200	95
4,6	10.500	520	5.000	250	3.800	130	3.200	95
4,7	10.500	520	5.000	260	3.800	130	3.100	95
4,8	10.500	530	4.900	260	3.700	130	3.100	95
4,9	10.000	530	4.900	270	3.600	130	3.100	95
5	9.500	540	4.800	270	3.500	130	3.000	100
5,1	9.500	540	4.700	270	3.500	130	3.000	100
5,2	9.300	540	4.600	270	3.400	130	2.900	100
5,3	9.200	540	4.600	270	3.400	130	2.900	100
5,4	9.000	540	4.500	270	3.300	130	2.800	100
5,5	8.800	540	4.400	270	3.200	130	2.700	100
5,6	8.700	540	4.300	270	3.100	130	2.600	100
5,7	8.500	540	4.200	270	3.100	130	2.600	100
5,8	8.400	530	4.200	270	3.000	130	2.600	100
5,9	8.200	530	4.100	270	2.900	130	2.500	100
6	7.900	530	4.000	270	2.900	130	2.500	100
6,5	7.500	530	3.700	270	2.700	130	2.300	100
7	6.900	530	3.400	270	2.500	130	2.100	100
7,5	6.400	530	3.200	270	2.300	130	2.000	100
8	5.900	520	3.000	260	2.200	125	1.900	100
8,5	5.600	520	2.800	260	2.000	125	1.700	100
9	5.300	510	2.600	260	1.900	125	1.500	100
9,5	5.100	510	2.500	260	1.800	125	1.400	95
10	4.700	500	2.400	250	1.700	125	1.500	95
11	4.400	500	2.200	250	1.600	125	1.100	95
12	4.000	510	2.000	250	1.400	125	1.200	95
16	3.000	400	1.500	200	1.100	115	800	80
18	2.700	360	1.300	180	900	100	700	70
20	2.400	300	1.200	150	800	90	600	60

Max cutting depth



D < 1	0,1D
1 ≤ D ≤ 3	0,3D
3 ≤ D	0,5D

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant properties.

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-4D-DE

Side milling

Ø	Cu		~32 HRC FC250 • SS400 • S55C • NAK55		33~41 HRC SKT • SKD61 • NAK80 • HPM1 • DH		42~50 HRC SKT • SKD61 • NAK80 • HPM1 • DH	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
0,2	32.000	90	22.500	30	19.000	30	—	—
0,3	32.000	110	22.500	40	19.000	35	—	—
0,4	25.000	110	16.000	45	14.500	35	—	—
0,5	20.000	120	13.000	45	13.000	40	—	—
0,6	16.000	120	11.000	45	10.000	40	—	—
0,7	16.000	120	9.400	45	6.800	40	—	—
0,8	12.000	120	8.400	45	6.000	40	—	—
0,9	12.000	120	7.500	45	5.400	40	—	—
1	9.800	120	5.700	45	5.400	40	—	—
1,1	9.500	140	5.200	45	5.000	40	—	—
1,2	8.600	130	4.800	45	4.500	40	—	—
1,3	8.100	130	4.500	45	4.200	40	—	—
1,4	7.500	130	4.200	45	3.900	40	—	—
1,5	7.000	130	3.900	45	3.600	40	—	—
1,6	6.400	120	3.700	45	3.500	40	—	—
1,7	6.200	120	3.600	45	3.400	40	—	—
1,8	5.800	120	3.300	45	3.100	40	—	—
1,9	5.500	120	3.200	45	3.000	40	—	—
2	5.200	120	3.000	45	2.800	40	—	—
2,1	4.800	120	2.900	45	2.800	40	—	—
2,2	4.600	130	2.700	50	2.600	40	—	—
2,3	4.500	130	2.700	50	2.600	40	—	—
2,4	4.400	130	2.600	55	2.500	40	—	—
2,5	4.100	140	2.500	55	2.500	40	—	—
2,6	3.900	140	2.400	55	2.400	40	—	—
2,7	3.700	150	2.300	55	2.300	45	—	—
2,8	3.600	150	2.200	55	2.200	45	—	—
2,9	3.500	150	2.100	60	2.100	45	—	—
3	3.400	150	2.100	60	2.100	50	1.900	30
3,1	3.200	160	2.000	60	2.000	50	1.800	30
3,2	3.000	160	2.000	65	2.000	50	1.800	30
3,3	2.900	160	1.900	65	1.900	55	1.700	30
3,4	2.800	160	1.800	70	1.800	55	1.700	30
3,5	2.800	160	1.800	70	1.800	55	1.600	30
3,6	2.700	160	1.800	70	1.800	60	1.600	30
3,7	2.700	170	1.700	70	1.700	60	1.500	35
3,8	2.500	170	1.700	70	1.700	60	1.500	35
3,9	2.400	170	1.600	75	1.600	60	1.500	35
4	2.400	170	1.600	75	1.600	65	1.400	35
4,1	2.400	180	1.600	75	1.600	65	1.400	35
4,2	2.300	190	1.600	80	1.600	65	1.400	35
4,3	2.300	190	1.500	80	1.500	65	1.400	35
4,4	2.100	190	1.500	80	1.500	65	1.400	35
4,5	2.100	200	1.500	85	1.500	65	1.300	40
4,6	2.100	200	1.500	85	1.500	65	1.300	40
4,7	2.100	200	1.500	90	1.500	65	1.300	40
4,8	2.100	200	1.500	90	1.500	65	1.300	40
4,9	2.000	210	1.400	90	1.400	65	1.300	40
5	2.000	210	1.400	95	1.400	65	1.300	40
5,1	1.900	210	1.400	95	1.400	65	1.200	40
5,2	1.900	210	1.400	95	1.400	65	1.200	40
5,3	1.800	210	1.300	95	1.300	65	1.200	40
5,4	1.800	210	1.300	95	1.300	65	1.200	40
5,5	1.800	210	1.300	95	1.300	65	1.100	40
5,6	1.700	210	1.300	95	1.300	65	1.100	40
5,7	1.700	210	1.300	95	1.300	65	1.100	40
5,8	1.700	210	1.200	95	1.200	65	1.100	40
5,9	1.600	210	1.200	95	1.200	65	1.000	40
6	1.600	210	1.200	95	1.200	65	1.000	40
8	1.100	200	900	95	900	65	800	40
10	900	200	700	90	700	65	630	40
12	800	200	600	90	600	65	525	40

Max cutting depth		ae			ap = 4D	
	D > 1	0,05D		D < 0,3		0,015D
	D < 1	0,1D		D 0,3-1,0		0,03D
				D 1,0-3,0		0,05D
				D > 3,0	0,1D	

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant properties.

Milling | Endmills

Cutting conditions

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-EMS

Side milling

Ø	Cu		~32 HRC FC250 • SS400 • S55C • NAK55		33~41 HRC SKT • SKD61 • NAK80 • HPM1 • DH		42~50 HRC SKT • SKD61 • NAK80 • HPM1 • DH	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
1	50.000	440	24.000	210	14.000	78	12.500	70
1,5	50.000	975	16.000	310	9.250	115	8.400	105
2	47.500	1.100	12.000	295	7.000	110	6.350	100
2,5	38.000	1.900	9.600	480	6.200	140	5.550	125
3	32.000	1.600	8.150	430	5.300	125	4.750	110
4	24.000	1.700	6.050	450	4.250	135	3.700	115
5	19.000	2.000	4.900	520	3.550	140	3.150	125
6	16.000	2.000	4.100	520	2.950	145	2.650	130
8	12.000	1.900	3.050	505	2.200	145	1.950	130
10	9.500	1.900	2.450	505	1.750	145	1.550	130
12	7.900	1.900	2.050	505	1.450	145	1.300	130
14	6.800	1.900	1.750	495	1.250	145	1.100	125
15	6.300	1.900	1.600	490	1.150	135	1.050	120
16	5.900	1.800	1.500	480	1.100	130	995	115
18	5.300	1.800	1.350	470	990	115	880	105
20	4.700	1.700	1.200	445	890	105	795	95
25	3.800	1.400	970	360	710	85	635	75
30	3.100	1.100	815	300	590	70	530	60

Max cutting depth		D	ap	ae
		<3	1,5D	0,05D
		>3	1,5D	0,1D

ap	ae
1D	0,02D

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant properties.
4. Refer to the table above to set the milling conditions in accordance with the actual situation

WXL-EMS

High speed side milling

Ø	Cu		~32 HRC FC250 • SS400 • S55C • NAK55		33~41 HRC SKT • SKD61 • NAK80 • HPM1 • DH		42~50 HRC SKT • SKD61 • NAK80 • HPM1 • DH	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
6	26.000	2.900	20.000	2.300	13.000	1.500	7.950	795
8	19.500	3.000	14.500	2.300	9.900	1.450	5.950	795
10	15.500	2.900	12.000	2.300	7.950	1.450	4.750	795
12	13.000	3.000	9.900	2.300	6.600	1.450	3.950	790
14	11.000	2.800	8.500	2.200	5.650	1.350	3.400	740
15	10.500	2.800	7.950	2.150	5.250	1.350	3.150	730
16	9.700	2.700	7.450	2.100	4.950	1.350	2.950	715
18	8.600	2.700	6.600	2.100	4.400	1.300	2.650	705
20	7.800	2.600	5.950	2.000	3.950	1.300	2.350	665
25	6.200	2.000	4.750	1.600	3.150	1.050	1.900	560
30	5.200	1.700	3.950	1.350	2.650	890	1.550	455

Max cutting depth		D	ap	ae
		D<Ø8	1,5D	0,01D
		Ø8≤D	1,5D	0,02D

D	ap	ae
D<Ø8	1D	0,01D
Ø8≤D	1D	0,02D



CUTTING CONDITIONS


Milling | Endmills | Cutting conditions

WXL-LN-EDS

Slotting

D		Cu			<32 HRC FC250 • S5400 • S55C			33~41 HRC SKT • SKD61 • NAK80 • HPM1 • DH			42~50 HRC SKT • SKD61 • NAK80 • HPM1 • DH		
		S (min ⁻¹)	F (mm/min)	ap	S (min ⁻¹)	F (mm/min)	ap	S (min ⁻¹)	F (mm/min)	ap	S (min ⁻¹)	F (mm/min)	ap
3	25	12.000	960	0,132	10.000	800	0,110	9.000	700	0,090	6.000	500	0,07
3	30	9.600	720	0,108	8.000	600	0,090	7.000	500	0,080	5.000	400	0,06
3	35	9.600	720	0,084	8.000	600	0,070	7.000	500	0,060	5.000	400	0,05
3	40	9.600	720	0,048	8.000	600	0,040	7.000	500	0,030	5.000	400	0,02
3	50	6.950	320	0,011	5.800	270	0,009	5.700	240	0,005	5.000	200	0,004
4	12	8.550	1.350	0,456	7.000	1.100	0,380	7.000	1.000	0,320	6.000	700	0,26
4	16	8.550	1.350	0,432	7.000	1.100	0,360	7.000	1.000	0,300	6.000	700	0,24
4	20	8.550	970	0,408	7.000	800	0,340	6.000	700	0,280	5.000	500	0,22
4	25	8.550	970	0,312	7.000	800	0,260	6.000	700	0,220	5.000	500	0,18
4	30	8.550	970	0,228	7.000	800	0,190	6.000	700	0,160	5.000	500	0,13
4	35	8.550	970	0,204	7.000	800	0,170	6.000	700	0,140	5.000	500	0,11
4	40	7.300	730	0,168	6.000	600	0,140	5.000	600	0,120	4.000	400	0,1
4	45	7.300	730	0,144	6.000	600	0,120	5.000	600	0,100	4.000	400	0,08
4	50	7.300	730	0,060	6.000	600	0,050	5.000	600	0,040	4.000	400	0,03
4	60	6.100	340	0,024	5.000	280	0,020	5.000	270	0,020	4.000	250	0,01
5	16	7.300	1.350	0,54	6.000	1.100	0,450	5.000	900	0,380	5.000	600	0,3
5	20	7.300	1.150	0,516	6.000	950	0,430	5.000	780	0,360	5.000	600	0,29
5	25	6.100	970	0,504	5.000	800	0,420	5.000	700	0,350	5.000	600	0,28
5	30	6.100	970	0,456	5.000	800	0,380	5.000	700	0,300	5.000	600	0,25
5	35	6.100	970	0,396	5.000	800	0,330	5.000	700	0,280	5.000	600	0,22
5	40	6.100	730	0,340	5.000	600	0,280	4.000	580	0,200	4.000	500	0,18
5	50	4.900	610	0,180	4.000	500	0,150	3.000	400	0,130	3.000	400	0,1
5	60	4.900	420	0,072	4.000	350	0,060	3.000	330	0,060	3.000	300	0,04

Max cutting depth




1. Use a rigid and precise machine and holder.
2. When machining carbon steel or hardened steel, using MQL (Minimum Quantity Lubrication, mist coolant) or air blow is recommended.
3. When using cutting fluid, choose based on work material and cutting conditions.
4. The cutting conditions shown for 3D milling are low-load, safe conditions for references. Refer to the table above to set the milling conditions in accordance with the actual situation.
5. Please adjust conditions based on machining accuracy, machining shape and machining path.
6. When using a tool with a dia. of 0,5 or less, or an L/D (effective length/tool diameter) ratio of greater than 10, high loads can cause tool breakage.
7. When the available RPM are insufficient, please reduce the RPM and feed rates in proportion.

WXL-LN-EMS-6

Slotting

Vc	C≤0,2% - GG SS400 • S55C • FC250 ~750 N/mm ²		~30 HRC SCM • SKT • SKS • SKD		30~38 HRC SKT • SKD • NAK55 • HPM1		38~45 HRC-SUS SUS304 • SKD		45~55 HRC TiAl		55~60 HRC	
	100 (m/min)	78 (m/min)	66 (m/min)	62 (m/min)	60 (m/min)	30 (m/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
1	26.500	1.000	21.500	700	17.500	500	15.000	400	9.500	160	6.350	60
1,5	17.500	1.000	14.000	700	11.500	500	10.000	400	6.350	160	4.250	60
2	13.000	1.050	10.500	700	8.900	590	7.600	400	4.750	160	3.200	60
2,5	10.400	1.250	8.400	700	7.100	500	6.100	400	3.800	160	2.550	60
3	8.900	1.000	7.200	700	5.900	500	5.050	400	3.150	160	2.100	60
4	6.650	1.000	5.400	700	4.450	500	3.800	400	2.350	160	1.550	60
5	5.300	1.000	4.300	700	3.550	500	3.050	400	1.900	160	1.250	60
6	4.450	1.000	3.600	700	2.950	500	2.500	400	1.550	160	1.050	60

Max cutting depth



ap
0,5D

ap
0,05D

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant properties.

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-CR-EDS-6

Slotting

Ø	C≤0,2% - GG SS400 • S55C • FC250 ~750 N/mm ²		~30 HRC SCM • SKT • SKS • SKD		30~38 HRC SKT • SKD • NAK55 • HPM1		38~45 HRC SUS304 • SKD		45~55 HRC		55~60 HRC	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
0,2	32.000	125	32.000	115	32.000	100	32.000	90	32.000	60	24.500	30
0,3	32.000	190	32.000	170	32.000	150	32.000	135	32.000	90	18.000	40
0,4	32.000	250	32.000	230	32.000	200	32.000	180	32.000	120	14.000	40
0,5	32.000	320	32.000	290	32.000	250	32.000	225	26.000	130	12.000	40
0,6	32.000	380	32.000	345	32.000	310	27.500	250	22.000	130	10.500	40
0,8	32.000	512	32.000	460	29.000	370	22.000	280	17.500	130	8.750	45
1	30.000	600	27.000	480	25.000	400	19.000	300	14.000	130	7.600	50
1,2	26.500	630	23.500	510	21.000	400	15.500	300	11.500	130	6.600	55
1,4	22.500	630	20.000	510	18.000	400	13.500	300	10.000	130	5.900	55
1,5	21.000	630	19.000	510	16.500	400	12.500	300	9.500	130	5.700	60
1,6	19.500	630	17.500	510	15.500	400	11.500	300	8.950	130	5.550	60
1,8	17.500	630	15.500	510	14.000	400	10.500	300	7.950	130	5.300	65
2	15.500	630	14.000	510	12.500	400	9.500	300	7.150	130	4.750	65
2,5	12.500	630	11.000	510	10.000	400	7.600	300	5.700	130	3.800	65

Max cutting depth		D	ap
		< 1	0,1D
		≥ 1	0,3D

D	ap
< 1	0,02D
≥ 1	0,05D

D	ap
< 1	0,01D
≥ 1	

WXL-HS-EBD

R	Copper • Copper Alloy				Mild Steel • Carbon Steel FC250 • S5400 • S55C ~32HRC				Hardened Steel • Prehardened Steel • Stainless Steel SKT • SKD61 • NAK55 • NAK80 • HPM1 • DH* • SUS304							
	S (min ⁻¹)	F (mm/min)	Depth of cut		S (min ⁻¹)	F (mm/min)	Depth of cut		33~41HRC				42~50HRC			
			ap	pf			ap	pf	S (min ⁻¹)	F (mm/min)	Depth of cut		S (min ⁻¹)	F (mm/min)	Depth of cut	
0.1	50.000	540	0,01	0,02	50.000	540	0,01	0,02	50.000	540	0,01	0,02	50.000	440	0,01	0,02
0.2	50.000	880	0,02	0,04	50.000	750	0,02	0,04	50.000	750	0,02	0,04	50.000	680	0,02	0,04
0.3	50.000	1.840	0,02	0,04	50.000	910	0,02	0,04	50.000	910	0,02	0,04	50.000	840	0,02	0,04
0.4	50.000	2.210	0,02	0,05	50.000	1.850	0,02	0,05	50.000	1.850	0,02	0,05	50.000	1.250	0,02	0,05
0.5	50.000	3.350	0,02	0,05	50.000	2.800	0,02	0,05	50.000	2.500	0,02	0,05	47.500	2.250	0,02	0,05
1	31.500	3.350	0,04	0,10	25.000	2.800	0,04	0,10	24.500	2.500	0,04	0,10	23.500	2.250	0,04	0,10
1.5	21.000	3.350	0,06	0,15	16.500	2.800	0,06	0,15	16.000	2.500	0,06	0,15	15.500	2.250	0,06	0,15
2	15.500	4.080	0,08	0,20	15.500	3.400	0,08	0,20	15.000	2.750	0,08	0,20	13.500	2.450	0,08	0,20
3	10.500	5.160	0,12	0,30	13.500	4.300	0,30	0,60	11.500	2.750	0,30	0,60	9.500	2.250	0,12	0,30
4	7.900	3.840	0,16	0,40	10.000	3.200	0,40	0,80	8.950	2.100	0,40	0,80	7.150	1.700	0,16	0,40
5	6.300	3.120	0,20	0,50	8.250	2.600	0,50	1,00	7.150	1.700	0,50	1,00	5.700	1.350	0,20	0,50
6	5.250	2.580	0,24	0,60	6.850	2.150	0,50	2,40	5.950	1.400	0,50	2,40	4.750	1.100	0,24	0,60

Depth of cut		β

- The indicated speeds and feeds are for high speed light milling with high speed/high precision machining centers.
 - Because tools can cause sparks, do not use flammable fluids.
 - Use an air blow or a suitable cutting fluid with high smoke retardant properties.
 - Refer to the table above to set the milling conditions in accordance with the actual situation.
- *If your machine tool does not attain the indicated speed, operate it at the highest possible speed.

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-EBD

Regular milling

R	Cu				~32 HRC FC250 • SS400 • S55C • NAK55				33~41 HRC SKT • SKD61 • NAK80 • HPM1 • DH				42~50 HRC SKT • SKD61 • NAK80 • HPM1 • DH			
	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
R 0,05	40.000	150	0,003	0,005	32.000	75	0,005	0,005	32.000	50	0,005	0,005	32.000	170	0,005	0,005
R 0,1	40.000	300	0,010	0,020	32.000	200	0,010	0,010	32.000	200	0,010	0,010	32.000	180	0,005	0,005
R 0,2	40.000	490	0,020	0,080	32.000	410	0,020	0,080	32.000	330	0,020	0,080	32.000	205	0,020	0,040
R 0,3	40.000	580	0,030	0,120	32.000	490	0,030	0,120	32.000	420	0,030	0,120	32.000	265	0,030	0,060
R 0,4	40.000	660	0,040	0,160	32.000	550	0,040	0,160	31.500	420	0,040	0,160	27.500	290	0,040	0,080
R 0,5	32.000	750	0,050	0,200	31.500	620	0,050	0,200	25.000	400	0,050	0,200	22.000	285	0,050	0,100
R 1	19.000	750	0,200	0,400	15.500	620	0,200	0,400	12.500	400	0,200	0,400	11.000	290	0,100	0,200
R 1,5	12.500	760	0,300	0,600	10.500	630	0,300	0,600	8.450	405	0,300	0,600	7.400	290	0,150	0,300
R 2	9.500	760	0,400	0,800	7.950	630	0,400	0,800	6.350	445	0,400	0,800	5.550	370	0,200	0,400
R 3	6.300	800	0,600	1,200	5.300	670	0,600	1,200	4.200	465	0,600	1,200	3.700	390	0,300	0,600
R 4	4.750	950	0,800	1,600	3.950	790	0,800	1,600	3.150	555	0,800	1,600	2.750	455	0,400	0,800
R 5	3.800	890	1,000	2,000	3.150	745	1,000	2,000	2.500	525	1,000	2,000	2.200	430	0,500	1,000
R 6	3.750	840	1,200	2,400	2.650	700	1,200	2,400	2.100	490	1,200	2,400	1.850	430	0,600	1,200
R 8	2.400	630	1,600	3,200	2.000	525	1,600	3,200	1.600	370	1,600	3,200	1.400	325	0,800	1,600
R 10	1.900	500	2,000	4,000	1.600	420	2,000	4,000	1.250	290	2,000	4,000	1.100	260	1,000	2,000



1. Use a rigid and precise machine and holder.
 2. Use a suitable cutting fluid with high smoke retardant properties.
 3. Refer to top the table above to set the milling conditions in accordance with the actual situation.
- * When the length of tool extension from the machine is long, reduce the speed and feed.
 ** When β is less than 15°, speed and feed in the above table can be increased 1,5 to 2 times.

High speed milling

R	Cu				~32 HRC FC250 • SS400 • S55C • NAK55				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
R 0,5	50.000	3.350	0,020	0,050	50.000	2.800	0,020	0,050	50.000	2.500	0,020	0,050	47.500	2.250	0,020	0,050
R 1	31.500	3.350	0,040	0,100	25.000	2.800	0,040	0,100	24.500	2.500	0,040	0,100	23.500	2.250	0,040	0,100
R 1,5	21.000	3.350	0,060	0,150	16.500	2.800	0,060	0,150	16.000	2.500	0,060	0,150	15.500	2.250	0,060	0,150
R 2	15.500	4.080	0,080	0,200	15.500	3.400	0,080	0,200	15.000	2.750	0,080	0,200	13.500	2.450	0,080	0,200
R 2,5	10.500	5.160	0,120	0,300	13.500	4.300	0,300	0,600	11.500	2.750	0,300	0,600	9.500	2.250	0,120	0,300
R 3	7.900	3.840	0,160	0,400	10.000	3.200	0,400	0,800	8.950	2.100	0,400	0,800	7.150	1.700	0,160	0,400
R 4	6.300	3.120	0,200	0,500	8.250	2.600	0,500	1,000	7.150	1.700	0,500	1,000	5.700	1.350	0,200	0,500
R 5	5.250	2.580	0,240	0,600	6.850	2.150	0,500	2,400	5.950	1.400	0,500	2,400	4.750	1.100	0,240	0,600
R 6	4.950	1.550	0,320	0,800	4.110	1.290	0,500	3,200	4.460	1.050	0,500	3,200	3.560	820	0,320	0,800
R 8	3.950	1.240	0,400	1,000	3.250	1.030	0,500	4,000	3.570	840	0,500	4,000	2.850	660	0,320	1,000



1. The indicated speeds and feeds are for high speed light milling with high speed/high precision machining centres.
2. We recommend using an air blow. If using cutting fluids, use a high quality fluid with smoke retardant properties.
3. Refer to top the table above to set the milling conditions in accordance with the actual situation.
4. When β is less than 15°, speed and feed in the above table can be increased 1.2 ~ 1.5 times

Milling | Endmills

Cutting conditions

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-LN-EBD

Regular milling

R	Lg (mm)	Cu					~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
		S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	
0,05	0,3	32.000	150	0,005	0,005	32.000	75	0,005	0,005	32.000	50	0,005	0,005	32.000	35	0,005	0,005	
0,05	0,5	32.000	120	0,005	0,005	32.000	60	0,005	0,005	32.000	40	0,005	0,005	32.000	25	0,005	0,005	
0,1	0,3	32.000	300	0,020	0,020	32.000	200	0,010	0,010	32.000	200	0,010	0,010	32.000	200	0,005	0,005	
0,1	0,5	32.000	300	0,020	0,020	32.000	200	0,010	0,010	32.000	200	0,010	0,010	32.000	200	0,005	0,005	
0,1	0,75	32.000	300	0,020	0,020	32.000	200	0,010	0,010	32.000	200	0,010	0,010	32.000	100	0,005	0,005	
0,1	1	32.000	150	0,020	0,020	32.000	100	0,010	0,010	32.000	100	0,010	0,010	32.000	80	0,005	0,005	
0,1	1,25	32.000	150	0,020	0,020	32.000	100	0,010	0,010	32.000	100	0,010	0,010	32.000	80	0,005	0,005	
0,1	1,5	32.000	150	0,020	0,020	32.000	100	0,010	0,010	32.000	100	0,010	0,010	32.000	80	0,005	0,005	
0,1	1,75	32.000	150	0,020	0,020	32.000	100	0,010	0,010	32.000	100	0,010	0,010	32.000	80	0,005	0,005	
0,1	2	32.000	150	0,010	0,010	32.000	100	0,010	0,010	32.000	100	0,010	0,010	32.000	80	0,005	0,005	
0,1	2,5	32.000	75	0,010	0,010	32.000	50	0,005	0,005	32.000	50	0,005	0,005	32.000	40	0,003	0,005	
0,1	3	32.000	75	0,010	0,010	32.000	50	0,005	0,005	32.000	50	0,005	0,005	32.000	40	0,003	0,005	
0,15	0,5	32.000	600	0,020	0,030	32.000	400	0,010	0,015	32.000	300	0,010	0,015	32.000	300	0,005	0,005	
0,15	0,6	32.000	600	0,020	0,030	32.000	400	0,010	0,015	32.000	300	0,010	0,015	32.000	300	0,005	0,005	
0,15	0,75	32.000	600	0,020	0,030	32.000	400	0,010	0,015	32.000	300	0,010	0,015	32.000	300	0,005	0,005	
0,15	1	32.000	450	0,020	0,030	32.000	300	0,010	0,015	32.000	200	0,010	0,015	32.000	200	0,005	0,005	
0,15	1,25	32.000	450	0,020	0,030	32.000	300	0,010	0,015	32.000	200	0,010	0,015	32.000	200	0,005	0,005	
0,15	1,5	32.000	450	0,020	0,030	32.000	300	0,010	0,015	32.000	200	0,010	0,015	32.000	200	0,005	0,005	
0,15	1,75	32.000	450	0,020	0,030	32.000	300	0,010	0,015	32.000	200	0,010	0,015	32.000	200	0,005	0,005	
0,15	2	32.000	450	0,020	0,030	32.000	300	0,010	0,015	32.000	200	0,010	0,015	32.000	200	0,005	0,005	
0,15	2,25	32.000	450	0,020	0,020	32.000	300	0,010	0,010	32.000	200	0,010	0,010	32.000	200	0,010	0,010	
0,15	2,5	32.000	450	0,020	0,020	32.000	300	0,010	0,010	32.000	200	0,010	0,010	32.000	200	0,010	0,010	
0,15	2,75	32.000	450	0,020	0,020	32.000	300	0,010	0,010	32.000	200	0,010	0,010	32.000	200	0,010	0,010	
0,15	3	32.000	450	0,020	0,020	32.000	300	0,010	0,010	32.000	200	0,010	0,010	32.000	200	0,005	0,010	
0,15	3,5	32.000	270	0,020	0,020	32.000	180	0,010	0,010	32.000	120	0,010	0,010	32.000	120	0,005	0,010	
0,15	4	32.000	270	0,020	0,020	32.000	180	0,010	0,010	32.000	120	0,010	0,010	32.000	120	0,005	0,005	
0,15	4,5	32.000	270	0,020	0,020	32.000	180	0,010	0,010	32.000	120	0,010	0,010	32.000	120	0,003	0,005	
0,15	5	32.000	150	0,010	0,020	32.000	100	0,005	0,010	32.000	70	0,005	0,010	32.000	70	0,003	0,005	
0,2	0,5	32.000	750	0,025	0,050	32.000	500	0,015	0,025	32.000	400	0,015	0,020	32.000	400	0,010	0,010	
0,2	0,75	32.000	750	0,025	0,050	32.000	500	0,015	0,025	32.000	400	0,015	0,020	32.000	400	0,010	0,010	
0,2	1	32.000	600	0,025	0,050	32.000	400	0,015	0,025	32.000	300	0,015	0,020	32.000	300	0,010	0,010	
0,2	1,5	32.000	600	0,025	0,050	32.000	400	0,015	0,025	32.000	300	0,015	0,020	32.000	300	0,010	0,010	
0,2	2	27.000	450	0,025	0,050	27.000	300	0,015	0,025	27.000	200	0,015	0,020	27.000	200	0,010	0,010	
0,2	2,5	27.000	450	0,025	0,050	27.000	300	0,015	0,025	27.000	200	0,015	0,020	27.000	200	0,010	0,010	
0,2	3	27.000	450	0,025	0,050	27.000	300	0,015	0,025	27.000	200	0,015	0,020	27.000	200	0,010	0,010	
0,2	3,5	27.000	450	0,025	0,050	27.000	300	0,015	0,025	27.000	200	0,015	0,020	27.000	200	0,010	0,010	
0,2	4	27.000	450	0,010	0,030	27.000	300	0,005	0,015	27.000	200	0,005	0,012	27.000	200	0,005	0,010	
0,2	4,5	24.000	300	0,010	0,030	27.000	200	0,005	0,015	27.000	100	0,005	0,012	27.000	100	0,005	0,010	
0,2	5	24.000	300	0,010	0,030	27.000	200	0,005	0,015	27.000	100	0,005	0,012	27.000	100	0,005	0,010	
0,2	5,5	21.000	300	0,010	0,020	27.000	200	0,005	0,010	27.000	100	0,005	0,008	27.000	100	0,005	0,005	
0,2	6	21.000	150	0,010	0,015	27.000	100	0,005	0,008	27.000	80	0,005	0,006	27.000	80	0,003	0,005	
0,25	1	32.000	750	0,040	0,050	32.000	500	0,020	0,025	32.000	400	0,020	0,020	32.000	400	0,010	0,010	
0,25	1,5	32.000	750	0,040	0,050	32.000	500	0,020	0,025	32.000	400	0,020	0,020	32.000	400	0,010	0,010	
0,25	2	32.000	600	0,040	0,050	32.000	400	0,020	0,025	32.000	300	0,020	0,020	32.000	300	0,010	0,010	
0,25	2,5	27.000	450	0,040	0,050	27.000	300	0,020	0,025	27.000	200	0,020	0,020	27.000	200	0,010	0,010	
0,25	3	27.000	450	0,040	0,050	27.000	300	0,020	0,025	27.000	200	0,020	0,020	27.000	200	0,010	0,010	
0,25	3,5	27.000	450	0,040	0,050	27.000	300	0,020	0,025	27.000	200	0,020	0,020	27.000	200	0,010	0,010	
0,25	4	27.000	450	0,040	0,050	27.000	300	0,020	0,025	27.000	200	0,020	0,020	27.000	200	0,010	0,010	
0,25	4,5	21.000	300	0,040	0,050	20.000	200	0,020	0,025	20.000	200	0,020	0,020	20.000	200	0,010	0,010	
0,25	5	21.000	300	0,040	0,050	20.000	200	0,020	0,025	20.000	150	0,020	0,020	20.000	150	0,010	0,010	
0,25	5,5	21.000	300	0,020	0,030	20.000	200	0,010	0,015	20.000	150	0,010	0,010	20.000	150	0,010	0,010	
0,25	6	21.000	300	0,020	0,030	20.000	200	0,010	0,015	20.000	150	0,010	0,010	20.000	150	0,010	0,010	
0,25	7	21.000	300	0,020	0,030	20.000	200	0,010	0,015	20.000	150	0,010	0,010	20.000	150	0,010	0,010	
0,25	8	21.000	300	0,020	0,030	15.000	200	0,010	0,015	15.000	150	0,010	0,010	15.000	150	0,005	0,010	
0,25	9	18.000	150	0,020	0,020	15.000	100	0,010	0,010	15.000	80	0,005	0,010	15.000	80	0,005	0,005	
0,25	10	18.000	150	0,010	0,010	15.000	100	0,005	0,005	15.000	80	0,005	0,005	15.000	80	0,003	0,005	
0,3	1	32.000	900	0,045	0,120	32.000	600	0,030	0,060	32.000	500	0,030	0,050	32.000	500	0,030	0,030	
0,3	1,5	32.000	900	0,045	0,120	32.000	600	0,030	0,060	32.000	500	0,030	0,050	32.000	500	0,030	0,030	
0,3	2	32.000	675	0,045	0,120	32.000	450	0,030	0,060	32.000	300	0,030	0,050	32.000	300	0,030	0,030	
0,3	2,5	30.000	675	0,045	0,120	32.000	450	0,030	0,060	32.000	300	0,030	0,050	32.000	300	0,030	0,030	
0,3	3	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,050	24.000	200	0,030	0,030	
0,3	3,5	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,040	24.000	200	0,030	0,030	
0,3	4	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,040	24.000	200	0,030	0,030	
0,3	4,5	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,040	24.000	200	0,030	0,030	
0,3	5	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,040	24.000	200	0,020	0,020	
0,3	5,5	25.000	300	0,045	0,120	20.000	200	0,030	0,060	20.000	200	0,030	0,040	20.000	200	0,020	0,020	
0,3	6	25.000	225	0,045	0,120	20.000	150	0,030	0,060	20.000	150	0,030	0,040	20.000	150	0,020	0,020	
0,3	6,5	25.000	225	0,045	0,120	20.000	150</											

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-LN-EBD

Regular milling

R	Lg (mm)	Cu					~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
		S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	
0,4	7	24.000	375	0,060	0,120	21.000	250	0,040	0,060	19.000	200	0,040	0,050	19.000	200	0,020	0,025	
0,4	8	22.000	225	0,060	0,120	19.000	150	0,040	0,060	17.000	150	0,040	0,050	17.000	150	0,020	0,025	
0,4	9	22.000	225	0,060	0,120	19.000	150	0,040	0,060	17.000	150	0,040	0,050	17.000	150	0,020	0,025	
0,4	10	22.000	225	0,060	0,120	19.000	150	0,040	0,060	17.000	150	0,040	0,050	17.000	150	0,020	0,025	
0,4	12	20.000	225	0,060	0,120	19.000	150	0,040	0,060	17.000	150	0,040	0,050	17.000	150	0,020	0,025	
0,5	2,5	28.000	900	0,075	0,200	25.000	600	0,050	0,100	21.000	400	0,050	0,080	21.000	400	0,050	0,050	
0,5	3	28.000	750	0,075	0,200	25.000	500	0,050	0,100	21.000	300	0,050	0,080	21.000	300	0,050	0,050	
0,5	4	28.000	750	0,075	0,200	25.000	500	0,050	0,100	21.000	300	0,050	0,080	21.000	300	0,050	0,050	
0,5	5	21.000	450	0,075	0,200	19.000	300	0,050	0,100	16.000	200	0,050	0,080	16.000	200	0,050	0,050	
0,5	6	21.000	450	0,075	0,200	19.000	300	0,050	0,100	16.000	200	0,050	0,080	16.000	200	0,050	0,050	
0,5	7	21.000	450	0,075	0,150	19.000	300	0,050	0,075	16.000	200	0,050	0,060	16.000	200	0,030	0,030	
0,5	8	21.000	450	0,075	0,150	19.000	300	0,050	0,075	16.000	200	0,050	0,060	16.000	200	0,030	0,030	
0,5	9	21.000	450	0,075	0,150	19.000	300	0,050	0,075	16.000	200	0,050	0,060	16.000	200	0,030	0,030	
0,5	10	18.000	300	0,060	0,120	17.000	200	0,030	0,050	14.000	150	0,030	0,040	14.000	150	0,010	0,015	
0,5	12	18.000	300	0,060	0,120	17.000	200	0,030	0,050	14.000	150	0,030	0,040	14.000	150	0,010	0,015	
0,5	14	18.000	300	0,060	0,120	17.000	200	0,030	0,050	14.000	150	0,030	0,040	14.000	150	0,010	0,015	
0,5	16	16.000	300	0,060	0,120	13.000	200	0,030	0,050	10.000	150	0,030	0,040	10.000	150	0,010	0,015	
0,5	18	16.000	300	0,060	0,120	13.000	200	0,030	0,050	10.000	150	0,030	0,040	10.000	150	0,010	0,015	
0,5	20	16.000	300	0,060	0,120	13.000	200	0,030	0,050	10.000	150	0,030	0,040	10.000	150	0,010	0,015	
0,5	22	16.000	225	0,050	0,050	13.000	150	0,020	0,025	10.000	100	0,020	0,020	10.000	100	0,005	0,005	
0,6	4	20.000	750	0,090	0,240	17.000	500	0,060	0,120	14.000	300	0,060	0,100	14.000	300	0,060	0,060	
0,6	6	20.000	450	0,090	0,240	17.000	300	0,060	0,120	14.000	200	0,060	0,100	14.000	200	0,060	0,060	
0,6	8	20.000	450	0,090	0,240	17.000	300	0,060	0,120	14.000	200	0,060	0,100	14.000	200	0,060	0,060	
0,6	10	20.000	450	0,090	0,180	17.000	300	0,060	0,090	14.000	200	0,060	0,070	14.000	200	0,030	0,030	
0,6	12	16.000	300	0,090	0,180	14.000	200	0,060	0,090	11.000	150	0,060	0,070	11.000	150	0,030	0,030	
0,6	14	16.000	300	0,090	0,180	14.000	200	0,060	0,090	11.000	150	0,060	0,070	11.000	150	0,010	0,030	
0,6	16	16.000	300	0,090	0,180	14.000	200	0,060	0,090	11.000	150	0,060	0,070	11.000	150	0,010	0,030	
0,6	18	16.000	300	0,090	0,180	14.000	200	0,060	0,090	11.000	150	0,060	0,070	11.000	150	0,010	0,030	
0,6	20	16.000	300	0,090	0,180	14.000	200	0,060	0,090	11.000	150	0,060	0,070	11.000	150	0,010	0,030	
0,6	24	16.000	300	0,090	0,180	14.000	200	0,060	0,090	11.000	150	0,060	0,070	11.000	150	0,010	0,030	
0,7	8	18.000	450	0,100	0,280	15.000	300	0,070	0,140	12.000	250	0,070	0,100	12.000	250	0,070	0,070	
0,7	12	18.000	450	0,100	0,200	15.000	300	0,070	0,100	12.000	250	0,070	0,080	12.000	250	0,070	0,070	
0,7	16	13.000	300	0,090	0,180	12.000	200	0,060	0,090	9.000	150	0,040	0,070	9.000	150	0,010	0,030	
0,75	3	20.000	900	0,120	0,300	15.000	600	0,080	0,150	12.000	500	0,080	0,120	12.000	300	0,080	0,100	
0,75	4	20.000	900	0,120	0,300	15.000	600	0,080	0,150	12.000	500	0,080	0,120	12.000	300	0,080	0,100	
0,75	6	18.000	750	0,120	0,300	15.000	500	0,080	0,150	12.000	350	0,080	0,120	12.000	300	0,080	0,100	
0,75	8	17.000	450	0,120	0,300	15.000	300	0,080	0,150	12.000	250	0,080	0,120	12.000	250	0,080	0,100	
0,75	10	17.000	450	0,120	0,300	15.000	300	0,080	0,150	12.000	250	0,080	0,120	12.000	250	0,080	0,100	
0,75	12	17.000	450	0,120	0,240	15.000	300	0,080	0,120	12.000	250	0,080	0,090	12.000	250	0,050	0,060	
0,75	14	17.000	450	0,120	0,240	15.000	300	0,080	0,120	12.000	250	0,080	0,090	12.000	250	0,050	0,060	
0,75	16	13.000	300	0,090	0,180	12.000	200	0,060	0,100	9.500	150	0,060	0,070	9.500	150	0,010	0,030	
0,75	18	13.000	300	0,090	0,180	12.000	200	0,060	0,100	9.500	150	0,060	0,070	9.500	150	0,010	0,030	
0,75	20	13.000	300	0,090	0,180	12.000	200	0,060	0,100	9.500	150	0,060	0,070	9.500	150	0,010	0,030	
0,75	22	13.000	300	0,090	0,180	12.000	200	0,060	0,100	9.500	150	0,060	0,070	9.500	150	0,010	0,030	
0,75	30	13.000	300	0,090	0,180	12.000	200	0,060	0,100	9.500	150	0,060	0,070	9.500	150	0,010	0,030	
0,8	4	20.000	900	0,120	0,320	14.000	600	0,080	0,160	11.000	500	0,080	0,130	11.000	350	0,080	0,100	
0,8	8	16.500	450	0,120	0,320	14.000	300	0,080	0,160	11.000	250	0,080	0,130	11.000	250	0,080	0,100	
0,8	12	16.500	450	0,120	0,240	14.000	300	0,080	0,120	11.000	250	0,080	0,080	11.000	250	0,050	0,050	
0,8	16	11.500	300	0,120	0,240	11.000	200	0,080	0,120	9.000	150	0,080	0,080	9.000	150	0,050	0,050	
0,8	20	11.500	300	0,090	0,200	11.000	200	0,060	0,120	9.000	150	0,060	0,075	9.000	150	0,015	0,030	
0,9	8	16.500	600	0,130	0,360	14.000	400	0,090	0,180	11.000	300	0,090	0,160	11.000	300	0,090	0,120	
0,9	12	16.500	600	0,130	0,360	14.000	400	0,090	0,180	11.000	300	0,090	0,160	11.000	300	0,090	0,120	
0,9	16	16.500	600	0,130	0,270	14.000	400	0,090	0,140	11.000	300	0,090	0,120	11.000	300	0,050	0,060	
0,9	20	11.000	300	0,100	0,220	11.000	200	0,060	0,130	8.000	200	0,060	0,080	8.000	200	0,020	0,030	
1	3	16.500	1.350	0,150	0,560	16.500	900	0,100	0,280	13.500	800	0,100	0,280	13.500	700	0,100	0,200	
1	4	16.500	1.050	0,150	0,560	16.500	700	0,100	0,280	13.500	500	0,100	0,280	13.500	500	0,100	0,200	
1	6	16.500	1.050	0,150	0,560	16.500	700	0,100	0,280	13.500	500	0,100	0,280	13.500	500	0,100	0,200	
1	8	16.500	1.050	0,150	0,560	16.500	700	0,100	0,280	13.500	500	0,100	0,280	13.500	500	0,100	0,200	
1	10	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200	
1	12	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200	
1	14	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200	
1	16	14.000	750	0,150	0,420	13.000	500	0,100	0,210	10.000	300	0,100	0,180	10.000	300	0,060	0,100	
1	18	14.000	750	0,150	0,420	13.000	500	0,100	0,210	10.000	300	0,100	0,180	10.000	300	0,060	0,100	
1	20	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100	
1	22	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100	
1	25	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100	
1	30	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100	
1	35	10.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,		

CUTTING CONDITIONS


Milling | Endmills | Cutting conditions

WXL-LN-EBD

Regular milling

R	Lg (mm)	Cu					~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
		S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	
1,5	15	10.000	600	0,200	0,840	8.500	400	0,150	0,420	6.500	250	0,150	0,360	6.500	250	0,150	0,300	
1,5	16	10.000	450	0,200	0,840	8.500	300	0,150	0,420	6.500	250	0,150	0,360	6.500	250	0,150	0,300	
1,5	20	10.000	450	0,200	0,840	8.500	300	0,150	0,420	6.500	250	0,150	0,360	6.500	250	0,150	0,300	
1,5	25	10.000	450	0,200	0,840	8.500	300	0,150	0,420	6.500	250	0,150	0,300	6.500	250	0,090	0,150	
1,5	30	9.000	375	0,200	0,840	7.500	250	0,150	0,420	6.000	200	0,150	0,300	6.000	200	0,090	0,150	
1,5	35	9.000	375	0,200	0,840	7.500	250	0,150	0,420	6.000	200	0,150	0,300	6.000	200	0,090	0,150	
1,5	40	9.000	375	0,200	0,840	7.500	250	0,150	0,420	6.000	200	0,150	0,300	6.000	200	0,090	0,150	
1,75	10	10.000	1.050	0,400	0,980	8.500	700	0,150	0,420	6.500	500	0,150	0,420	6.500	500	0,150	0,350	
1,75	15	10.000	900	0,400	0,980	8.500	600	0,150	0,420	6.500	400	0,150	0,420	6.500	400	0,150	0,350	
1,75	20	8.000	750	0,400	0,980	7.500	500	0,150	0,490	5.500	300	0,150	0,420	5.500	300	0,150	0,350	
1,75	25	8.000	600	0,400	0,980	7.500	400	0,150	0,490	5.500	275	0,150	0,420	5.500	275	0,150	0,350	
1,75	30	8.000	450	0,400	0,980	7.500	300	0,150	0,490	5.500	250	0,150	0,350	5.500	250	0,100	0,200	
1,75	35	8.000	375	0,400	0,980	6.000	250	0,150	0,490	5.000	200	0,150	0,350	5.000	200	0,100	0,200	
1,75	40	6.000	375	0,300	0,980	6.000	250	0,150	0,490	5.000	200	0,150	0,350	5.000	200	0,100	0,200	
1,75	45	6.000	375	0,300	0,980	6.000	250	0,150	0,490	5.000	200	0,150	0,350	5.000	200	0,100	0,200	
2	8	11.000	1.200	0,500	1,280	7.500	800	0,200	0,640	6.000	700	0,200	0,600	6.000	700	0,200	0,400	
2	10	9.000	900	0,500	1,280	7.500	600	0,200	0,640	6.000	400	0,200	0,600	6.000	400	0,200	0,400	
2	12	9.000	900	0,500	1,280	7.500	600	0,200	0,640	6.000	400	0,200	0,600	6.000	400	0,200	0,400	
2	14	9.000	900	0,500	1,280	7.500	600	0,200	0,640	6.000	400	0,200	0,600	6.000	400	0,200	0,400	
2	15	9.000	900	0,500	1,280	7.500	600	0,200	0,640	6.000	400	0,200	0,600	6.000	400	0,200	0,400	
2	16	9.000	900	0,500	1,280	7.500	600	0,200	0,640	6.000	400	0,200	0,600	6.000	400	0,200	0,400	
2	20	7.000	600	0,500	1,280	6.000	400	0,200	0,640	5.000	250	0,200	0,600	5.000	250	0,200	0,400	
2	25	7.000	600	0,500	1,280	6.000	400	0,200	0,640	5.000	250	0,200	0,600	5.000	250	0,200	0,400	
2	30	7.000	600	0,400	1,280	6.000	400	0,200	0,640	5.000	250	0,200	0,560	5.000	250	0,120	0,200	
2	35	7.000	600	0,400	1,280	6.000	400	0,200	0,640	5.000	250	0,200	0,560	5.000	250	0,120	0,200	
2	40	5.000	375	0,350	1,280	5.000	250	0,200	0,640	4.000	200	0,200	0,560	4.000	200	0,120	0,200	
2	45	5.000	375	0,350	1,280	5.000	250	0,200	0,640	4.000	200	0,200	0,560	4.000	200	0,120	0,200	
2	50	5.000	375	0,350	1,280	5.000	250	0,200	0,640	4.000	200	0,200	0,560	4.000	200	0,120	0,200	
2,5	10	9.000	1.350	0,600	1,800	6.500	900	0,250	0,900	5.000	750	0,250	0,700	5.000	750	0,250	0,500	
2,5	15	9.000	1.350	0,600	1,800	6.500	900	0,250	0,900	5.000	750	0,250	0,700	5.000	750	0,250	0,500	
2,5	20	7.000	750	0,600	1,800	6.500	500	0,250	0,900	5.000	400	0,250	0,700	5.000	400	0,250	0,500	
2,5	25	6.000	750	0,600	1,800	5.000	500	0,250	0,900	4.000	250	0,250	0,700	4.000	250	0,250	0,500	
2,5	30	6.000	750	0,600	1,800	5.000	500	0,250	0,900	4.000	250	0,250	0,700	4.000	250	0,250	0,500	
2,5	35	6.000	750	0,600	1,800	5.000	500	0,250	0,900	4.000	250	0,250	0,700	4.000	250	0,250	0,500	
2,5	40	5.000	600	0,400	1,800	4.000	400	0,250	0,900	4.000	200	0,250	0,600	4.000	200	0,200	0,250	
2,5	45	5.000	600	0,400	1,800	4.000	400	0,250	0,900	4.000	200	0,250	0,600	4.000	200	0,200	0,250	
2,5	50	5.000	450	0,400	1,800	4.000	300	0,250	0,900	4.000	200	0,250	0,600	4.000	200	0,200	0,250	
3	10	7.000	1.500	0,750	2,400	5.500	1.000	0,300	1,200	4.500	800	0,300	0,960	4.500	800	0,300	0,600	
3	20	7.000	1.200	0,750	2,400	5.500	800	0,300	1,200	4.500	600	0,300	0,960	4.500	600	0,300	0,600	
3	25	6.000	900	0,750	2,400	5.500	600	0,300	1,200	4.500	400	0,300	0,960	4.500	400	0,300	0,600	
3	30	5.000	600	0,750	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,600	
3	35	5.000	600	0,750	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,600	
3	40	5.000	600	0,600	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,600	
3	45	5.000	600	0,600	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,600	
3	50	5.000	600	0,600	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,600	

Max cutting depth



1. Use a rigid and precise machine and holder.
2. When machining carbon steel or hardened steel, using MQL (Minimum Quantity Lubrication / mist coolant) is recommended.
3. Please adjust conditions based on machining accuracy, machining shape and machining path.
4. When using a tool with a diameter of dia. 0.5 (R0.25) or less, or an L/D (effective length/tool diameter) ratio greater than 10, high loads can cause tool breakage. Therefore, adjust the cutting conditions based on the machining situation.
5. When the available RPM is insufficient, reduce the RPM and feed rates in proportion

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-LN-EBD

High speed milling



R	Lg (mm)	Cu				~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
		S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
0,05	0,3	50.000	280	0,003	0,005	50.000	150	0,003	0,003	50.000	100	0,003	0,003	50.000	70	0,003	0,003
0,05	0,5	50.000	220	0,003	0,005	50.000	120	0,003	0,003	50.000	80	0,003	0,003	50.000	50	0,003	0,003
0,1	0,3	50.000	490	0,008	0,010	50.000	400	0,005	0,005	50.000	380	0,005	0,005	50.000	380	0,005	0,005
0,1	0,5	50.000	490	0,008	0,010	50.000	400	0,005	0,005	50.000	380	0,005	0,005	50.000	380	0,005	0,005
0,1	0,75	50.000	440	0,008	0,010	50.000	360	0,005	0,005	50.000	340	0,005	0,005	50.000	340	0,005	0,005
0,1	1	50.000	440	0,008	0,010	50.000	360	0,005	0,005	50.000	340	0,005	0,005	50.000	340	0,005	0,005
0,1	1,25	50.000	390	0,008	0,010	47.000	320	0,005	0,005	47.000	300	0,005	0,005	47.000	300	0,005	0,005
0,1	1,5	50.000	360	0,008	0,010	45.000	300	0,005	0,005	45.000	280	0,005	0,005	45.000	280	0,005	0,005
0,1	1,75	50.000	350	0,008	0,010	42.000	260	0,005	0,005	42.000	240	0,005	0,005	42.000	240	0,005	0,005
0,1	2	50.000	320	0,008	0,010	38.000	230	0,005	0,005	38.000	210	0,005	0,005	37.000	200	0,005	0,005
0,15	0,5	50.000	750	0,008	0,020	50.000	620	0,005	0,010	50.000	600	0,005	0,010	50.000	600	0,005	0,010
0,15	0,6	50.000	730	0,008	0,020	50.000	600	0,005	0,010	50.000	570	0,005	0,010	50.000	570	0,005	0,010
0,15	0,75	50.000	730	0,008	0,020	50.000	600	0,005	0,010	50.000	570	0,005	0,010	50.000	570	0,005	0,010
0,15	1	50.000	730	0,008	0,020	50.000	600	0,005	0,010	50.000	570	0,005	0,010	50.000	570	0,005	0,010
0,15	1,25	50.000	730	0,008	0,020	50.000	600	0,005	0,010	50.000	570	0,005	0,010	50.000	570	0,005	0,010
0,15	1,5	50.000	730	0,008	0,020	50.000	600	0,005	0,010	50.000	570	0,005	0,010	50.000	570	0,005	0,010
0,15	1,75	50.000	610	0,008	0,020	47.000	510	0,005	0,010	47.000	480	0,005	0,010	47.000	480	0,005	0,010
0,15	2	50.000	580	0,008	0,010	45.000	480	0,005	0,005	45.000	450	0,005	0,005	45.000	450	0,005	0,005
0,15	2,25	50.000	490	0,008	0,010	45.000	400	0,005	0,005	45.000	380	0,005	0,005	45.000	380	0,005	0,005
0,15	2,5	50.000	360	0,008	0,010	40.000	300	0,005	0,005	40.000	280	0,005	0,005	40.000	280	0,005	0,005
0,15	2,75	50.000	320	0,008	0,010	38.000	250	0,005	0,005	38.000	230	0,005	0,005	38.000	230	0,005	0,005
0,15	3	50.000	290	0,008	0,010	38.000	250	0,005	0,005	38.000	230	0,005	0,005	37.000	230	0,005	0,005
0,2	0,5	50.000	1.100	0,015	0,040	50.000	920	0,020	0,010	50.000	870	0,010	0,020	50.000	870	0,010	0,020
0,2	0,75	50.000	1.090	0,015	0,040	50.000	900	0,020	0,010	50.000	850	0,010	0,020	50.000	850	0,010	0,020
0,2	1	50.000	1.090	0,015	0,040	50.000	900	0,020	0,010	50.000	850	0,010	0,020	50.000	850	0,010	0,020
0,2	1,5	50.000	970	0,015	0,040	50.000	800	0,020	0,010	50.000	760	0,010	0,020	50.000	760	0,010	0,020
0,2	2	50.000	850	0,015	0,040	50.000	700	0,020	0,010	50.000	660	0,010	0,020	50.000	660	0,010	0,020
0,2	2,5	50.000	670	0,012	0,030	45.000	550	0,015	0,008	45.000	520	0,010	0,015	45.000	520	0,008	0,015
0,2	3	48.000	540	0,008	0,020	43.000	500	0,005	0,010	43.000	470	0,010	0,010	43.000	470	0,005	0,010
0,2	3,5	45.000	460	0,008	0,020	40.000	420	0,005	0,010	40.000	400	0,010	0,010	40.000	400	0,005	0,010
0,2	4	40.000	400	0,008	0,010	36.000	370	0,005	0,005	36.000	350	0,010	0,005	35.000	340	0,005	0,005
0,25	1	50.000	1.420	0,023	0,045	50.000	1.100	0,015	0,030	50.000	1.050	0,010	0,030	50.000	1.050	0,015	0,030
0,25	1,5	50.000	1.420	0,023	0,045	50.000	1.100	0,015	0,030	50.000	1.050	0,010	0,030	50.000	1.050	0,015	0,030
0,25	2	50.000	1.400	0,023	0,045	50.000	1.000	0,015	0,030	50.000	950	0,010	0,030	50.000	950	0,015	0,030
0,25	2,5	50.000	1.380	0,023	0,045	50.000	1.000	0,015	0,030	50.000	950	0,010	0,030	50.000	950	0,015	0,030
0,25	3	50.000	1.190	0,015	0,040	48.000	900	0,010	0,020	48.000	850	0,010	0,020	48.000	850	0,010	0,020
0,25	3,5	50.000	1.140	0,015	0,040	45.000	700	0,010	0,020	45.000	650	0,010	0,020	45.000	650	0,010	0,020
0,25	4	45.000	1.000	0,015	0,020	43.000	600	0,010	0,010	43.000	570	0,010	0,010	43.000	570	0,010	0,010
0,25	4,5	38.000	940	0,015	0,020	38.000	500	0,010	0,010	38.000	470	0,010	0,010	38.000	470	0,010	0,010
0,25	5	30.000	760	0,008	0,020	30.000	400	0,005	0,010	30.000	380	0,005	0,010	29.000	360	0,005	0,010
0,3	1	50.000	1.660	0,045	0,100	50.000	1.400	0,030	0,050	50.000	1.300	0,030	0,050	50.000	1.300	0,030	0,050
0,3	1,5	50.000	1.600	0,045	0,100	50.000	1.300	0,030	0,050	50.000	1.200	0,030	0,050	50.000	1.200	0,030	0,050
0,3	2	50.000	1.600	0,045	0,100	50.000	1.300	0,030	0,050	50.000	1.200	0,030	0,050	50.000	1.200	0,030	0,050
0,3	2,5	50.000	1.550	0,045	0,100	50.000	1.200	0,030	0,050	50.000	1.100	0,030	0,050	50.000	1.100	0,030	0,050
0,3	3	50.000	1.550	0,030	0,060	50.000	1.200	0,020	0,030	50.000	1.100	0,020	0,030	50.000	1.100	0,020	0,030
0,3	3,5	50.000	1.340	0,030	0,060	45.000	1.000	0,020	0,030	45.000	950	0,020	0,030	45.000	950	0,020	0,030
0,3	4	50.000	1.200	0,015	0,040	40.000	900	0,010	0,020	40.000	850	0,010	0,020	40.000	850	0,010	0,020
0,3	4,5	45.000	1.040	0,015	0,040	34.000	780	0,010	0,020	34.000	740	0,010	0,020	34.000	740	0,010	0,020
0,3	5	30.000	960	0,015	0,040	30.000	680	0,010	0,020	30.000	640	0,010	0,020	30.000	640	0,010	0,020
0,3	5,5	30.000	820	0,015	0,040	28.000	650	0,010	0,020	28.000	610	0,010	0,020	28.000	610	0,010	0,020
0,3	6	30.000	720	0,015	0,040	26.000	600	0,010	0,020	26.000	570	0,010	0,020	25.000	540	0,010	0,020
0,4	2	50.000	2.200	0,060	0,160	50.000	2.000	0,040	0,080	50.000	1.900	0,040	0,080	50.000	1.900	0,040	0,080
0,4	3	50.000	1.740	0,060	0,160	48.000	1.600	0,040	0,080	48.000	1.500	0,040	0,080	48.000	1.500	0,040	0,080
0,4	4	50.000	1.680	0,060	0,160	40.000	1.200	0,040	0,080	40.000	1.100	0,040	0,080	40.000	1.100	0,040	0,080
0,4	5	43.000	1.600	0,045	0,100	34.000	950	0,030	0,050	34.000	900	0,030	0,050	34.000	900	0,030	0,050
0,4	6	32.000	1.260	0,045	0,100	30.000	800	0,030	0,050	30.000	760	0,030	0,050	30.000	760	0,030	0,050
0,4	7	30.000	1.000	0,020	0,080	25.000	600	0,010	0,020	25.000	570	0,010	0,020	25.000	570	0,010	0,020
0,4	8	24.000	720	0,010	0,040	23.000	450	0,005	0,010	23.000	420	0,005	0,010	23.000	420	0,005	0,010
0,5	2,5	50.000	3.270	0,075	0,200	50.000	3.400	0,050	0,100	50.000	3.200	0,050	0,100	50.000	3.200	0,050	0,100
0,5	3	50.000	3.060	0,075	0,200	45.000	3.200	0,050	0,100	45.000	3.000	0,050	0,100	45.000	3.000	0,050	0,100
0,5	4	50.000	3.000	0,075	0,200	40.000	3.000	0,050	0,100	40.000	2.850	0,050	0,100	40.000	2.850	0,050	0,100
0,5	5	47.000	2.870	0,075	0,200	36.000	2.300	0,050	0,100	36.000	2.100	0,050	0,100	36.000	2.100	0,050	0,100
0,5	6	43.000	2.600	0,075	0,200	30.000	2.000	0,050	0,100	30.000	1.900	0,050	0,100	30.000	1.900	0,050	0,100
0,5	7	30.000	2.350	0,075	0,150	27.000	1.700	0,050	0,100	27.000	1.600	0,050	0,100	27.000	1.600	0,050	0,100
0,5	8	27.000	2.000	0,075	0,150	26.000	1.600	0,050	0,100	26.000	1.500	0,050	0,100	26.000	1.500	0,050	0,100
0,5	9	26.000	1.540	0,045	0,075	24.000	1.200	0,030	0,050	24.000	1.100	0,030	0,050	24.000	1.100	0,030	0,050
0,5	10																

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-LN-EBD

High speed milling

R	Lg (mm)	Cu					~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
		S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	
0,8	8	26.000	3.000	0,160	0,320	24.000	3.000	0,080	0,160	24.000	2.800	0,080	0,160	23.000	2.600	0,080	0,160	
0,8	12	24.000	2.400	0,120	0,200	21.000	1.800	0,050	0,100	21.000	1.700	0,050	0,100	20.000	1.600	0,050	0,100	
0,8	16	18.000	1.600	0,100	0,200	16.000	800	0,050	0,100	16.000	760	0,050	0,100	15.000	700	0,050	0,100	
0,9	8	25.000	3.200	0,180	0,540	24.000	3.000	0,090	0,270	24.000	2.800	0,090	0,270	23.000	2.600	0,090	0,270	
0,9	12	22.000	2.500	0,180	0,360	18.000	1.800	0,090	0,180	15.800	1.500	0,090	0,180	14.700	1.350	0,090	0,180	
0,9	16	16.000	1.200	0,100	0,240	16.000	980	0,050	0,120	14.000	850	0,050	0,120	13.000	780	0,050	0,120	
1	3	50.000	5.800	0,200	0,400	50.000	5.600	0,100	0,200	50.000	5.600	0,100	0,200	47.000	5.300	0,100	0,200	
1	4	50.000	5.800	0,200	0,400	50.000	5.600	0,100	0,200	50.000	5.600	0,100	0,200	47.000	5.300	0,100	0,200	
1	6	38.000	4.000	0,200	0,400	36.000	3.000	0,100	0,200	36.000	2.800	0,100	0,200	34.000	2.600	0,100	0,200	
1	8	27.000	3.360	0,200	0,400	25.000	2.600	0,100	0,200	25.000	2.400	0,100	0,200	23.000	2.200	0,100	0,200	
1	10	22.000	3.050	0,200	0,400	20.000	2.400	0,100	0,200	20.000	2.200	0,100	0,200	19.000	2.000	0,100	0,200	
1	12	16.000	2.580	0,200	0,400	16.000	2.000	0,100	0,200	16.000	1.900	0,100	0,200	15.000	1.700	0,100	0,200	
1	14	15.000	2.400	0,200	0,300	15.000	1.800	0,100	0,200	15.000	1.700	0,100	0,200	14.000	1.500	0,100	0,200	
1	16	14.000	2.200	0,200	0,200	14.000	1.700	0,100	0,100	14.000	1.600	0,100	0,100	13.000	1.400	0,100	0,100	
1	18	13.000	2.000	0,200	0,200	13.000	1.600	0,100	0,100	13.000	1.500	0,100	0,100	12.000	1.300	0,100	0,100	
1	20	12.000	1.200	0,100	0,200	12.000	1.200	0,050	0,100	11.000	1.100	0,050	0,100	10.000	1.000	0,000	0,100	
1,25	6	32.000	5.550	0,250	0,400	28.000	4.600	0,100	0,200	28.000	4.300	0,100	0,200	25.000	3.700	0,100	0,200	
1,25	10	21.000	4.000	0,250	0,400	20.000	3.300	0,100	0,200	20.000	3.100	0,100	0,200	18.000	2.700	0,100	0,200	
1,25	15	17.000	3.000	0,250	0,400	17.000	2.800	0,100	0,200	17.000	2.600	0,100	0,200	16.000	2.400	0,100	0,200	
1,25	20	15.000	1.800	0,250	0,400	15.000	1.800	0,100	0,200	15.000	1.700	0,100	0,200	14.000	1.500	0,100	0,200	
1,25	25	12.000	1.010	0,060	0,100	12.000	1.000	0,030	0,050	12.000	950	0,030	0,050	10.000	860	0,030	0,050	
1,25	30	10.000	800	0,060	0,100	-	-	-	-	-	-	-	-	-	-	-	-	
1,5	6	42.000	6.800	0,300	0,600	41.500	6.200	0,150	0,300	41.500	6.200	0,150	0,300	32.000	4.800	0,150	0,300	
1,5	8	32.000	4.600	0,300	0,600	30.000	4.500	0,150	0,300	30.000	4.200	0,150	0,300	25.000	3.500	0,150	0,300	
1,5	10	28.000	4.000	0,300	0,600	25.000	3.800	0,150	0,300	25.000	3.600	0,150	0,300	20.000	2.800	0,150	0,300	
1,5	12	24.000	3.100	0,300	0,600	20.000	3.000	0,150	0,300	20.000	2.800	0,150	0,300	18.000	2.500	0,150	0,300	
1,5	14	22.000	2.900	0,300	0,600	18.000	2.700	0,150	0,300	18.000	2.500	0,150	0,300	15.000	2.000	0,150	0,300	
1,5	15	20.000	2.800	0,250	0,600	16.000	2.400	0,100	0,300	16.000	2.200	0,100	0,300	13.000	1.700	0,100	0,300	
1,5	16	20.000	2.600	0,250	0,400	16.000	2.000	0,100	0,200	16.000	1.900	0,100	0,200	13.000	1.500	0,100	0,200	
1,5	20	16.000	2.200	0,250	0,400	14.000	1.800	0,100	0,200	14.000	1.700	0,100	0,200	11.000	1.300	0,100	0,200	
1,5	25	16.000	1.800	0,125	0,200	12.000	1.200	0,050	0,100	12.000	1.100	0,050	0,100	9.000	820	0,050	0,100	
1,5	30	12.000	1.000	0,075	0,100	10.000	800	0,030	0,050	9.000	760	0,030	0,050	7.800	590	0,030	0,050	
1,75	10	26.000	5.400	0,375	0,600	25.000	3.750	0,150	0,300	25.000	3.500	0,150	0,300	19.500	2.660	0,150	0,300	
1,75	15	20.000	4.000	0,300	0,600	18.000	3.000	0,100	0,300	18.000	2.800	0,100	0,300	14.000	2.180	0,100	0,300	
1,75	20	18.000	3.000	0,300	0,400	16.000	2.700	0,100	0,200	16.000	2.500	0,100	0,200	12.000	1.850	0,100	0,200	
1,75	25	14.000	2.800	0,200	0,200	12.000	2.000	0,100	0,100	12.000	1.900	0,100	0,100	9.000	1.400	0,100	0,100	
1,75	30	10.000	2.200	0,125	0,200	10.000	1.600	0,050	0,100	10.000	1.500	0,050	0,100	8.000	1.200	0,050	0,100	
1,75	35	10.000	1.200	0,100	0,100	10.000	1.000	0,050	0,050	10.000	950	0,050	0,050	7.000	670	0,050	0,050	
2	8	31.000	5.700	0,400	1,000	31.000	5.700	0,200	0,500	31.000	5.700	0,200	0,500	24.000	4.400	0,200	0,500	
2	10	25.000	4.500	0,400	1,000	25.000	4.500	0,200	0,500	25.000	4.200	0,200	0,500	20.000	3.300	0,200	0,500	
2	12	20.000	4.000	0,400	1,000	20.000	3.600	0,200	0,500	20.000	3.400	0,200	0,500	16.000	2.700	0,200	0,500	
2	14	20.000	4.000	0,400	1,000	20.000	3.600	0,200	0,500	20.000	3.400	0,200	0,500	16.000	2.700	0,200	0,500	
2	15	20.000	4.000	0,400	1,000	20.000	3.600	0,200	0,500	20.000	3.400	0,200	0,500	16.000	2.700	0,200	0,500	
2	16	20.000	3.460	0,400	0,600	18.000	3.200	0,200	0,500	18.000	3.000	0,200	0,500	14.000	2.300	0,200	0,500	
2	20	18.000	3.000	0,400	0,500	16.000	2.800	0,200	0,400	16.000	2.600	0,200	0,400	12.000	1.900	0,200	0,400	
2	25	18.000	3.000	0,250	0,600	16.000	2.800	0,100	0,300	16.000	2.600	0,100	0,300	12.000	1.900	0,100	0,300	
2	30	16.000	2.850	0,250	0,400	14.000	2.400	0,100	0,200	14.000	2.200	0,100	0,200	11.000	1.700	0,100	0,200	
2	35	14.000	2.200	0,250	0,400	12.000	1.800	0,100	0,200	12.000	1.700	0,100	0,200	9.000	1.700	0,100	0,200	
2	40	12.000	1.600	0,125	0,200	10.000	1.300	0,050	0,100	10.000	1.200	0,050	0,100	7.000	840	0,050	0,100	
2,5	10	25.000	5.600	0,500	1,250	25.000	5.400	0,250	0,500	25.000	5.400	0,250	0,500	19.000	4.000	0,250	0,500	
2,5	15	20.000	4.400	0,500	1,250	20.000	4.200	0,250	0,500	20.000	3.900	0,250	0,500	16.000	3.100	0,250	0,500	
2,5	20	18.000	3.800	0,500	1,250	16.000	3.500	0,250	0,500	16.000	3.300	0,250	0,500	12.000	2.400	0,250	0,500	
2,5	25	20.000	3.400	0,400	0,750	15.000	3.200	0,200	0,300	15.000	3.000	0,200	0,300	12.000	2.400	0,200	0,300	
2,5	30	16.000	2.900	0,250	0,750	14.000	2.500	0,100	0,300	14.000	2.300	0,100	0,300	11.000	1.800	0,100	0,300	
2,5	35	14.000	2.200	0,250	0,750	12.000	1.600	0,100	0,300	12.000	1.500	0,100	0,300	9.000	1.100	0,100	0,300	
2,5	40	12.000	1.800	0,250	0,500	10.000	1.200	0,100	0,200	10.000	1.100	0,100	0,200	8.000	880	0,100	0,200	
2,5	45	9.000	1.200	0,200	0,250	9.000	900	0,100	0,100	9.000	850	0,100	0,100	7.000	660	0,100	0,100	
2,5	50	8.000	1.100	0,200	0,250	8.000	800	0,100	0,100	8.000	760	0,100	0,100	6.000	570	0,100	0,100	
3	10	22.000	5.900	0,750	1,250	20.000	5.400	0,300	0,500	20.000	5.000	0,300	0,500	15.000	3.750	0,300	0,500	
3	20	18.000	4.400	0,750	1,250	16.000	4.200	0,300	0,500	16.000	3.900	0,300	0,500	12.000	2.900	0,300	0,500	
3	25	14.000	4.000	0,600	1,250	12.000	3.200	0,300	0,500	12.000	3.000	0,300	0,500	9.000	2.250	0,300	0,500	
3	30	10.000	3.200	0,600	1,250	10.000	2.600	0,300	0,500	10.000	2.400	0,300	0,500	8.000	1.900	0,300	0,500	
3	35	9.000	3.000	0,400	1,000	9.000	2.300	0,200	0,400	9.000	2.100	0,200	0,400	7.000	1.600	0,200	0,400	
3	40	9.000	2.800	0,400	0,750	9.000	2.000	0,200	0,300	9.000	1.900	0,200	0,300	7.000	1.400	0,200	0,300	
3	45	8.000	2.500	0,400	0,750	8.000	1.800	0,200	0,300	8.000	1.700	0,200	0,300	6.500	1.300	0,200	0,300	
3	50	7.000	2.300	0,400	0,750	7.000	1.600	0,200	0,300	7.000	1.500	0,200</						

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-PC-EBD

Regular milling

R	θ	l2	Cutting angle	Cu				~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
				S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
0,1	0,5°	1	0,3°	32.000	200	0,020	0,020	32.000	150	0,010	0,010	32.000	150	0,010	0,010	32.000	100	0,005	0,005
0,1	0,5°	1,5	0,3°	32.000	200	0,020	0,020	32.000	150	0,010	0,010	32.000	150	0,010	0,010	32.000	100	0,005	0,005
0,1	0,5°	2	0,3°	32.000	150	0,020	0,020	32.000	100	0,010	0,010	32.000	100	0,010	0,010	32.000	80	0,005	0,005
0,1	0,5°	2,5	0,3°	32.000	150	0,010	0,010	32.000	100	0,005	0,005	32.000	100	0,005	0,005	32.000	80	0,005	0,005
0,1	0,5°	3	0,3°	32.000	100	0,010	0,010	32.000	80	0,005	0,005	32.000	80	0,005	0,005	32.000	60	0,003	0,005
0,1	1°	2	0,3°	32.000	150	0,020	0,020	32.000	100	0,010	0,010	32.000	100	0,010	0,010	32.000	80	0,005	0,005
0,1	1°	2,5	0,3°	32.000	150	0,020	0,020	32.000	100	0,010	0,010	32.000	100	0,010	0,010	32.000	80	0,005	0,005
0,1	1°	3	0,3°	32.000	150	0,010	0,010	32.000	100	0,005	0,005	32.000	100	0,005	0,005	32.000	80	0,005	0,005
0,15	0,5°	2	0,3°	32.000	600	0,020	0,030	32.000	300	0,010	0,015	32.000	200	0,010	0,015	32.000	200	0,005	0,005
0,15	0,5°	3	0,3°	32.000	450	0,020	0,020	32.000	300	0,010	0,010	32.000	200	0,010	0,010	32.000	200	0,010	0,010
0,15	1°	3	0,3°	32.000	450	0,020	0,020	32.000	300	0,010	0,015	32.000	200	0,010	0,015	32.000	200	0,005	0,005
0,15	1°	4	0,3°	32.000	450	0,020	0,020	32.000	300	0,010	0,010	32.000	200	0,010	0,010	32.000	200	0,010	0,010
0,2	0,5°	2	0,3°	27.000	450	0,030	0,050	32.000	400	0,015	0,025	32.000	300	0,015	0,020	32.000	300	0,010	0,010
0,2	0,5°	3	0,3°	27.000	450	0,025	0,050	27.000	300	0,015	0,025	27.000	200	0,015	0,020	27.000	200	0,010	0,010
0,2	0,5°	4	0,3°	27.000	450	0,020	0,050	27.000	300	0,015	0,025	27.000	200	0,015	0,020	27.000	200	0,010	0,010
0,2	0,5°	5	0,3°	27.000	400	0,015	0,050	27.000	300	0,005	0,015	27.000	200	0,005	0,012	27.000	200	0,005	0,010
0,2	0,5°	6	0,3°	27.000	300	0,010	0,030	27.000	300	0,005	0,015	27.000	200	0,005	0,012	27.000	200	0,005	0,010
0,2	1°	4	0,3°	27.000	450	0,025	0,050	27.000	300	0,015	0,025	27.000	200	0,015	0,020	27.000	200	0,010	0,010
0,2	1°	5	0,3°	27.000	450	0,020	0,050	27.000	300	0,015	0,025	27.000	200	0,015	0,020	27.000	200	0,010	0,010
0,2	1°	6	0,3°	27.000	400	0,015	0,050	27.000	300	0,005	0,015	27.000	200	0,005	0,012	27.000	200	0,005	0,010
0,25	0,5°	4	0,3°	32.000	600	0,040	0,050	32.000	400	0,020	0,025	32.000	300	0,020	0,020	32.000	300	0,010	0,015
0,25	0,5°	6	0,3°	27.000	450	0,040	0,050	20.000	200	0,020	0,025	20.000	150	0,020	0,020	20.000	150	0,010	0,010
0,25	0,5°	8	0,3°	21.000	300	0,020	0,030	20.000	200	0,010	0,015	20.000	150	0,010	0,010	20.000	150	0,010	0,010
0,25	0,5°	10	0,3°	21.000	300	0,020	0,030	20.000	200	0,010	0,015	20.000	150	0,010	0,010	20.000	150	0,005	0,010
0,25	1°	4	0,3°	32.000	600	0,040	0,050	32.000	400	0,020	0,025	32.000	300	0,020	0,020	32.000	300	0,010	0,010
0,25	1°	6	0,3°	27.000	450	0,040	0,050	32.000	400	0,020	0,025	32.000	300	0,020	0,020	32.000	300	0,010	0,010
0,25	1°	8	0,3°	27.000	450	0,040	0,050	20.000	200	0,020	0,025	20.000	150	0,020	0,020	20.000	150	0,010	0,010
0,25	1°	10	0,3°	21.000	300	0,020	0,030	20.000	200	0,020	0,025	20.000	150	0,020	0,020	20.000	150	0,010	0,010
0,25	1°	12	0,3°	21.000	300	0,020	0,030	20.000	200	0,010	0,015	20.000	150	0,010	0,010	20.000	150	0,010	0,010
0,3	0,5°	2	0,3°	32.000	675	0,045	0,120	32.000	450	0,030	0,060	32.000	300	0,030	0,050	32.000	300	0,030	0,030
0,3	0,5°	4	0,3°	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,050	24.000	200	0,030	0,030
0,3	0,5°	6	0,3°	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,040	24.000	200	0,020	0,020
0,3	0,5°	8	0,3°	25.000	225	0,045	0,120	20.000	150	0,030	0,060	20.000	150	0,030	0,040	20.000	150	0,020	0,020
0,3	0,5°	10	0,3°	25.000	225	0,045	0,120	20.000	150	0,030	0,060	20.000	150	0,030	0,040	20.000	150	0,020	0,020
0,3	0,5°	12	0,3°	25.000	225	0,045	0,120	20.000	150	0,030	0,060	20.000	150	0,030	0,040	20.000	150	0,010	0,010
0,3	0,5°	16	0,3°	20.000	150	0,025	0,050	20.000	150	0,030	0,060	20.000	150	0,010	0,040	20.000	150	0,010	0,010
0,3	1°	4	0,3°	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,050	24.000	200	0,030	0,030
0,3	1°	6	0,3°	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,040	24.000	200	0,020	0,020
0,3	1°	8	0,3°	30.000	375	0,045	0,120	25.000	250	0,030	0,060	24.000	200	0,030	0,040	24.000	200	0,020	0,020
0,3	1°	10	0,3°	25.000	225	0,045	0,120	20.000	150	0,030	0,060	20.000	150	0,030	0,040	20.000	150	0,020	0,020
0,3	1°	12	0,3°	25.000	225	0,045	0,120	20.000	150	0,030	0,060	20.000	150	0,030	0,040	20.000	150	0,020	0,020
0,3	1°	16	0,3°	25.000	225	0,045	0,120	20.000	150	0,030	0,060	20.000	150	0,030	0,040	20.000	150	0,020	0,020
0,4	0,5°	4	0,3°	27.000	675	0,060	0,160	23.000	450	0,040	0,080	21.000	300	0,040	0,060	21.000	300	0,040	0,080
0,4	0,5°	6	0,3°	24.000	375	0,060	0,120	21.000	250	0,040	0,060	19.000	200	0,040	0,050	19.000	200	0,030	0,050
0,4	0,5°	8	0,3°	24.000	375	0,060	0,120	21.000	250	0,040	0,060	19.000	200	0,040	0,050	19.000	200	0,030	0,050
0,4	0,5°	12	0,3°	22.000	225	0,060	0,120	19.000	150	0,040	0,060	17.000	150	0,040	0,050	17.000	150	0,020	0,050
0,4	1°	8	0,3°	24.000	375	0,060	0,120	21.000	250	0,040	0,060	19.000	200	0,040	0,050	19.000	200	0,030	0,050
0,4	1°	12	0,3°	24.000	375	0,060	0,120	21.000	250	0,040	0,060	19.000	200	0,040	0,050	19.000	200	0,020	0,050
0,4	1°	16	0,3°	22.000	225	0,060	0,120	19.000	150	0,040	0,060	17.000	150	0,040	0,050	17.000	150	0,020	0,020
0,5	0,5°	6	0,3°	28.000	750	0,075	0,200	25.000	500	0,050	0,100	21.000	300	0,050	0,080	21.000	300	0,050	0,050
0,5	0,5°	8	0,3°	28.000	750	0,075	0,200	25.000	500	0,050	0,100	21.000	300	0,050	0,080	21.000	300	0,050	0,050
0,5	0,5°	10	0,3°	21.000	450	0,075	0,150	19.000	300	0,050	0,100	16.000	200	0,050	0,080	16.000	200	0,050	0,050
0,5	0,5°	12	0,3°	21.000	450	0,075	0,150	19.000	300	0,050	0,100	16.000	200	0,050	0,080	16.000	200	0,050	0,050
0,5	0,5°	16	0,3°	18.000	300	0,060	0,120	17.000	200	0,030	0,050	14.000	150	0,030	0,040	14.000	150	0,010	0,025
0,5	0,5°	18	0,3°	18.000	300	0,060	0,120	17.000	200	0,030	0,050	14.000	150	0,030	0,040	14.000	150	0,010	0,025
0,5	0,5°	20	0,3°	18.000	300	0,060	0,120	17.000	200	0,030	0,050	14.000	150	0,030	0,040	14.000	150	0,010	0,025
0,5	0,5°	25	0,3°	16.000	300	0,060	0,120	13.000	200	0,030	0,050	10.000	150	0,030	0,040	10.000	150	0,010	0,015
0,5	0,5°	30	0,3°	16.000	300	0,060	0,120	13.000	200	0,030	0,050	10.000	150	0,030	0,040	10.000	150	0,010	0,015
0,5	0,5°	35	0,3°	13.000	300	0,040	0,120	13.000	200	0,010	0,050	10.000	150	0,010	0,040	10.000	150	0,005	0,015
0,5	1°	10	0,3°	28.000	750	0,075	0,200	25.000	500	0,050	0,100	21.000	300	0,050	0,080	21.000	300	0,050	0,050
0,5	1°	16	0,3°	21.000	450	0,075	0,150	19.000	300	0,050	0,100	16.000	200	0,050	0,080	16.000	200	0,050	0,050
0,5	1°	20	0,3°	21.000	450	0,075	0,150	17.000	200	0,030	0,050								

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-PC-EBD

Regular milling

R	θ	l2	Cutting angle	Cu				~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
				S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
0,6	1,5°	12	0,3°	20.000	600	0,090	0,240	17.000	450	0,060	0,120	14.000	300	0,060	0,100	14.000	300	0,060	0,060
0,6	1,5°	25	0,3°	20.000	450	0,090	0,240	17.000	300	0,060	0,120	14.000	200	0,060	0,100	14.000	200	0,060	0,060
0,75	0,5°	8	0,3°	18.000	750	0,140	0,300	15.000	500	0,080	0,150	12.000	350	0,080	0,150	12.000	300	0,080	0,150
0,75	0,5°	10	0,3°	17.000	450	0,140	0,300	15.000	300	0,080	0,150	12.000	250	0,080	0,150	12.000	250	0,080	0,150
0,75	0,5°	12	0,3°	17.000	450	0,120	0,300	15.000	300	0,080	0,150	12.000	250	0,080	0,150	12.000	250	0,080	0,150
0,75	0,5°	16	0,3°	17.000	450	0,120	0,240	15.000	300	0,080	0,120	12.000	250	0,080	0,100	12.000	250	0,075	0,100
0,75	0,5°	20	0,3°	13.000	300	0,120	0,200	12.000	200	0,060	0,100	9.500	150	0,060	0,100	9.500	150	0,050	0,100
0,75	0,5°	25	0,3°	13.000	300	0,120	0,200	12.000	200	0,060	0,100	9.500	150	0,060	0,100	9.500	150	0,050	0,100
0,75	0,5°	30	0,3°	13.000	300	0,120	0,200	12.000	200	0,060	0,100	9.500	150	0,060	0,100	9.500	150	0,035	0,100
0,75	0,5°	35	0,3°	13.000	300	0,090	0,200	12.000	200	0,060	0,100	9.500	150	0,060	0,100	9.500	150	0,030	0,100
0,75	1°	10	0,3°	18.000	750	0,140	0,300	15.000	500	0,080	0,150	12.000	350	0,080	0,150	12.000	300	0,080	0,150
0,75	1°	12	0,3°	17.000	450	0,140	0,300	15.000	300	0,080	0,150	12.000	250	0,080	0,150	12.000	250	0,080	0,150
0,75	1°	16	0,3°	17.000	450	0,120	0,300	15.000	300	0,080	0,150	12.000	250	0,080	0,150	12.000	250	0,080	0,150
0,75	1°	20	0,3°	17.000	450	0,120	0,240	15.000	300	0,080	0,120	12.000	250	0,080	0,100	12.000	250	0,075	0,100
0,75	1°	25	0,3°	17.000	450	0,120	0,240	15.000	300	0,080	0,120	12.000	250	0,080	0,100	12.000	250	0,050	0,100
0,75	1°	30	0,3°	13.000	300	0,090	0,200	12.000	200	0,060	0,100	9.500	150	0,060	0,100	9.500	150	0,030	0,100
0,75	1°	35	0,3°	13.000	300	0,090	0,200	12.000	200	0,060	0,100	9.500	150	0,060	0,100	9.500	150	0,020	0,100
0,75	1,5°	10	0,3°	18.000	750	0,120	0,300	15.000	500	0,080	0,150	12.000	350	0,080	0,150	12.000	300	0,080	0,150
0,75	1,5°	12	0,3°	17.000	450	0,120	0,300	15.000	300	0,080	0,150	12.000	250	0,080	0,150	12.000	250	0,080	0,150
0,75	1,5°	16	0,3°	17.000	450	0,120	0,300	15.000	300	0,080	0,150	12.000	250	0,080	0,150	12.000	250	0,080	0,150
0,75	1,5°	20	0,3°	17.000	450	0,120	0,300	15.000	300	0,080	0,150	12.000	250	0,080	0,150	12.000	250	0,080	0,150
0,75	1,5°	25	0,3°	17.000	450	0,120	0,240	15.000	300	0,080	0,120	12.000	250	0,080	0,100	12.000	250	0,075	0,100
0,75	1,5°	30	0,3°	17.000	450	0,120	0,240	15.000	300	0,080	0,120	12.000	250	0,080	0,100	12.000	250	0,075	0,100
0,75	1,5°	35	0,3°	13.000	300	0,075	0,200	12.000	200	0,060	0,100	9.500	150	0,060	0,100	9.500	150	0,050	0,100
0,75	2°	38,6	0,3°	17.000	450	0,120	0,240	15.000	300	0,080	0,120	12.000	250	0,080	0,100	12.000	250	0,075	0,100
1	0,5°	8	0,3°	16.500	1.050	0,200	0,560	16.500	700	0,100	0,280	13.500	500	0,100	0,280	13.500	500	0,100	0,200
1	0,5°	10	0,3°	16.500	1.050	0,200	0,560	16.500	700	0,100	0,280	13.500	500	0,100	0,280	13.500	500	0,100	0,200
1	0,5°	12	0,3°	16.500	1.050	0,200	0,560	16.500	700	0,100	0,280	13.500	500	0,100	0,280	13.500	500	0,100	0,200
1	0,5°	16	0,3°	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200
1	0,5°	20	0,3°	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200
1	0,5°	25	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100
1	0,5°	30	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100
1	0,5°	35	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100
1	0,5°	40	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100
1	1°	16	0,3°	16.500	1.050	0,200	0,560	16.500	700	0,100	0,280	13.500	500	0,100	0,280	13.500	500	0,100	0,200
1	1°	20	0,3°	14.000	750	0,200	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200
1	1°	25	0,3°	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200
1	1°	30	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,080	0,100
1	1°	35	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,080	0,100
1	1°	40	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100
1	1°	50	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100
1	1°	60	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100
1	1°	70	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100
1	1,5°	16	0,3°	16.500	1.050	0,200	0,560	16.500	700	0,100	0,280	13.500	500	0,100	0,280	13.500	500	0,100	0,200
1	1,5°	20	0,3°	16.500	1.050	0,200	0,560	16.500	700	0,100	0,280	13.500	500	0,100	0,280	13.500	500	0,100	0,200
1	1,5°	25	0,3°	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200
1	1,5°	30	0,3°	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200
1	1,5°	35	0,3°	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200
1	1,5°	41,5	0,3°	11.000	375	0,150	0,420	10.000	250	0,100	0,210	8.000	200	0,100	0,180	8.000	200	0,060	0,100
1	2°	31,5	0,3°	14.000	750	0,150	0,560	13.000	500	0,100	0,280	10.000	300	0,100	0,280	10.000	300	0,100	0,200
1,5	0,5°	8	0,3°	15.000	1.200	0,200	0,840	9.500	800	0,150	0,420	7.500	600	0,150	0,420	7.500	600	0,150	0,300
1,5	0,5°	10	0,3°	15.000	1.200	0,200	0,840	9.500	800	0,150	0,420	7.500	600	0,150	0,420	7.500	600	0,150	0,300
1,5	0,5°	12	0,3°	12.000	900	0,200	0,840	9.500	600	0,150	0,420	7.500	400	0,150	0,360	7.500	400	0,150	0,300
1,5	0,5°	16	0,3°	10.000	900	0,200	0,840	9.500	600	0,150	0,420	7.500	400	0,150	0,360	7.500	400	0,150	0,300
1,5	0,5°	20	0,3°	10.000	450	0,200	0,840	8.500	300	0,150	0,420	6.500	250	0,150	0,360	6.500	250	0,150	0,300
1,5	0,5°	25	0,3°	10.000	450	0,200	0,840	8.500	300	0,150	0,420	6.500	250	0,150	0,360	6.500	250	0,150	0,300
1,5	0,5°	30	0,3°	10.000	450	0,200	0,840	8.500	300	0,150	0,420	6.500	250	0,150	0,300	6.500	250	0,090	0,150
1,5	0,5°	35	0,3°	10.000	450	0,200	0,840	8.500	300	0,150	0,420	6.500	250	0,150	0,300	6.500	250	0,090	0,150
1,5	0,5°	40	0,3°	9.000	375	0,200	0,840	7.500	250	0,150	0,420	6.000	200	0,150	0,300	6.000	200	0,090	0,150
1,5	0,5°	50	0,3°	9.000	375	0,200	0,840	7.500	250	0,150	0,420	6.000	200	0,150	0,300	6.000	200	0,090	0,150
1,5	1°	20	0,3°	10.000	900	0,200	0,840	9.500	600	0,150	0,420	7.500	400	0,150	0,360	7.500	400	0,150	0,300
1,5	1°	25	0,3°	10.000	450	0,200	0,840	8.500	300	0,150	0,420	6.500	250	0,150	0,360	6.			

CUTTING CONDITIONS


Milling | Endmills | Cutting conditions

WXL-PC-EBD

Regular milling

R	θ	l2	Cutting angle	Cu				~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
				S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
2	2°	34	0,5°	7.000	600	0,500	1,280	6.000	400	0,200	0,640	5.000	250	0,200	0,600	5.000	250	0,200	0,500
2,5	1°	30	0,5°	7.000	750	0,600	1,800	6.500	500	0,250	0,900	5.000	400	0,250	0,700	5.000	400	0,250	0,500
2,5	1°	40	0,5°	6.000	750	0,600	1,800	5.000	500	0,250	0,900	4.000	250	0,250	0,700	4.000	250	0,250	0,500
2,5	1°	60	0,5°	5.000	600	0,400	1,800	4.000	400	0,250	0,900	4.000	200	0,250	0,600	4.000	200	0,200	0,250
2,5	1,5°	26,9	0,5°	9.000	1.350	0,600	1,800	6.500	900	0,250	0,900	5.000	750	0,250	0,700	5.000	750	0,250	0,500
2,5	1,5°	65,1	0,5°	6.000	750	0,600	1,800	5.000	500	0,250	0,900	4.000	250	0,250	0,700	4.000	250	0,250	0,500
2,5	2°	50,1	0,5°	6.000	750	0,600	1,800	5.000	500	0,250	0,900	4.000	250	0,250	0,700	4.000	250	0,250	0,500
3	1°	30	0,5°	7.000	1.200	0,750	2,400	5.500	800	0,300	1,200	4.500	600	0,300	0,960	4.500	600	0,300	0,600
3	1°	40	0,5°	5.000	600	0,750	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,600
3	1°	50	0,5°	5.000	600	0,600	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,600
3	1°	60	0,5°	5.000	600	0,600	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,600
3	1°	70	0,5°	5.000	600	0,600	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,300
3	1°	80	0,5°	5.000	600	0,450	2,400	4.000	400	0,200	1,200	4.000	300	0,200	0,960	4.000	300	0,200	0,300
3	1,5°	49	0,5°	5.000	600	0,600	2,400	4.000	400	0,300	1,200	4.000	300	0,300	0,960	4.000	300	0,300	0,600
3	2°	36	0,5°	7.000	1.200	0,750	2,400	5.500	800	0,300	1,200	4.500	600	0,300	0,960	4.500	600	0,300	0,600

Max cutting depth



- Highly rigid machines and tool holders should be used. If not, machining should be kept below above-mentioned conditions
- Tool vibrations should be kept at a minimum level for maximum accuracy.
- Use a suitable cutting fluid with high smoke retardant properties.
- For the milling of corners or removal of residue, reduce the cutting depth and feed to 70%..
- More stable high-feed machining in corners can be attained by setting an R insertion or deceleration on the CAM or machine side.
- When cutting load fluctuates (in the corners, etc.) or when high precision is required, be sure to control the rotational speed.
- When cutting at greater than the recommended cutting angle, reduce the feed.
- When cutting load is fluctuating, or when higher milling accuracy is required, keep machining conditions below the above-mentioned values.
- When the rotational speed does not meet the recommended conditions, reduce the feed in proportion to the RPM that is suitable for your machine.
- The chart above is intended as general guidelines for reference only. The given values should be adjusted individually based on actual machining conditions.
- The cutting conditions are intended for intermediate machining after roughing.
- When the work includes extensive roughing including flat areas, chattering is more likely to occur.
- If the cutting depth is shallow, increase the cutting speed appropriately to minimize chattering.

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-PC-EBD

High speed milling




R	θ	l2	Cutting angle	Cu				~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
				S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
0.1	0.5°	1	0.3°	50.000	440	0,007	0,010	50.000	360	0,005	0,005	50.000	340	0,005	0,005	50.000	340	0,005	0,005
0.1	0.5°	1.5	0.3°	50.000	440	0,007	0,010	50.000	360	0,005	0,005	50.000	340	0,005	0,005	50.000	340	0,005	0,005
0.1	0.5°	2	0.3°	50.000	360	0,007	0,010	45.000	300	0,005	0,005	45.000	280	0,005	0,005	45.000	280	0,005	0,005
0.1	0.5°	2.5	0.3°	50.000	320	0,007	0,010	38.000	230	0,005	0,005	38.000	210	0,005	0,005	37.000	200	0,005	0,005
0.1	0.5°	3	0.3°	50.000	250	0,007	0,010	38.000	200	0,005	0,005	38.000	180	0,005	0,005	37.000	150	0,003	0,005
0.1	1°	3.5	0.3°	50.000	440	0,007	0,010	50.000	360	0,005	0,005	50.000	340	0,005	0,005	50.000	340	0,005	0,005
0.1	1°	4	0.3°	50.000	360	0,007	0,010	45.000	300	0,005	0,005	45.000	280	0,005	0,005	45.000	280	0,005	0,005
0.1	1°	4.5	0.3°	50.000	320	0,007	0,010	38.000	230	0,005	0,005	38.000	210	0,005	0,005	37.000	200	0,005	0,005
1.5	0.5°	2	0.3°	50.000	730	0,007	0,020	50.000	600	0,005	0,010	50.000	570	0,005	0,010	50.000	570	0,005	0,005
1.5	0.5°	3	0.3°	50.000	580	0,007	0,010	45.000	480	0,005	0,005	45.000	450	0,005	0,005	45.000	450	0,005	0,005
1.5	1°	3	0.3°	50.000	610	0,007	0,020	47.000	510	0,005	0,010	47.000	480	0,005	0,010	47.000	480	0,005	0,005
1.5	1°	4	0.3°	50.000	580	0,007	0,010	45.000	480	0,005	0,005	45.000	450	0,005	0,005	45.000	450	0,005	0,005
0.2	0.5°	2	0.3°	50.000	970	0,015	0,040	50.000	800	0,010	0,020	50.000	760	0,010	0,020	50.000	760	0,010	0,010
0.2	0.5°	3	0.3°	50.000	670	0,012	0,030	45.000	550	0,008	0,015	45.000	520	0,008	0,015	45.000	520	0,008	0,010
0.2	0.5°	4	0.3°	48.000	540	0,007	0,020	43.000	500	0,005	0,010	43.000	470	0,005	0,010	43.000	470	0,005	0,010
0.2	0.5°	5	0.3°	45.000	480	0,007	0,020	40.000	420	0,005	0,010	40.000	400	0,005	0,010	40.000	400	0,005	0,010
0.2	0.5°	6	0.3°	40.000	400	0,007	0,010	36.000	370	0,005	0,005	36.000	350	0,005	0,005	35.000	340	0,005	0,005
0.2	1°	4	0.3°	50.000	670	0,012	0,030	45.000	550	0,008	0,015	45.000	520	0,008	0,015	45.000	520	0,008	0,010
0.2	1°	5	0.3°	48.000	540	0,007	0,020	43.000	500	0,005	0,010	43.000	470	0,005	0,010	43.000	470	0,005	0,010
0.2	1°	6	0.3°	45.000	480	0,007	0,020	40.000	420	0,005	0,010	40.000	400	0,005	0,010	40.000	400	0,005	0,010
0.25	0.5°	4	0.3°	50.000	1.200	0,015	0,040	48.000	900	0,010	0,020	48.000	850	0,010	0,020	48.000	850	0,010	0,015
0.25	0.5°	6	0.3°	38.000	940	0,015	0,020	38.000	500	0,010	0,010	38.000	470	0,010	0,010	38.000	470	0,010	0,010
0.25	0.5°	8	0.3°	30.000	760	0,007	0,020	30.000	400	0,005	0,010	30.000	380	0,005	0,010	29.000	360	0,005	0,010
0.25	0.5°	10	0.3°	30.000	500	0,005	0,020	30.000	400	0,005	0,010	30.000	300	0,005	0,010	29.000	250	0,005	0,010
0.25	1°	4	0.3°	50.000	1.200	0,015	0,040	48.000	900	0,010	0,020	48.000	850	0,010	0,020	48.000	850	0,010	0,010
0.25	1°	6	0.3°	50.000	1.200	0,015	0,040	48.000	900	0,010	0,020	48.000	850	0,010	0,020	48.000	850	0,010	0,010
0.25	1°	8	0.3°	50.000	1.200	0,015	0,040	48.000	900	0,010	0,020	48.000	850	0,010	0,020	48.000	850	0,010	0,010
0.25	1°	10	0.3°	30.000	760	0,007	0,020	30.000	400	0,005	0,010	30.000	380	0,005	0,010	29.000	360	0,005	0,010
0.25	1°	12	0.3°	30.000	760	0,007	0,020	30.000	400	0,005	0,010	30.000	380	0,005	0,010	29.000	360	0,005	0,010
0.3	0.5°	2	0.3°	50.000	1.550	0,030	0,060	50.000	1.200	0,020	0,030	50.000	1.100	0,020	0,030	50.000	1.100	0,020	0,030
0.3	0.5°	4	0.3°	50.000	1.350	0,030	0,060	45.000	1.000	0,020	0,030	45.000	950	0,020	0,030	45.000	950	0,020	0,030
0.3	0.5°	6	0.3°	35.000	960	0,015	0,040	30.000	680	0,010	0,020	30.000	640	0,010	0,020	30.000	640	0,010	0,020
0.3	0.5°	8	0.3°	30.000	720	0,015	0,040	26.000	600	0,010	0,020	26.000	570	0,010	0,020	25.000	540	0,010	0,020
0.3	0.5°	10	0.3°	30.000	500	0,015	0,040	26.000	480	0,010	0,020	26.000	450	0,010	0,020	25.000	380	0,010	0,020
0.3	0.5°	12	0.3°	30.000	500	0,010	0,040	26.000	480	0,007	0,020	26.000	450	0,007	0,020	25.000	380	0,007	0,010
0.3	0.5°	16	0.3°	30.000	400	0,007	0,040	26.000	380	0,005	0,020	26.000	360	0,005	0,020	25.000	300	0,005	0,010
0.3	1°	4	0.3°	50.000	1.350	0,030	0,060	45.000	1.000	0,020	0,030	45.000	950	0,020	0,030	45.000	950	0,020	0,030
0.3	1°	6	0.3°	35.000	960	0,015	0,040	30.000	680	0,010	0,020	30.000	640	0,010	0,020	30.000	640	0,010	0,020
0.3	1°	8	0.3°	35.000	960	0,015	0,040	30.000	680	0,010	0,020	30.000	640	0,010	0,020	30.000	640	0,010	0,020
0.3	1°	10	0.3°	30.000	720	0,015	0,040	26.000	600	0,010	0,020	26.000	570	0,010	0,020	25.000	540	0,010	0,020
0.3	1°	12	0.3°	30.000	720	0,015	0,040	26.000	600	0,010	0,020	26.000	570	0,010	0,020	25.000	540	0,010	0,020
0.3	1°	16	0.3°	30.000	500	0,015	0,040	26.000	480	0,010	0,020	26.000	450	0,010	0,020	25.000	380	0,010	0,020
0.4	0.5°	4	0.3°	50.000	1.750	0,060	0,160	48.000	1.600	0,040	0,080	48.000	1.500	0,040	0,060	48.000	1.500	0,040	0,040
0.4	0.5°	6	0.3°	43.000	1.600	0,045	0,100	34.000	950	0,030	0,050	34.000	900	0,030	0,050	34.000	900	0,020	0,025
0.4	0.5°	8	0.3°	32.000	1.250	0,045	0,100	30.000	800	0,030	0,050	30.000	760	0,030	0,050	30.000	760	0,020	0,025
0.4	0.5°	12	0.3°	24.000	720	0,010	0,040	23.000	450	0,005	0,010	23.000	420	0,005	0,010	23.000	420	0,005	0,025
0.4	1°	8	0.3°	43.000	1.600	0,045	0,100	34.000	950	0,030	0,050	34.000	900	0,030	0,050	34.000	900	0,020	0,025
0.4	1°	12	0.3°	32.000	1.250	0,045	0,100	30.000	800	0,030	0,050	30.000	760	0,030	0,050	30.000	760	0,020	0,025
0.4	1°	16	0.3°	24.000	720	0,010	0,040	23.000	450	0,005	0,010	23.000	420	0,005	0,010	23.000	420	0,005	0,015
0.5	0.5°	6	0.3°	47.000	2.850	0,075	0,200	36.000	2.300	0,050	0,100	36.000	2.100	0,050	0,080	36.000	2.100	0,050	0,050
0.5	0.5°	8	0.3°	30.000	2.350	0,075	0,150	27.000	1.700	0,050	0,100	27.000	1.600	0,050	0,080	27.000	1.600	0,050	0,050
0.5	0.5°	10	0.3°	27.000	2.000	0,075	0,150	26.000	1.600	0,050	0,100	26.000	1.500	0,050	0,080	26.000	1.500	0,050	0,050
0.5	0.5°	12	0.3°	24.000	1.400	0,015	0,040	22.000	1.100	0,010	0,020	22.000	1.000	0,010	0,050	21.000	950	0,010	0,020
0.5	0.5°	16	0.3°	24.000	1.000	0,015	0,040	22.000	770	0,010	0,020	22.000	700	0,010	0,020	21.000	680	0,010	0,020
0.5	0.5°	18	0.3°	24.000	1.000	0,010	0,040	22.000	770	0,007	0,020	22.000	700	0,007	0,020	21.000	680	0,007	0,020
0.5	0.5°	20	0.3°	24.000	1.000	0,010	0,030	22.000	770	0,007	0,015	22.000	700	0,007	0,015	21.000	680	0,007	0,015
0.5	0.5°	25	0.3°	20.000	800	0,010	0,030	18.000	600	0,007	0,015	18.000	480	0,007	0,015	17.000	550	0,007	0,015
0.5	0.5°	30	0.3°	20.000	800	0,007	0,030	18.000	600	0,005	0,015	18.000	480	0,005	0,015	17.000	550	0,005	0,015
0.5	0.5°	35	0.3°	15.000	550	0,005	0,030	14.000	450	0,005	0,010	12.000	400	0,005	0,010	11.000	350	0,005	0,010
0.5	1°	10	0.3°	30.000	2.350	0,075	0,150	27.000	1.700	0,050	0,100	27.000	1.600	0,050	0,050	27.000	1.600	0,050	0,050
0.5	1°	16	0.3°	24.000	1.400	0,015	0,040	22.000	1.100	0,010	0,020	22.000	1.000	0,010	0,020	21.0			

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-PC-EBD

High speed milling

				Cu				~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
				S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
R	θ	l2	Cutting angle																
0,6	1,5°	12	0,3°	30.000	2.200	0,090	0,210	25.000	2.000	0,060	0,120	25.000	2.000	0,060	0,100	25.000	1.900	0,060	0,060
0,6	1,5°	25	0,3°	30.000	2.000	0,050	0,210	25.000	1.700	0,060	0,120	25.000	1.600	0,06	0,100	25.000	1.600	0,050	0,060
0,75	0,5°	8	0,3°	32.000	3.000	0,120	0,300	30.000	2.900	0,075	0,150	30.000	2.700	0,075	0,120	30.000	2.700	0,075	0,100
0,75	0,5°	10	0,3°	30.000	2.650	0,120	0,300	24.000	2.300	0,075	0,150	24.000	2.100	0,075	0,120	24.000	2.100	0,075	0,100
0,75	0,5°	12	0,3°	30.000	2.400	0,120	0,300	24.000	2.000	0,075	0,150	24.000	1.900	0,075	0,120	24.000	1.900	0,075	0,100
0,75	0,5°	16	0,3°	24.000	1.400	0,120	0,200	21.000	1.400	0,075	0,100	21.000	1.300	0,075	0,090	21.000	1.300	0,050	0,060
0,75	0,5°	20	0,3°	22.000	1.400	0,100	0,200	18.000	1.200	0,050	0,100	18.000	1.100	0,050	0,070	17.000	1.100	0,030	0,030
0,75	0,5°	25	0,3°	22.000	1.100	0,100	0,200	18.000	1.000	0,050	0,100	18.000	900	0,050	0,070	17.000	900	0,020	0,030
0,75	0,5°	30	0,3°	22.000	1.100	0,075	0,200	18.000	1.000	0,035	0,100	18.000	900	0,035	0,070	17.000	900	0,010	0,030
0,75	0,5°	35	0,3°	20.000	1.000	0,050	0,200	17.000	9.000	0,030	0,100	17.000	800	0,030	0,070	15.000	800	0,010	0,030
0,75	1°	10	0,3°	32.000	3.000	0,120	0,300	30.000	2.900	0,075	0,150	30.000	2.700	0,075	0,120	30.000	2.700	0,075	0,100
0,75	1°	12	0,3°	30.000	2.650	0,120	0,300	24.000	2.300	0,075	0,150	24.000	2.100	0,075	0,120	24.000	2.100	0,075	0,100
0,75	1°	16	0,3°	30.000	2.400	0,120	0,300	24.000	2.000	0,075	0,150	24.000	1.900	0,075	0,120	24.000	1.900	0,075	0,100
0,75	1°	20	0,3°	24.000	1.400	0,120	0,200	21.000	1.400	0,075	0,100	21.000	1.300	0,075	0,090	21.000	1.300	0,050	0,060
0,75	1°	25	0,3°	22.000	1.400	0,100	0,200	18.000	1.200	0,050	0,100	18.000	1.100	0,050	0,090	17.000	1.100	0,050	0,060
0,75	1°	30	0,3°	22.000	1.400	0,070	0,200	18.000	1.200	0,050	0,100	18.000	1.100	0,050	0,070	17.000	1.100	0,030	0,030
0,75	1°	35	0,3°	22.000	1.100	0,070	0,200	18.000	1.000	0,050	0,100	18.000	900	0,050	0,070	17.000	900	0,020	0,030
0,75	1,5°	10	0,3°	32.000	3.000	0,120	0,300	30.000	2.900	0,075	0,150	30.000	2.700	0,075	0,120	30.000	2.700	0,075	0,100
0,75	1,5°	12	0,3°	32.000	3.000	0,120	0,300	30.000	2.900	0,075	0,150	30.000	2.700	0,075	0,120	30.000	2.700	0,075	0,100
0,75	1,5°	16	0,3°	30.000	2.400	0,120	0,300	24.000	2.000	0,075	0,150	24.000	1.900	0,075	0,120	24.000	1.900	0,075	0,100
0,75	1,5°	20	0,3°	30.000	2.400	0,120	0,300	24.000	2.000	0,075	0,150	24.000	1.900	0,075	0,120	24.000	1.900	0,080	0,100
0,75	1,5°	25	0,3°	24.000	1.400	0,100	0,200	21.000	1.400	0,075	0,100	21.000	1.300	0,075	0,090	21.000	1.300	0,050	0,060
0,75	1,5°	30	0,3°	24.000	1.400	0,100	0,200	21.000	1.400	0,075	0,100	21.000	1.300	0,075	0,090	21.000	1.300	0,050	0,060
0,75	1,5°	35	0,3°	22.000	1.400	0,050	0,200	18.000	1.200	0,050	0,100	18.000	1.100	0,050	0,070	17.000	1.100	0,020	0,030
0,75	2°	38,6	0,3°	24.000	1.400	0,100	0,200	21.000	1.400	0,075	0,100	21.000	1.300	0,075	0,090	21.000	1.300	0,050	0,060
1	0,5°	8	0,3°	27.000	3.350	0,150	0,400	25.000	2.600	0,100	0,200	25.000	2.400	0,100	0,200	23.000	2.200	0,100	0,200
1	0,5°	10	0,3°	22.000	3.050	0,150	0,400	20.000	2.400	0,100	0,200	20.000	2.200	0,100	0,200	19.000	2.000	0,100	0,200
1	0,5°	12	0,3°	22.000	3.050	0,150	0,400	20.000	2.400	0,100	0,200	20.000	2.200	0,100	0,200	19.000	2.000	0,100	0,200
1	0,5°	16	0,3°	15.000	2.400	0,150	0,300	15.000	1.800	0,100	0,200	15.000	1.700	0,100	0,200	14.000	1.500	0,100	0,200
1	0,5°	20	0,3°	15.000	2.200	0,150	0,200	14.000	1.700	0,100	0,100	14.000	1.600	0,100	0,100	13.000	1.400	0,100	0,100
1	0,5°	25	0,3°	12.000	1.200	0,100	0,200	12.000	1.200	0,050	0,100	11.000	1.100	0,050	0,100	10.000	1.000	0,050	0,100
1	0,5°	30	0,3°	12.000	1.000	0,100	0,200	12.000	1.000	0,050	0,100	11.000	900	0,050	0,100	10.000	800	0,050	0,100
1	0,5°	35	0,3°	12.000	1.000	0,075	0,200	12.000	1.000	0,030	0,100	11.000	900	0,030	0,100	10.000	800	0,030	0,100
1	0,5°	40	0,3°	12.000	800	0,050	0,200	12.000	800	0,020	0,100	11.000	800	0,020	0,100	10.000	700	0,020	0,100
1	1°	16	0,3°	22.000	3.050	0,150	0,400	20.000	2.400	0,100	0,200	20.000	2.200	0,100	0,200	19.000	2.000	0,100	0,200
1	1°	20	0,3°	15.000	2.400	0,150	0,300	15.000	1.800	0,100	0,200	15.000	1.700	0,100	0,200	14.000	1.500	0,100	0,200
1	1°	25	0,3°	15.000	2.200	0,150	0,200	14.000	1.700	0,100	0,100	14.000	1.600	0,100	0,100	13.000	1.400	0,100	0,100
1	1°	30	0,3°	14.000	2.200	0,150	0,200	14.000	1.700	0,100	0,100	14.000	1.600	0,100	0,100	13.000	1.400	0,070	0,100
1	1°	35	0,3°	12.000	1.200	0,100	0,200	12.000	1.200	0,050	0,100	11.000	1.100	0,050	0,100	10.000	1.000	0,050	0,100
1	1°	40	0,3°	12.000	1.000	0,100	0,200	12.000	1.000	0,050	0,100	11.000	900	0,050	0,100	10.000	800	0,050	0,100
1	1°	50	0,3°	12.000	1.000	0,075	0,200	12.000	1.000	0,030	0,100	11.000	900	0,030	0,100	10.000	800	0,030	0,100
1	1°	60	0,3°	12.000	800	0,050	0,200	12.000	800	0,020	0,100	11.000	800	0,020	0,100	10.000	700	0,020	0,100
1	1°	70	0,3°	12.000	800	0,030	0,100	12.000	800	0,010	0,050	11.000	800	0,010	0,050	10.000	700	0,010	0,050
1	1,5°	16	0,3°	22.000	3.050	0,200	0,400	20.000	2.400	0,100	0,200	20.000	2.200	0,100	0,200	19.000	2.000	0,100	0,200
1	1,5°	20	0,3°	22.000	3.050	0,200	0,400	20.000	2.400	0,100	0,200	20.000	2.200	0,100	0,200	19.000	2.000	0,100	0,200
1	1,5°	25	0,3°	15.000	2.400	0,150	0,300	15.000	1.800	0,100	0,200	15.000	1.700	0,100	0,200	14.000	1.500	0,100	0,200
1	1,5°	30	0,3°	15.000	2.200	0,150	0,200	14.000	1.700	0,100	0,100	14.000	1.600	0,100	0,100	13.000	1.400	0,100	0,100
1	1,5°	35	0,3°	15.000	2.200	0,150	0,200	14.000	1.700	0,100	0,100	14.000	1.600	0,100	0,100	13.000	1.400	0,100	0,100
1	1,5°	41,5	0,3°	12.000	1.200	0,100	0,200	12.000	1.200	0,050	0,100	11.000	1.100	0,050	0,100	10.000	1.000	0,050	0,100
1	2°	31,5	0,3°	15.000	2.400	0,150	0,300	15.000	1.800	0,100	0,200	15.000	1.700	0,100	0,200	14.000	1.500	0,100	0,200
1,5	0,5°	8	0,3°	32.000	4.600	0,200	0,600	30.000	4.500	0,150	0,300	30.000	4.200	0,150	0,300	25.000	3.500	0,150	0,300
1,5	0,5°	10	0,3°	28.000	4.000	0,200	0,600	25.000	3.800	0,150	0,300	25.000	3.600	0,150	0,300	20.000	2.800	0,150	0,300
1,5	0,5°	12	0,3°	28.000	4.000	0,200	0,600	25.000	3.800	0,150	0,300	25.000	3.600	0,150	0,300	20.000	2.800	0,150	0,300
1,5	0,5°	16	0,3°	22.000	2.900	0,200	0,600	18.000	2.700	0,150	0,300	18.000	2.500	0,150	0,300	15.000	2.000	0,150	0,300
1,5	0,5°	20	0,3°	20.000	2.600	0,150	0,400	16.000	2.000	0,100	0,200	16.000	1.900	0,100	0,200	13.000	1.500	0,100	0,200
1,5	0,5°	25	0,3°	16.000	2.200	0,150	0,400	14.000	1.800	0,100	0,200	14.000	1.700	0,100	0,200	11.000	1.300	0,100	0,200
1,5	0,5°	30	0,3°	16.000	1.800	0,125	0,200	12.000	1.200	0,050	0,100	12.000	1.100	0,050	0,100	9.000	820	0,050	0,100
1,5	0,5°	35	0,3°	12.000	1.000	0,075	0,100	10.000	800	0,030	0,050	9.000	760	0,030	0,050	7.800	590	0,030	0,050
1,5	0,5°	40	0,3°	12.000	800	0,075	0,100	10.000	600	0,030	0,050	9.000	600	0,030	0,050	7.800	480	0,030	0,050
1,5	0,5°	50	0,3°	10.000															

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXL-PC-EBD

High speed milling

R	θ	l2	Cutting angle	Cu				~32 HRC				33~41 HRC Hardened steel, pre-hardened steel				42~50 HRC Hardened steel, pre-hardened steel			
				S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
2	1,5°	44,2	0,5°	18.000	3.000	0,250	0,600	16.000	2.800	0,100	0,300	16.000	2.600	0,100	0,300	12.000	1.900	0,100	0,300
2	2°	34	0,5°	20.000	3.450	0,400	0,600	18.000	3.200	0,200	0,500	18.000	3.000	0,200	0,500	14.000	2.300	0,200	0,500
2,5	1°	30	0,5°	20.000	3.400	0,400	0,750	15.000	3.200	0,200	0,300	15.000	3.000	0,200	0,300	12.000	2.400	0,200	0,300
2,5	1°	40	0,5°	16.000	2.900	0,250	0,750	14.000	2.500	0,100	0,300	14.000	2.300	0,100	0,300	11.000	1.800	0,100	0,300
2,5	1°	60	0,5°	12.000	1.800	0,250	0,500	10.000	1.200	0,100	0,200	10.000	1.100	0,100	0,200	8.000	880	0,100	0,200
2,5	1,5°	26,9	0,5°	18.000	3.800	0,500	1,250	16.000	3.500	0,250	0,500	16.000	3.300	0,250	0,500	12.000	2.400	0,250	0,500
2,5	1,5°	65,1	0,5°	14.000	2.200	0,250	0,750	12.000	1.600	0,100	0,300	12.000	1.500	0,100	0,300	9.000	1.100	0,100	0,300
2,5	2°	50,1	0,5°	16.000	2.900	0,250	0,750	14.000	2.500	0,100	0,300	14.000	2.300	0,100	0,300	11.000	1.800	0,100	0,300
3	1°	30	0,5°	14.000	4.000	0,600	1,250	12.000	3.200	0,300	0,500	12.000	3.000	0,300	0,500	9.000	2.250	0,300	0,500
3	1°	40	0,5°	10.000	3.200	0,600	1,250	10.000	2.600	0,300	0,500	10.000	2.400	0,300	0,500	8.000	1.900	0,300	0,500
3	1°	50	0,5°	9.000	3.000	0,400	1,000	9.000	2.300	0,200	0,400	9.000	2.100	0,200	0,400	7.000	1.600	0,200	0,400
3	1°	60	0,5°	9.000	2.800	0,400	0,750	9.000	2.000	0,200	0,300	9.000	1.900	0,200	0,300	7.000	1.400	0,200	0,300
3	1°	70	0,5°	7.000	2.300	0,400	0,750	7.000	1.600	0,200	0,300	7.000	1.500	0,200	0,300	5.500	1.100	0,200	0,300
3	1°	80	0,5°	6.000	2.000	0,300	0,750	6.000	1.300	0,150	0,300	6.000	1.200	0,150	0,300	5.000	900	0,150	0,300
3	1,5°	49	0,5°	10.000	3.200	0,600	1,250	10.000	2.600	0,300	0,500	10.000	2.400	0,300	0,500	8.000	1.900	0,300	0,500
3	2°	36	0,5°	14.000	4.000	0,600	1,250	12.000	3.200	0,300	0,500	12.000	3.000	0,300	0,500	9.000	2.250	0,300	0,500

Max cutting depth

1. Highly rigid machines and tool holders should be used. If not, machining should be kept below above-mentioned conditions
2. Tool vibrations should be kept at a minimum level for maximum accuracy.
3. Use a suitable cutting fluid with high smoke retardant properties.
4. For the milling of corners or removal of residue, reduce the cutting depth and feed to 70%.
5. More stable high-feed machining in corners can be attained by setting an R insertion or deceleration on the CAM or machine side.
6. When cutting load fluctuates (in the corners, etc.) or when high precision is required, be sure to control the rotational speed.
7. When cutting at greater than the recommended cutting angle, reduce the feed.
8. When cutting load is fluctuating, or when higher milling accuracy is required, keep machining conditions below the above-mentioned values.
9. When the rotational speed does not meet the recommended conditions, reduce the feed in proportion to the RPM that is suitable for your machine.
10. The chart above is intended as general guidelines for reference only. The given values should be adjusted individually based on actual machining conditions.
11. The cutting conditions are intended for intermediate machining after roughing.
12. When the work includes extensive roughing including flat areas, chattering is more likely to occur.
13. If the cutting depth is shallow, increase the cutting speed appropriately to minimize chattering.

WXS-CRE / WXS-HS-CRE

Regular milling

Ø	GG		30~38 HRC NAK55 · HPM1 · SKT · SKD		38~45 HRC SUS304 · SKD · HPM50 NAK80		45~55 HRC		55~60 HRC		60~ HRC	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
2 x R0,5	16.000	5.250	12.500	3.800	11.000	3.350	7.950	2.150	4.750	860	4.270	615
3 x R0,75	10.500	6.250	8.500	4.500	7.450	3.900	5.300	2.600	3.200	995	2.850	715
4 x R1	7.950	6.600	6.350	4.800	5.550	4.200	4.000	2.750	2.400	1.050	2.150	755
6 x R1,5	5.300	7.000	4.250	5.100	3.700	4.450	2.650	2.850	1.600	1.150	1.400	825
8 x R2	4.000	7.000	3.200	5.100	2.800	4.450	2.000	2.850	1.200	1.150	1.050	825
10 x R2	3.200	7.000	2.550	5.100	2.250	4.450	1.600	2.850	955	1.150	860	825
12 x R2	2.650	7.000	2.100	5.100	1.850	4.450	1.350	2.850	795	1.150	715	825

High speed side milling

Ø	GG		30~38 HRC NAK55 · HPM1 · SKT · SKD		38~45 HRC SUS304 · SKD · HPM50 NAK80		45~55 HRC		55~60 HRC		60~ HRC	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
2 x R0,5	31.850	10.500	32.000	9.550	24.000	7.150	24.000	6.450	16.000	2.850	14.400	2.050
3 x R0,75	21.000	12.500	21.000	12.000	16.000	8.400	16.000	7.850	10.500	3.300	9.450	2.370
4 x R1	16.000	13.000	16.000	12.000	12.000	9.000	12.000	8.200	7.950	3.550	7.150	2.550
6 x R1,5	10.600	14.000	10.600	12.700	7.950	9.550	7.950	8.600	5.300	3.800	5.300	3.800
8 x R2	7.950	14.000	7.950	12.700	5.950	9.550	5.950	8.600	4.000	3.800	4.000	3.800
10 x R2	6.350	14.000	6.350	12.700	4.750	9.550	4.750	8.600	3.200	3.800	3.200	3.800
12 x R2	5.300	14.000	5.300	12.700	4.000	9.550	4.000	8.600	2.650	3.800	2.650	3.800

Max cutting depth

ap	ae
0,1xR	0,3D

ap	ae
R<2	0,1xR
2<R	0,2mm

ap	ae
R<2	0,05xR
2<R	0,1mm

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-EMS

Side milling

Ø	~ 40 HRC NAK55 • HPM1 • SKT		40 ~ 45 HRC NAK80 • SKD11 • SKD61		45~55 HRC		55~60 HRC		60~65 HRC		65~70 HRC	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
1	20.000	800	20.000	800	20.000	800	20.000	560	20.000	480	16.000	335
2	20.000	1.600	20.000	1.600	16.000	1.250	12.000	670	11.000	535	7.950	335
3	15.000	1.800	13.500	1.600	10.500	1.250	7.950	670	7.450	535	5.300	335
4	11.000	1.800	9.950	1.600	7.950	1.250	5.950	670	5.550	535	4.000	335
5	8.900	1.800	7.950	1.600	6.350	1.250	4.800	670	4.450	535	3.200	335
6	7.450	2.650	6.650	2.400	5.300	1.900	4.000	1.000	3.700	800	2.650	505
8	5.550	2.650	4.950	2.400	4.000	1.900	3.000	1.000	2.800	800	2.000	505
10	4.450	2.650	4.000	2.400	3.200	1.900	2.400	1.000	2.250	800	1.600	505
12	3.700	2.650	3.300	2.400	2.650	1.900	2.000	1.000	1.850	800	1.350	505
14	3.100	2.500	2.800	2.250	2.250	1.800	1.700	1.000	1.550	800	1.100	505
15	2.850	2.400	2.600	2.200	2.100	1.750	1.550	950	1.450	800	1.050	505
16	2.700	2.400	2.400	2.100	1.950	1.700	1.450	930	1.350	800	995	505
18	2.400	2.250	2.200	2.000	1.750	1.600	1.300	895	1.200	800	885	505
20	2.200	2.150	1.950	1.900	1.550	1.500	1.150	845	1.100	695	800	505
25	1.700	2.450	1.550	2.100	1.250	1.500	955	915	890	750	635	505
30	1.400	2.300	1.300	1.750	1.050	1.250	795	760	740	620	620	430

Max cutting depth		D	ap	ae
		< 1,5	1,5D	0,02D
		1,5-2,5	1,5D	0,05D
		> 2,5	1,5D	0,10D
		ae max = 1mm		

ap	ae
1,5D	0,05D
ae max = 1mm	

ap	ae
1,5D	0,03D
ae max = 0,5mm	

ap	ae
1D	0,02D
ae max = 0,5mm	

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant properties.

WXS-EMS

High speed side milling

Ø	~ 40 HRC NAK55 • HPM1 • SKT		40 ~ 45 HRC NAK80 • SKD11 • SKD61		45~55 HRC		55~60 HRC		60~65 HRC		65~70 HRC	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
1	50.000	1.600	50.000	2.000	50.000	2.000	50.000	1.600	47.500	1.350	32.000	715
2	47.500	3.250	47.500	3.800	40.000	3.200	25.500	1.650	24.000	1.350	16.000	800
3	32.000	3.450	32.000	3.800	26.500	3.200	17.000	1.650	16.000	1.350	10.500	800
4	24.000	3.900	24.000	3.800	20.000	3.200	12.500	1.650	12.000	1.350	7.950	800
5	19.000	4.100	19.000	3.800	16.000	3.200	10.000	1.650	9.550	1.350	6.350	800
6	16.000	5.750	16.000	5.750	13.500	4.800	8.500	2.450	7.950	2.000	5.300	1.200
8	12.000	5.750	12.000	5.750	9.950	4.800	6.350	2.450	5.950	2.000	4.000	1.200
10	9.550	5.750	9.550	5.750	7.950	4.800	5.100	2.450	4.800	2.000	3.200	1.200
12	7.950	5.750	7.950	5.750	6.650	4.800	4.250	2.450	4.000	2.000	2.650	1.200
14	6.800	5.400	6.800	5.400	5.650	4.500	3.600	2.400	3.400	2.000	2.250	1.200
15	6.350	5.300	6.350	5.300	5.250	4.350	3.350	2.300	3.150	1.950	2.100	1.200
16	5.950	5.150	5.950	5.150	4.950	4.250	3.150	2.250	2.950	1.850	1.950	1.200
18	5.300	4.850	5.300	4.850	4.400	4.050	2.800	2.200	2.650	1.750	1.750	1.200
20	4.750	4.600	4.750	4.600	3.950	3.650	2.500	2.050	2.350	1.550	1.550	1.100
25	3.800	5.350	3.800	5.050	3.150	3.800	2.000	2.000	1.900	1.250	1.250	1.050
30	3.150	4.950	3.150	4.250	2.650	3.150	1.650	1.800	1.550	1.050	1.050	1.000

Max cutting depth		ap	ae
		1D	0,05D
		ae max = 0,5mm	

ap	ae
1D	0,03D
ae max = 0,5mm	

ap	ae
1D	0,02D
ae max = 0,2mm	

ap	ae
1D	0,01D
ae max = 0,2mm	

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant properties.

Milling | Endmills

Cutting conditions

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-HS-EBD

High speed light milling

Ø	Tool Steel • Hardened Steel • Prehardened Steel ~45 HRC SKD • NAK80 • HPM50		Hardened Steel 45~55 HRC		Hardened Steel 55~60 HRC		Hardened Steel 60~65 HRC		Hardened Steel 65~70 HRC	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
R 0,5x1	50.000	3.700	50.000	3.700	50.000	3.100	50.000	2.600	47.500	2.400
R1x2	50.000	5.600	47.500	5.350	40.000	3.650	32.000	2.800	24.000	2.100
R1,5x3	41.500	6.200	32.000	4.800	26.500	3.350	21.000	2.550	16.000	1.900
R2x4	31.000	5.700	24.000	4.400	20.000	3.200	16.000	2.400	12.000	1.800
R2,5x5	25.000	5.450	19.000	4.000	16.000	2.850	13.000	2.150	9.550	1.600
R3x6	20.500	5.200	16.000	3.450	13.500	2.550	10.500	2.050	7.950	1.550
R4 x 8	15.500	4.450	12.000	3.050	9.950	2.250	7.950	1.800	5.950	1.350
R5x10	12.500	3.950	9.550	2.650	7.950	1.900	6.350	1.550	4.800	1.150
R6x12	10.500	3.700	7.950	2.500	6.650	1.600	5.300	1.350	4.000	995

Max cutting depth		Hardened Steel 45~55 HRC		Hardened Steel 55~60 HRC		Hardened Steel 60~65 HRC	
		ap	pf	ap	pf	ap	pf
		0,02D	0,05D	0,02D	0,05D	0,01D	0,05D

1. Use a rigid and precise machine and holder.
2. We suggest using air blow or MQL (mist).
3. These milling conditions are for end mill where the tool extension length is 4 times the diameter of the end mill. When length of the tool extension from the machine is long, reduce the speed and feed and milling depth.
4. The above condition shows an approximate standard for contouring operation (side milling) with a low machining load. If abnormal cutting sounds, vibration or chattering occur depending on the machining shape, cutting amount, rigidity of the machine or work holding condition, etc., please adjust the speed, feed and the depth of cut. As a guideline in selecting end mills. To increase the depth of cut, use the FX Heavy Cutting Strong Ball Series (FX-HS-EBDS). To increase the feed rate, use the FX Multiple Flute Ball Series (FX-EBT, FXS-EBM).

Regular milling

Ø	Tool Steel • Hardened Steel • Prehardened Steel ~45 HRC SKD • NAK80 • HPM50		Hardened Steel 45~55 HRC		Hardened Steel 55~60 HRC		Hardened Steel 60~65 HRC		Hardened Steel 65~70 HRC	
	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)
R0,5	32.000	2.350	32.000	2.350	32.000	2.000	32.000	1.600	32.000	1450
R0,75	32.000	3.050	32.000	3.050	32.000	2.500	26.500	1.900	21.000	1400
R1	32.000	3.600	32.000	3.550	24.000	2.200	2.000	1.750	16.000	1250
R1,5	26.500	4.000	21.000	3.200	16.000	2.000	13.500	1.600	10.500	1200
R2	20.000	3.650	16.000	2.950	12.000	1.900	9.950	1.500	7.950	1150
R2,5	16.000	3.500	12.500	2.650	9.550	1.700	7.950	1.350	6.350	1000
R3	13.500	3.350	10.500	2.300	7.950	1.550	6.650	1.250	5.300	955
R4	9.950	2.850	7.950	2.050	5.950	1.350	4.950	1.050	4.000	830
R5	7.950	2.550	6.350	1.800	4.800	1.150	4.000	875	3.200	700
R6	6.650	2.400	5.300	1.650	4.000	955	3.300	795	2.650	635
R8	4.950	1.800	4.000	1.250	3.000	775	2.500	595	2.000	475
R10	4.000	1.450	3.200	1.000	2.400	620	2.000	475	1.600	380
R12,5	3.200	1.150	2.550	815	1.900	495	1.600	380	1.250	305

Max cutting depth		Hardened Steel 45~55 HRC		Hardened Steel 55~60 HRC		Hardened Steel 60~65 HRC	
		ap	pf	ap	pf	ap	pf
		0,05D	0,1D	0,03D	0,1D	0,02D	0,05D
		ap max = 0,5mm		ap max = 0,5mm		ap max = 0,3mm	

1. Use a rigid and precise machine and holder.
2. We suggest using air blow or MQL (mist).
3. These milling conditions are for end mill where the tool extension length is 4 times the diameter of the end mill. When length of the tool extension from the machine is long, reduce the speed and feed and milling depth.
4. The above condition shows an approximate standard for contouring operation (side milling) with a low machining load. If abnormal cutting sounds, vibration or chattering occur depending on the machining shape, cutting amount, rigidity of the machine or work holding condition, etc., please adjust the speed, feed and the depth of cut. As a guideline in selecting end mills. To increase the depth of cut, use the FX Heavy Cutting Strong Ball Series (FX-HS-EBDS). To increase the feed rate, use the FX Multiple Flute Ball Series (FX-EBT, FXS-EBM).

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-LN-EBD

High speed milling

Vc		C≤0,2% - GG				~30 HRC				30~38 HRC			
		120 (m/min)				110 (m/min)				100 (m/min)			
R	l1 (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
0,1	0,3	50,000	70	0,003	0,003	50,000	70	0,003	0,003	50,000	70	0,003	0,003
0,1	0,5	50,000	50	0,003	0,003	50,000	50	0,003	0,003	50,000	50	0,003	0,003
0,2	0,5	50,000	400	0,005	0,005	50,000	400	0,005	0,005	50,000	380	0,005	0,005
0,2	0,75	50,000	360	0,005	0,005	50,000	360	0,005	0,005	50,000	340	0,005	0,005
0,2	1	50,000	360	0,005	0,005	50,000	360	0,005	0,005	50,000	340	0,005	0,005
0,2	1,25	47,000	320	0,005	0,005	47,000	320	0,005	0,005	47,000	300	0,005	0,005
0,2	1,5	45,000	300	0,005	0,005	45,000	300	0,005	0,005	45,000	280	0,005	0,005
0,2	1,75	42,000	260	0,005	0,005	42,000	260	0,005	0,005	42,000	240	0,005	0,005
0,2	2	38,000	230	0,005	0,005	38,000	230	0,005	0,005	38,000	210	0,005	0,005
0,2	2,5	32,000	170	0,004	0,005	32,000	170	0,005	0,004	32,000	160	0,004	0,005
0,2	3	32,000	150	0,004	0,005	32,000	150	0,005	0,004	32,000	140	0,004	0,005
0,3	1,2	50,000	600	0,005	0,010	50,000	600	0,005	0,010	50,000	570	0,005	0,010
0,3	2	50,000	600	0,005	0,010	50,000	600	0,005	0,010	50,000	570	0,005	0,010
0,3	2,5	50,000	600	0,005	0,010	50,000	600	0,005	0,010	50,000	570	0,005	0,010
0,3	3	50,000	600	0,005	0,010	50,000	600	0,005	0,010	50,000	570	0,005	0,010
0,3	3,5	47,000	510	0,005	0,010	47,000	510	0,005	0,010	47,000	480	0,005	0,010
0,3	4	45,000	480	0,005	0,005	45,000	480	0,005	0,005	45,000	450	0,005	0,005
0,3	4,5	45,000	400	0,005	0,005	45,000	400	0,005	0,005	45,000	380	0,005	0,005
0,3	5	40,000	300	0,005	0,005	40,000	300	0,005	0,005	40,000	280	0,005	0,005
0,3	6	38,000	250	0,005	0,005	38,000	250	0,005	0,005	38,000	230	0,005	0,005
0,3	7	34,000	200	0,004	0,005	34,000	200	0,004	0,005	34,000	190	0,005	0,004
0,3	8	32,000	150	0,004	0,005	32,000	150	0,004	0,005	32,000	140	0,005	0,004
0,3	9	32,000	130	0,004	0,005	32,000	130	0,004	0,005	32,000	120	0,005	0,004
0,3	10	29,000	100	0,004	0,005	29,000	100	0,004	0,005	29,000	95	0,005	0,004
0,4	0,8	50,000	900	0,010	0,020	50,000	900	0,010	0,020	50,000	850	0,010	0,020
0,4	1	50,000	900	0,010	0,020	50,000	900	0,010	0,020	50,000	850	0,010	0,020
0,4	1,5	50,000	800	0,010	0,020	50,000	800	0,010	0,020	50,000	760	0,010	0,020
0,4	2	50,000	700	0,010	0,020	50,000	700	0,010	0,020	50,000	660	0,010	0,020
0,4	2,5	45,000	550	0,008	0,015	45,000	550	0,008	0,015	45,000	520	0,008	0,015
0,4	3	43,000	500	0,005	0,010	43,000	500	0,005	0,010	43,000	470	0,005	0,010
0,4	3,5	40,000	420	0,005	0,010	40,000	420	0,005	0,010	40,000	400	0,005	0,010
0,4	4	36,000	370	0,005	0,005	36,000	370	0,005	0,005	36,000	350	0,005	0,005
0,4	4,5	32,000	290	0,004	0,005	32,000	290	0,004	0,005	32,000	270	0,004	0,005
0,4	5	32,000	280	0,004	0,005	32,000	280	0,004	0,005	32,000	260	0,004	0,005
0,4	5,5	30,000	230	0,004	0,005	30,000	230	0,004	0,005	30,000	210	0,004	0,005
0,4	6	30,000	200	0,004	0,005	30,000	200	0,004	0,005	30,000	190	0,004	0,005
0,5	1	50,000	1.100	0,015	0,030	50,000	1.100	0,015	0,030	50,000	1.050	0,015	0,030
0,5	1,5	50,000	1.100	0,015	0,030	50,000	1.100	0,015	0,030	50,000	1.050	0,015	0,030
0,5	2	50,000	1.000	0,015	0,030	50,000	1.000	0,015	0,030	50,000	950	0,015	0,030
0,5	2,5	50,000	1.000	0,015	0,030	50,000	1.000	0,015	0,030	50,000	950	0,015	0,030
0,5	3	48,000	900	0,010	0,020	48,000	900	0,010	0,020	48,000	850	0,010	0,020
0,5	3,5	45,000	700	0,010	0,020	45,000	700	0,010	0,020	45,000	650	0,010	0,020
0,5	4	43,000	600	0,010	0,010	43,000	600	0,010	0,010	43,000	570	0,010	0,010
0,5	4,5	38,000	500	0,010	0,010	38,000	500	0,010	0,010	38,000	470	0,010	0,010
0,5	5	30,000	400	0,005	0,010	30,000	400	0,005	0,010	30,000	380	0,005	0,010
0,5	5,5	28,000	300	0,004	0,005	28,000	300	0,004	0,005	28,000	280	0,004	0,005
0,5	6	26,000	250	0,004	0,005	26,000	250	0,004	0,005	26,000	230	0,004	0,005
0,5	7	24,000	200	0,004	0,005	24,000	200	0,004	0,005	24,000	190	0,004	0,005
0,5	8	22,000	160	0,004	0,005	22,000	160	0,004	0,005	22,000	150	0,004	0,005
0,5	9	20,000	120	0,004	0,005	20,000	120	0,004	0,005	20,000	110	0,004	0,005
0,5	10	20,000	100	0,004	0,005	20,000	100	0,004	0,005	20,000	95	0,004	0,005
0,6	1,2	50,000	1.350	0,030	0,050	50,000	1.350	0,030	0,050	50,000	1.200	0,030	0,050
0,6	2	50,000	1.300	0,030	0,050	50,000	1.300	0,030	0,050	50,000	1.200	0,030	0,050
0,6	2,5	50,000	1.200	0,030	0,050	50,000	1.200	0,030	0,050	50,000	1.100	0,030	0,050
0,6	3	50,000	1.200	0,020	0,030	50,000	1.200	0,020	0,030	50,000	1.100	0,020	0,030
0,6	3,5	45,000	1.000	0,020	0,030	45,000	1.000	0,020	0,030	45,000	950	0,020	0,030
0,6	4	40,000	900	0,010	0,020	40,000	900	0,010	0,020	40,000	850	0,010	0,020
0,6	4,5	34,000	780	0,010	0,020	34,000	780	0,010	0,020	34,000	740	0,010	0,020
0,6	5	30,000	680	0,010	0,020	30,000	680	0,010	0,020	30,000	640	0,010	0,020
0,6	5,5	28,000	650	0,010	0,020	28,000	650	0,010	0,020	28,000	610	0,010	0,020
0,6	6	26,000	600	0,010	0,020	26,000	600	0,010	0,020	26,000	570	0,010	0,020
0,6	6,5	24,000	550	0,010	0,010	24,000	550	0,010	0,010	24,000	520	0,010	0,010
0,6	7	23,000	450	0,010	0,010	23,000	450	0,010	0,010	23,000	420	0,010	0,010
0,6	7,5	23,000	400	0,010	0,010	23,000	400	0,010	0,010	23,000	380	0,010	0,010
0,6	8	20,000	320	0,005	0,010	20,000	320	0,005	0,010	20,000	300	0,005	0,010
0,6	8,5	20,000	300	0,005	0,010	20,000	300	0,005	0,010	20,000	280	0,005	0,010
0,6	9	20,000	280	0,005	0,010	20,000	280	0,005	0,010	20,000	260	0,005	0,010
0,6	9,5	20,000	240	0,005	0,008	20,000	240	0,005	0,008	20,000	220	0,005	0,008
0,6	10	20,000	200	0,005	0,008	20,000	200	0,005	0,008	20,000	190	0,005	0,008
0,6	11	18,000	150	0,005	0,008	18,000	150	0,005	0,008	18,000	140	0,005	0,008
0,6	12	18,000	120	0,005	0,005	18,000	120	0,005	0,005	18,000	110	0,005	0,005
0,8	2	50,000	2.000	0,040	0,080	50,000	2.000	0,040	0,080	50,000	1.900	0,040	0,080
0,8	3	48,000	1.600	0,040	0,080	48,000	1.600	0,040	0,080	48,000	1.500	0,040	0,080
0,8	4	40,000	1.200	0,040	0,080	40,000	1.200	0,040	0,080	40,000	1.100	0,040	0,080
0,8	5	34,000	950	0,030	0,050	34,000	950	0,030	0,050	34,000	900	0,030	0,050
0,8	6	30,000	800	0,030	0,050	30,000	800	0,030	0,050	30,000	760	0,030	0,050
0,8	7	25,000	600	0,010	0,020	25,000	600	0,010	0,020	25,000	570	0,010	0,020
0,8	8	23,000	450	0,005	0,010	23,000	450	0,005	0,010	23,000	420	0,005	0,010
0,8	10	18,000	320	0,005	0,008	18,000	320	0,005	0,008	18,000	300	0,005	0,008

Milling | Endmills

Cutting conditions

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-LN-EBD

High speed milling



Vc		C≤0,2% - GG				~30 HRC				30~38 HRC			
R	l1 (mm)	120 (m/min)				110 (m/min)				100 (m/min)			
		S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
0,8	12	17.000	250	0,005	0,005	17.000	250	0,005	0,005	17.000	230	0,005	0,005
1	2	50.000	3.700	0,050	0,100	50.000	3.700	0,050	0,100	50.000	3.700	0,050	0,100
1	3	45.000	3.200	0,050	0,100	45.000	3.200	0,050	0,100	45.000	3.000	0,050	0,100
1	4	40.000	3.000	0,050	0,100	40.000	3.000	0,050	0,100	40.000	2.850	0,050	0,100
1	5	36.000	2.300	0,050	0,100	36.000	2.300	0,050	0,100	36.000	2.100	0,050	0,100
1	6	30.000	2.000	0,050	0,100	30.000	2.000	0,050	0,100	30.000	1.900	0,050	0,100
1	7	27.000	1.700	0,050	0,100	27.000	1.700	0,050	0,100	27.000	1.600	0,050	0,100
1	8	26.000	1.600	0,050	0,100	26.000	1.600	0,050	0,100	26.000	1.500	0,050	0,100
1	9	24.000	1.200	0,030	0,050	24.000	1.200	0,030	0,050	24.000	1.100	0,030	0,050
1	10	22.000	1.100	0,010	0,020	22.000	1.100	0,010	0,020	22.000	1.000	0,010	0,020
1	12	20.000	800	0,010	0,010	20.000	800	0,010	0,010	20.000	760	0,010	0,010
1	14	18.000	600	0,005	0,010	18.000	600	0,005	0,010	18.000	570	0,005	0,010
1	16	16.000	420	0,005	0,010	16.000	420	0,005	0,010	16.000	400	0,005	0,010
1	18	14.000	320	0,005	0,005	14.000	320	0,005	0,005	14.000	300	0,005	0,005
1	20	13.000	300	0,005	0,005	13.000	300	0,005	0,005	13.000	285	0,005	0,005
1	22	12.000	200	0,005	0,005	12.000	200	0,005	0,005	12.000	190	0,005	0,005
1,2	2,4	50.000	3.800	0,060	0,120	50.000	3.800	0,060	0,120	50.000	3.600	0,060	0,120
1,2	4	40.000	3.000	0,060	0,120	40.000	3.000	0,060	0,120	40.000	2.850	0,060	0,120
1,2	6	32.000	2.100	0,060	0,120	32.000	2.100	0,060	0,120	32.000	2.000	0,060	0,120
1,2	8	25.000	1.700	0,060	0,120	25.000	1.700	0,060	0,120	25.000	1.600	0,060	0,120
1,2	10	20.000	1.200	0,050	0,100	20.000	1.200	0,050	0,100	20.000	1.100	0,050	0,100
1,2	12	19.000	900	0,030	0,050	19.000	900	0,030	0,050	19.000	850	0,030	0,050
1,2	14	18.000	650	0,030	0,050	18.000	650	0,030	0,050	18.000	610	0,030	0,050
1,2	16	16.000	450	0,020	0,050	16.000	450	0,020	0,050	16.000	420	0,020	0,050
1,2	18	16.000	350	0,005	0,005	16.000	350	0,005	0,005	16.000	330	0,005	0,005
1,2	20	14.000	320	0,005	0,005	14.000	320	0,005	0,005	14.000	300	0,005	0,005
1,4	8	25.000	1.700	0,070	0,140	25.000	1.700	0,07	0,140	25.000	1.600	0,070	0,140
1,4	12	19.000	1.000	0,030	0,070	19.000	1.000	0,03	0,070	19.000	950	0,030	0,070
1,4	16	14.000	500	0,020	0,050	14.000	500	0,02	0,050	14.000	470	0,020	0,050
1,5	3	50.000	4.800	0,075	0,150	50.000	4.800	0,075	0,150	50.000	4.800	0,075	0,150
1,5	4	40.000	3.900	0,075	0,150	40.000	3.900	0,075	0,150	40.000	3.700	0,075	0,150
1,5	6	30.000	2.900	0,075	0,150	30.000	2.900	0,075	0,150	30.000	2.700	0,075	0,150
1,5	8	24.000	2.300	0,075	0,150	24.000	2.300	0,075	0,150	24.000	2.100	0,075	0,150
1,5	10	24.000	2.000	0,075	0,150	24.000	2.000	0,075	0,150	24.000	1.900	0,075	0,150
1,5	12	21.000	1.400	0,075	0,100	21.000	1.400	0,075	0,100	21.000	1.300	0,075	0,100
1,5	14	18.000	1.200	0,050	0,100	18.000	1.200	0,050	0,100	18.000	1.100	0,050	0,100
1,5	16	16.000	800	0,050	0,100	16.000	800	0,050	0,100	16.000	760	0,050	0,100
1,5	18	14.000	500	0,030	0,050	14.000	500	0,030	0,050	14.000	470	0,030	0,050
1,5	20	13.000	360	0,020	0,050	13.000	360	0,020	0,050	13.000	340	0,020	0,050
1,5	22	13.000	320	0,020	0,050	13.000	320	0,020	0,050	13.000	300	0,020	0,050
1,5	30	12.000	200	0,005	0,010	12.000	200	0,005	0,010	12.000	190	0,005	0,010
1,6	8	24.000	3.000	0,080	0,160	24.000	3.000	0,080	0,160	24.000	2.800	0,080	0,160
1,6	12	21.000	1.800	0,050	0,100	21.000	1.800	0,050	0,100	21.000	1.700	0,050	0,100
1,6	16	16.000	800	0,050	0,100	16.000	800	0,050	0,100	16.000	760	0,050	0,100
1,6	20	13.000	380	0,030	0,050	13.000	380	0,030	0,050	13.000	360	0,030	0,050
1,8	8	21.000	3.000	0,090	0,270	21.000	3.000	0,090	0,270	21.000	2.800	0,090	0,270
1,8	12	18.000	1.800	0,090	0,180	18.000	1.800	0,090	0,180	18.000	1.700	0,090	0,180
1,8	16	16.000	900	0,050	0,120	16.000	900	0,050	0,120	16.000	850	0,050	0,120
1,8	20	12.000	380	0,040	0,050	12.000	380	0,040	0,050	12.000	360	0,040	0,050
2	4	50.000	5.600	0,100	0,200	50.000	5.600	0,100	0,200	50.000	5.600	0,100	0,200
2	6	36.000	3.000	0,100	0,200	36.000	3.000	0,100	0,200	36.000	2.800	0,100	0,200
2	8	25.000	2.600	0,100	0,200	25.000	2.600	0,100	0,200	25.000	2.400	0,100	0,200
2	10	20.000	2.400	0,100	0,200	20.000	2.400	0,100	0,200	20.000	2.200	0,100	0,200
2	12	16.000	2.000	0,100	0,200	16.000	2.000	0,100	0,200	16.000	1.900	0,100	0,200
2	14	15.000	1.800	0,100	0,200	15.000	1.800	0,100	0,200	15.000	1.700	0,100	0,200
2	16	14.000	1.700	0,100	0,100	14.000	1.700	0,100	0,100	14.000	1.600	0,100	0,100
2	18	13.000	1.600	0,100	0,100	13.000	1.600	0,100	0,100	13.000	1.500	0,100	0,100
2	20	12.000	1.200	0,050	0,100	12.000	1.200	0,050	0,100	12.000	1.100	0,050	0,100
2	22	10.000	1.000	0,050	0,100	10.000	1.000	0,050	0,100	10.000	950	0,050	0,100
2	25	10.000	800	0,030	0,050	10.000	800	0,030	0,050	10.000	760	0,030	0,050
2	30	10.000	500	0,020	0,050	10.000	500	0,020	0,050	10.000	470	0,020	0,050
2	35	8.000	250	0,020	0,030	8.000	250	0,020	0,030	8.000	230	0,020	0,030
2	40	7.000	150	0,020	0,030	7.000	150	0,020	0,030	7.000	140	0,020	0,030
2,5	10	20.000	3.300	0,100	0,200	20.000	3.300	0,100	0,200	20.000	3.100	0,100	0,200
2,5	15	17.000	2.800	0,100	0,200	17.000	2.800	0,100	0,200	17.000	2.600	0,100	0,200
2,5	20	15.000	1.800	0,100	0,200	15.000	1.800	0,100	0,200	15.000	1.700	0,100	0,200
2,5	25	12.000	1.000	0,030	0,050	12.000	1.000	0,030	0,050	12.000	950	0,030	0,050
2,5	30	10.000	800	0,030	0,050	10.000	800	0,030	0,050	10.000	760	0,030	0,050
2,5	35	8.000	500	0,020	0,030	8.000	500	0,020	0,030	8.000	470	0,020	0,030
3	6	41.500	6.200	0,150	0,300	41.500	6.200	0,150	0,300	41.500	6.200	0,150	0,300
3	8	30.000	4.500	0,150	0,300	30.000	4.500	0,150	0,300	30.000	4.200	0,150	0,300
3	10	25.000	3.800	0,150	0,300	25.000	3.800	0,150	0,300	25.000	3.600	0,150	0,300
3	12	20.000	3.000	0,150	0,300	20.000	3.000	0,150	0,300	20.000	2.800	0,150	0,300
3	14	18.000	2.700	0,150	0,300	18.000	2.700	0,150	0,300	18.000	2.500	0,150	0,300
3	15	16.000	2.400	0,100	0,300	16.000	2.400	0,100	0,300	16.000	2.200	0,100	0,300
3	16	16.000	2.000	0,100	0,200	16.000	2.000	0,100	0,200	16.000	1.900	0,100	0,200
3	20	14.000	1.800	0,100	0,200	14.000	1.800	0,100	0,200	14.000	1.700	0,100	0,200
3	25	12.000	1.200	0,050	0,100	12.000	1.200	0,050	0,100	12.000	1.100	0,050	0,100
3	30	10.000	800	0,030	0,050	10.000	800	0,030	0,050	10.000	760	0,030	0,050

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-LN-EBD

High speed milling

Vc		C≤0,2% - GG					~30 HRC				30~38 HRC			
		120 (m/min)					110 (m/min)				100 (m/min)			
R	l1 (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	
3	35	8.000	600	0,020	0,050	8.000	600	0,020	0,050	8.000	570	0,020	0,050	
3	40	7.000	500	0,020	0,030	7.000	500	0,020	0,030	7.000	470	0,020	0,030	
3,5	15	18.000	3.000	0,100	0,300	18.000	3.000	0,100	0,300	18.000	2.800	0,100	0,300	
3,5	20	16.000	2.700	0,100	0,200	16.000	2.700	0,100	0,200	16.000	2.500	0,100	0,200	
3,5	25	12.000	2.000	0,100	0,100	12.000	2.000	0,100	0,100	12.000	1.900	0,100	0,100	
3,5	30	10.000	1.600	0,050	0,100	10.000	1.600	0,050	0,100	10.000	1.500	0,050	0,100	
3,5	35	10.000	1.000	0,050	0,050	10.000	1.000	0,050	0,050	10.000	950	0,050	0,050	
3,5	40	8.000	800	0,050	0,050	8.000	800	0,050	0,050	8.000	760	0,050	0,050	
3,5	45	7.000	600	0,030	0,030	7.000	600	0,030	0,030	7.000	570	0,030	0,030	
4	8	31.000	5.700	0,200	0,500	31.000	5.700	0,200	0,500	31.000	5.700	0,200	0,500	
4	10	25.000	4.500	0,200	0,500	25.000	4.500	0,200	0,500	25.000	4.200	0,200	0,500	
4	12	20.000	3.600	0,200	0,500	20.000	3.600	0,200	0,500	20.000	3.400	0,200	0,500	
4	15	20.000	3.600	0,200	0,500	20.000	3.600	0,200	0,500	20.000	3.400	0,200	0,500	
4	16	18.000	3.200	0,200	0,500	18.000	3.200	0,200	0,500	18.000	3.000	0,200	0,500	
4	20	16.000	2.800	0,200	0,400	16.000	2.800	0,200	0,400	16.000	2.600	0,200	0,400	
4	25	16.000	2.800	0,100	0,300	16.000	2.800	0,100	0,300	16.000	2.600	0,100	0,300	
4	30	14.000	2.400	0,100	0,200	14.000	2.400	0,100	0,200	14.000	2.200	0,100	0,200	
4	35	12.000	1.800	0,100	0,200	12.000	1.800	0,100	0,200	12.000	1.700	0,100	0,200	
4	40	10.000	1.300	0,050	0,100	10.000	1.300	0,050	0,100	10.000	1.200	0,050	0,100	
4	45	8.000	1.000	0,050	0,050	8.000	1.000	0,050	0,050	8.000	950	0,050	0,050	
4	50	7.000	700	0,020	0,050	7.000	700	0,020	0,050	7.000	660	0,020	0,050	
5	10	25.000	5.400	0,250	0,500	25.000	5.400	0,250	0,500	25.000	5.400	0,250	0,500	
5	15	20.000	4.200	0,250	0,500	20.000	4.200	0,250	0,500	20.000	3.900	0,250	0,500	
5	20	16.000	3.500	0,250	0,500	16.000	3.500	0,250	0,500	16.000	3.300	0,250	0,500	
5	25	15.000	3.200	0,200	0,300	15.000	3.200	0,200	0,300	15.000	3.000	0,200	0,300	
5	30	14.000	2.500	0,100	0,300	14.000	2.500	0,100	0,300	14.000	2.300	0,100	0,300	
5	35	12.000	1.600	0,100	0,300	12.000	1.600	0,100	0,300	12.000	1.500	0,100	0,300	
5	40	10.000	1.200	0,100	0,200	10.000	1.200	0,100	0,200	10.000	1.100	0,100	0,200	
5	45	9.000	900	0,100	0,100	9.000	900	0,100	0,100	9.000	850	0,100	0,100	
5	50	8.000	800	0,100	0,100	8.000	800	0,100	0,100	8.000	760	0,100	0,100	
6	12	20.000	5.200	0,300	0,500	20.000	5.200	0,300	0,500	20.000	5.200	0,300	0,500	
6	20	16.000	4.200	0,300	0,500	16.000	4.200	0,300	0,500	16.000	3.900	0,300	0,500	
6	25	12.000	3.200	0,300	0,500	12.000	3.200	0,300	0,500	12.000	3.000	0,300	0,500	
6	30	10.000	2.600	0,300	0,500	10.000	2.600	0,300	0,500	10.000	2.400	0,300	0,500	
6	35	9.000	2.300	0,200	0,400	9.000	2.300	0,200	0,400	9.000	2.100	0,200	0,400	
6	40	9.000	2.000	0,200	0,300	9.000	2.000	0,200	0,300	9.000	1.900	0,200	0,300	
6	45	8.000	1.800	0,200	0,300	8.000	1.800	0,200	0,300	8.000	1.700	0,200	0,300	
6	50	7.000	1.600	0,200	0,300	7.000	1.600	0,200	0,300	7.000	1.500	0,200	0,300	

Max cutting depth

Attention : sparks and/or flames can cause coolant fire. Be sure adequate fire prevention is available.

- Speeds and feeds are designed to be used in conjunction with small passes on a high speed & precision machine set-up.
- Do not use inflammable coolant. Using worn tools may generate sparks.
- Use compressed air or a high quality coolant with a low co-efficient of smoke emission.

* Modified parameters

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-LN-EBD

High speed milling



		38 ~ 45 HRC				45 ~ 55 HRC				55 ~ 60 HRC			
Vc		120 (m/min)				110 (m/min)				100 (m/min)			
R	l1 (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
0,1	0,3	50.000	70	0,003	0,003	50.000	60	0,003	0,003	-	-	-	-
0,1	0,5	50.000	50	0,003	0,003	50.000	40	0,003	0,003	-	-	-	-
0,2	0,5	50.000	380	0,005	0,005	50.000	260	0,005	0,005	50.000	200	0,004	0,005
0,2	0,75	50.000	340	0,005	0,005	50.000	230	0,005	0,005	50.000	180	0,004	0,005
0,2	1	50.000	340	0,005	0,005	50.000	230	0,005	0,005	50.000	180	0,004	0,005
0,2	1,25	47.000	300	0,005	0,005	47.000	210	0,005	0,005	43.000	150	0,004	0,005
0,2	1,5	45.000	280	0,005	0,005	45.000	190	0,005	0,005	41.000	130	0,004	0,005
0,2	1,75	42.000	240	0,005	0,005	42.000	170	0,005	0,005	38.000	120	0,004	0,005
0,2	2	38.000	210	0,005	0,005	37.000	140	0,005	0,005	33.000	100	0,004	0,005
0,2	2,5	32.000	160	0,004	0,005	31.000	100	0,004	0,005	31.000	80	0,004	0,005
0,2	3	32.000	140	0,004	0,005	31.000	90	0,004	0,005	31.000	70	0,004	0,005
0,3	1,2	50.000	570	0,005	0,010	50.000	390	0,005	0,010	50.000	300	0,005	0,010
0,3	2	50.000	570	0,005	0,010	50.000	390	0,005	0,010	50.000	310	0,005	0,010
0,3	2,5	50.000	570	0,005	0,010	50.000	380	0,005	0,010	50.000	300	0,005	0,010
0,3	3	50.000	570	0,005	0,010	50.000	370	0,005	0,010	50.000	290	0,005	0,010
0,3	3,5	47.000	480	0,005	0,010	47.000	310	0,005	0,010	43.000	220	0,005	0,010
0,3	4	45.000	450	0,005	0,005	45.000	290	0,005	0,005	41.000	210	0,004	0,005
0,3	4,5	45.000	380	0,005	0,005	45.000	250	0,005	0,005	41.000	180	0,004	0,005
0,3	5	40.000	280	0,005	0,005	40.000	190	0,005	0,005	36.000	130	0,004	0,005
0,3	6	38.000	230	0,005	0,005	37.000	150	0,005	0,005	33.000	100	0,004	0,005
0,3	7	34.000	190	0,004	0,005	33.000	120	0,004	0,005	33.000	95	0,004	0,005
0,3	8	32.000	140	0,004	0,005	31.000	90	0,004	0,005	31.000	70	0,004	0,005
0,3	9	32.000	120	0,004	0,005	31.000	80	0,004	0,005	31.000	60	0,004	0,005
0,3	10	29.000	95	0,004	0,005	28.000	60	0,004	0,005	28.000	50	0,004	0,005
0,4	0,8	50.000	850	0,010	0,020	50.000	590	0,010	0,020	50.000	470	0,008	0,015
0,4	1	50.000	850	0,010	0,020	50.000	550	0,010	0,020	50.000	440	0,008	0,015
0,4	1,5	50.000	760	0,010	0,020	50.000	520	0,010	0,020	50.000	410	0,008	0,015
0,4	2	50.000	660	0,010	0,020	50.000	460	0,010	0,020	45.000	330	0,008	0,015
0,4	2,5	45.000	520	0,008	0,015	45.000	360	0,008	0,015	41.000	260	0,008	0,015
0,4	3	43.000	470	0,005	0,010	43.000	320	0,005	0,010	38.000	220	0,005	0,010
0,4	3,5	40.000	400	0,005	0,010	40.000	280	0,005	0,010	36.000	200	0,005	0,010
0,4	4	36.000	350	0,005	0,005	35.000	230	0,005	0,005	31.000	160	0,005	0,005
0,4	4,5	32.000	270	0,004	0,005	31.000	180	0,004	0,005	28.000	130	0,004	0,005
0,4	5	32.000	260	0,004	0,005	31.000	170	0,004	0,005	28.000	120	0,004	0,005
0,4	5,5	30.000	210	0,004	0,005	29.000	140	0,004	0,005	26.000	100	0,004	0,005
0,4	6	30.000	190	0,004	0,005	29.000	120	0,004	0,005	26.000	100	0,004	0,005
0,5	1	50.000	1.050	0,015	0,030	50.000	730	0,015	0,030	50.000	580	0,010	0,020
0,5	1,5	50.000	1.050	0,015	0,030	50.000	700	0,015	0,030	50.000	560	0,010	0,020
0,5	2	50.000	950	0,015	0,030	50.000	650	0,015	0,030	50.000	520	0,010	0,020
0,5	2,5	50.000	950	0,015	0,030	50.000	600	0,015	0,030	45.000	430	0,010	0,020
0,5	3	48.000	850	0,010	0,020	48.000	550	0,010	0,020	43.000	390	0,010	0,020
0,5	3,5	45.000	650	0,010	0,020	45.000	450	0,010	0,020	40.000	320	0,010	0,020
0,5	4	43.000	570	0,010	0,010	43.000	390	0,010	0,010	38.000	270	0,010	0,010
0,5	4,5	38.000	470	0,010	0,010	38.000	320	0,010	0,010	34.000	220	0,010	0,010
0,5	5	30.000	380	0,005	0,010	29.000	250	0,005	0,010	26.000	170	0,005	0,010
0,5	5,5	28.000	280	0,004	0,005	27.000	180	0,004	0,005	24.000	120	0,004	0,005
0,5	6	26.000	230	0,004	0,005	25.000	150	0,004	0,005	22.000	100	0,004	0,005
0,5	7	24.000	190	0,004	0,005	23.000	130	0,004	0,005	20.000	100	0,004	0,005
0,5	8	22.000	150	0,004	0,005	21.000	110	0,004	0,005	20.000	100	0,004	0,005
0,5	9	20.000	110	0,004	0,005	21.000	100	0,004	0,005	20.000	90	0,004	0,005
0,5	10	20.000	95	0,004	0,005	21.000	100	0,004	0,005	20.000	90	0,004	0,005
0,6	1,2	50.000	1.200	0,030	0,050	50.000	840	0,030	0,050	50.000	670	0,010	0,020
0,6	2	50.000	1.200	0,030	0,050	50.000	820	0,030	0,050	50.000	650	0,010	0,020
0,6	2,5	50.000	1.100	0,030	0,050	50.000	770	0,030	0,050	50.000	610	0,010	0,020
0,6	3	50.000	1.100	0,020	0,030	50.000	750	0,020	0,030	45.000	540	0,010	0,020
0,6	3,5	45.000	950	0,020	0,030	45.000	660	0,020	0,030	41.000	480	0,010	0,020
0,6	4	40.000	850	0,010	0,020	40.000	590	0,010	0,020	36.000	420	0,010	0,020
0,6	4,5	34.000	740	0,010	0,020	34.000	510	0,010	0,020	31.000	370	0,010	0,020
0,6	5	30.000	640	0,010	0,020	30.000	440	0,010	0,020	27.000	310	0,010	0,020
0,6	5,5	28.000	610	0,010	0,020	28.000	420	0,010	0,020	25.000	300	0,010	0,020
0,6	6	26.000	570	0,010	0,020	25.000	380	0,010	0,020	22.000	260	0,010	0,020
0,6	6,5	24.000	520	0,010	0,010	23.000	340	0,010	0,010	20.000	230	0,010	0,010
0,6	7	23.000	420	0,010	0,010	22.000	280	0,010	0,010	19.000	190	0,010	0,010
0,6	7,5	23.000	380	0,010	0,010	22.000	250	0,010	0,010	19.000	170	0,010	0,010
0,6	8	20.000	300	0,005	0,010	19.000	200	0,005	0,010	17.000	140	0,005	0,010
0,6	8,5	20.000	280	0,005	0,010	19.000	180	0,005	0,010	17.000	130	0,005	0,010
0,6	9	20.000	260	0,005	0,010	19.000	170	0,005	0,010	17.000	120	0,005	0,010
0,6	9,5	20.000	220	0,005	0,008	19.000	140	0,005	0,008	17.000	110	0,005	0,008
0,6	10	20.000	190	0,005	0,008	19.000	120	0,005	0,008	17.000	100	0,005	0,008
0,6	11	18.000	140	0,005	0,008	17.000	90	0,005	0,008	17.000	80	0,005	0,008
0,6	12	18.000	110	0,005	0,005	17.000	80	0,005	0,005	17.000	70	0,004	0,005
0,8	2	50.000	1.900	0,040	0,080	50.000	1.600	0,040	0,080	50.000	1.200	0,015	0,030
0,8	3	48.000	1.500	0,040	0,080	48.000	1.100	0,040	0,080	45.000	820	0,015	0,030
0,8	4	40.000	1.100	0,040	0,080	40.000	1.000	0,040	0,080	38.000	760	0,015	0,030
0,8	5	34.000	900	0,030	0,050	34.000	800	0,030	0,050	31.000	580	0,015	0,030
0,8	6	30.000	760	0,030	0,050	30.000	650	0,030	0,050	27.000	460	0,015	0,030
0,8	7	25.000	570	0,010	0,020	25.000	450	0,010	0,020	22.000	310	0,010	0,020
0,8	8	23.000	420	0,005	0,010	23.000	300	0,005	0,010	20.000	200	0,005	0,010
0,8	10	18.000	300	0,005	0,008	17.000	200	0,005	0,008	17.000	170	0,005	0,008

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-LN-EBD

High speed milling

Vc		38 ~ 45 HRC				45 ~ 55 HRC				55 ~ 60 HRC			
		120 (m/min)				110 (m/min)				100 (m/min)			
R	l1 (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
0,8	12	17.000	230	0,005	0,005	16.000	160	0,005	0,005	16.000	110	0,005	0,005
1	2	50.000	3.700	0,050	0,100	50.000	3.700	0,050	0,100	50.000	3.000	0,020	0,050
1	3	45.000	3.000	0,050	0,100	45.000	2.400	0,050	0,100	45.000	1.900	0,020	0,050
1	4	40.000	2.850	0,050	0,100	40.000	2.200	0,050	0,100	40.000	1.700	0,020	0,050
1	5	36.000	2.100	0,050	0,100	36.000	1.600	0,050	0,100	36.000	1.200	0,020	0,050
1	6	30.000	1.900	0,050	0,100	30.000	1.500	0,050	0,100	30.000	1.200	0,020	0,050
1	7	27.000	1.600	0,050	0,100	27.000	1.300	0,050	0,100	27.000	1.000	0,020	0,050
1	8	26.000	1.500	0,050	0,100	26.000	1.200	0,050	0,100	26.000	960	0,020	0,050
1	9	24.000	1.100	0,030	0,050	24.000	880	0,030	0,050	24.000	700	0,020	0,050
1	10	22.000	1.000	0,010	0,020	21.000	760	0,010	0,020	18.000	520	0,010	0,020
1	12	20.000	760	0,010	0,010	19.000	570	0,010	0,010	17.000	400	0,010	0,010
1	14	18.000	570	0,005	0,010	17.000	430	0,005	0,010	15.000	300	0,005	0,010
1	16	16.000	400	0,005	0,010	15.000	300	0,005	0,010	13.000	200	0,005	0,010
1	18	14.000	300	0,005	0,005	13.000	220	0,005	0,005	12.000	160	0,004	0,005
1	20	13.000	285	0,005	0,005	12.000	180	0,005	0,005	12.000	140	0,004	0,005
1	22	12.000	190	0,005	0,005	12.000	110	0,005	0,005	12.000	100	0,004	0,005
1,2	2,4	50.000	3.600	0,060	0,120	50.000	3.600	0,060	0,120	50.000	3.000	0,020	0,050
1,2	4	40.000	2.850	0,060	0,120	40.000	2.300	0,060	0,120	38.000	1.750	0,020	0,050
1,2	6	32.000	2.000	0,060	0,120	32.000	1.600	0,060	0,120	30.000	1.200	0,020	0,050
1,2	8	25.000	1.600	0,060	0,120	25.000	1.200	0,060	0,120	25.000	960	0,020	0,050
1,2	10	20.000	1.100	0,050	0,100	18.000	800	0,050	0,100	16.000	560	0,020	0,050
1,2	12	17.000	850	0,030	0,050	16.000	640	0,030	0,050	14.000	440	0,020	0,050
1,2	14	16.000	610	0,030	0,050	15.000	450	0,030	0,050	13.000	310	0,020	0,050
1,2	16	15.000	420	0,020	0,050	14.000	300	0,020	0,050	12.000	200	0,020	0,050
1,2	18	15.000	330	0,005	0,005	14.000	200	0,005	0,005	12.000	130	0,004	0,005
1,2	20	13.000	300	0,005	0,005	12.000	180	0,005	0,005	10.000	120	0,004	0,005
1,4	8	25.000	1.600	0,070	0,140	25.000	1.200	0,070	0,140	25.000	960	0,030	0,070
1,4	12	19.000	950	0,030	0,070	19.000	760	0,030	0,070	17.000	540	0,030	0,070
1,4	16	13.000	470	0,020	0,050	12.000	340	0,020	0,050	10.000	220	0,020	0,050
1,5	3	50.000	4.800	0,075	0,150	50.000	4.800	0,075	0,150	50.000	3.900	0,030	0,060
1,5	4	40.000	3.700	0,075	0,150	40.000	2.900	0,075	0,150	38.000	2.200	0,030	0,060
1,5	6	30.000	2.700	0,075	0,150	30.000	2.200	0,075	0,150	27.000	1.500	0,030	0,060
1,5	8	24.000	2.100	0,075	0,150	24.000	1.700	0,075	0,150	21.000	1.100	0,030	0,060
1,5	10	24.000	1.900	0,075	0,150	24.000	1.500	0,075	0,150	21.000	1.000	0,030	0,060
1,5	12	21.000	1.300	0,075	0,100	21.000	1.000	0,075	0,100	18.000	680	0,030	0,060
1,5	14	17.000	1.100	0,050	0,100	17.000	900	0,050	0,100	15.000	630	0,030	0,060
1,5	16	14.000	760	0,050	0,100	13.000	560	0,050	0,100	10.000	340	0,030	0,050
1,5	18	13.000	470	0,030	0,050	12.000	350	0,030	0,050	10.000	230	0,030	0,050
1,5	20	12.000	340	0,020	0,050	11.000	240	0,020	0,050	9.000	150	0,020	0,050
1,5	22	12.000	300	0,020	0,050	11.000	220	0,020	0,050	9.000	140	0,020	0,050
1,5	30	11.000	190	0,005	0,010	10.000	120	0,005	0,010	9.000	90	0,005	0,010
1,6	8	24.000	2.800	0,080	0,160	23.000	2.100	0,080	0,160	20.000	1.400	0,030	0,080
1,6	12	21.000	1.700	0,050	0,100	20.000	1.380	0,050	0,100	18.000	990	0,030	0,080
1,6	16	14.000	760	0,050	0,100	13.000	600	0,050	0,100	11.000	400	0,030	0,080
1,6	20	12.000	360	0,030	0,050	11.000	280	0,030	0,050	10.000	200	0,030	0,050
1,8	8	24.000	2.800	0,090	0,270	23.000	2.280	0,090	0,270	20.000	1.500	0,030	0,080
1,8	12	21.000	1.700	0,090	0,180	20.000	1.380	0,090	0,180	18.000	990	0,030	0,080
1,8	16	14.000	850	0,050	0,120	13.000	670	0,050	0,120	11.000	450	0,030	0,080
1,8	20	11.000	360	0,040	0,050	10.000	280	0,040	0,050	9.000	200	0,030	0,050
2	4	50.000	5.600	0,100	0,200	47.000	5.300	0,100	0,200	40.000	3.600	0,050	0,100
2	6	36.000	2.800	0,100	0,200	35.000	2.700	0,100	0,200	30.000	1.800	0,050	0,100
2	8	25.000	2.400	0,100	0,200	24.000	2.300	0,100	0,200	20.000	1.500	0,050	0,100
2	10	20.000	2.200	0,100	0,200	19.000	2.000	0,100	0,200	17.000	1.400	0,050	0,100
2	12	16.000	1.900	0,100	0,200	15.000	1.700	0,100	0,200	13.000	1.100	0,050	0,100
2	14	15.000	1.700	0,100	0,200	14.000	1.500	0,100	0,200	12.000	1.000	0,050	0,100
2	16	14.000	1.600	0,100	0,100	13.000	1.400	0,100	0,100	11.000	950	0,050	0,100
2	18	13.000	1.500	0,100	0,100	12.000	1.200	0,100	0,100	10.000	800	0,050	0,100
2	20	11.000	1.100	0,050	0,100	10.000	890	0,050	0,100	9.000	640	0,050	0,100
2	22	9.000	950	0,050	0,100	9.000	860	0,050	0,100	7.500	570	0,050	0,100
2	25	9.000	760	0,030	0,050	9.000	680	0,030	0,050	7.500	450	0,030	0,050
2	30	9.000	470	0,020	0,050	9.000	360	0,020	0,050	7.500	240	0,020	0,050
2	35	7.500	230	0,020	0,030	7.000	130	0,020	0,030	6.000	100	0,020	0,030
2	40	6.000	140	0,020	0,030	6.000	100	0,020	0,030	6.000	90	0,020	0,030
2,5	10	20.000	3.100	0,100	0,200	19.000	2.900	0,100	0,200	16.000	1.900	0,050	0,100
2,5	15	17.000	2.600	0,100	0,200	16.000	2.400	0,100	0,200	14.000	1.600	0,050	0,100
2,5	20	15.000	1.700	0,100	0,200	14.000	1.600	0,100	0,200	12.000	1.000	0,050	0,100
2,5	25	11.000	950	0,030	0,050	10.000	830	0,030	0,050	9.000	590	0,030	0,050
2,5	30	9.000	760	0,030	0,050	8.000	650	0,030	0,050	7.000	450	0,030	0,050
2,5	35	7.500	470	0,020	0,030	7.000	430	0,020	0,030	6.000	290	0,020	0,030
3	6	41.500	6.200	0,150	0,300	32.000	4.800	0,150	0,300	26.500	3.300	0,060	0,150
3	8	30.000	4.200	0,150	0,300	25.000	3.500	0,150	0,300	22.000	2.400	0,060	0,150
3	10	25.000	3.600	0,150	0,300	20.000	2.800	0,150	0,300	18.000	2.000	0,060	0,150
3	12	20.000	2.800	0,150	0,300	18.000	2.500	0,150	0,300	16.000	1.700	0,060	0,150
3	14	18.000	2.500	0,150	0,300	15.000	2.000	0,150	0,300	13.000	1.300	0,060	0,150
3	15	16.000	2.200	0,100	0,300	13.000	1.800	0,100	0,300	11.000	1.200	0,060	0,150
3	16	16.000	1.900	0,100	0,200	13.000	1.500	0,100	0,200	11.000	1.100	0,060	0,150
3	20	14.000	1.700	0,100	0,200	11.000	1.600	0,100	0,200	10.000	1.000	0,060	0,150
3	25	12.000	1.100	0,050	0,100	9.000	820	0,050	0,100	8.000	580	0,050	0,100
3	30	9.000	760	0,030	0,050	7.000	590	0,030	0,050	6.000	400	0,030	0,050

Milling | Endmills

Cutting conditions

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-LN-EBD

High speed milling




Vc		38 ~ 45 HRC				45 ~ 55 HRC				55 ~ 60 HRC			
R	l1 (mm)	120 (m/min)				110 (m/min)				100 (m/min)			
		S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)	S (min ⁻¹)	F (mm/min)	ap (mm)	pf (mm)
3	35	7.500	570	0,020	0,050	6.000	460	0,020	0,050	5.000	300	0,020	0,050
3	40	6.500	470	0,020	0,030	5.000	360	0,020	0,030	4.000	230	0,020	0,030
3,5	15	18.000	2.800	0,100	0,300	14.000	2.000	0,100	0,300	12.000	1.300	0,070	0,150
3,5	20	16.000	2.500	0,100	0,200	12.000	1.800	0,100	0,200	10.000	1.200	0,070	0,150
3,5	25	12.000	1.900	0,100	0,100	9.000	1.300	0,100	0,100	8.000	920	0,070	0,150
3,5	30	10.000	1.500	0,050	0,100	8.000	1.100	0,050	0,100	7.000	770	0,050	0,100
3,5	35	9.000	950	0,050	0,050	7.000	700	0,050	0,050	5.000	400	0,050	0,050
3,5	40	7.500	760	0,050	0,050	6.000	580	0,050	0,050	4.000	300	0,050	0,050
3,5	45	6.500	570	0,030	0,030	5.000	420	0,030	0,030	4.000	260	0,030	0,030
4	8	31.000	5.700	0,200	0,500	24.000	4.400	0,200	0,500	20.000	3.200	0,080	0,200
4	10	25.000	4.200	0,200	0,500	20.000	3.300	0,200	0,500	18.000	2.300	0,080	0,200
4	12	20.000	3.400	0,200	0,500	17.000	2.900	0,200	0,500	14.000	1.900	0,080	0,200
4	15	20.000	3.400	0,200	0,500	16.000	2.700	0,200	0,500	12.000	1.600	0,080	0,200
4	16	18.000	3.000	0,200	0,500	15.000	2.500	0,200	0,500	10.000	1.300	0,080	0,200
4	20	16.000	2.600	0,200	0,400	14.000	2.300	0,200	0,400	8.000	1.000	0,080	0,200
4	25	16.000	2.600	0,100	0,300	13.000	2.200	0,100	0,300	6.000	810	0,080	0,200
4	30	14.000	2.200	0,100	0,200	12.000	1.900	0,100	0,200	5.000	630	0,080	0,200
4	35	12.000	1.700	0,100	0,200	9.000	1.200	0,100	0,200	4.000	420	0,080	0,200
4	40	9.000	1.200	0,050	0,100	8.000	1.000	0,050	0,100	4.000	400	0,050	0,100
4	45	7.500	950	0,050	0,050	7.000	890	0,050	0,050	3.600	360	0,050	0,050
4	50	6.500	660	0,020	0,050	6.000	600	0,020	0,050	3.600	280	0,020	0,050
5	10	25.000	5.400	0,250	0,500	19.000	4.000	0,250	0,500	16.000	2.800	0,100	0,250
5	15	20.000	3.900	0,250	0,500	17.000	3.300	0,250	0,500	13.000	2.000	0,100	0,250
5	20	16.000	3.300	0,250	0,500	13.000	2.700	0,250	0,500	8.000	1.300	0,100	0,250
5	25	15.000	3.000	0,200	0,300	12.000	2.400	0,200	0,300	6.000	960	0,100	0,250
5	30	14.000	2.300	0,100	0,300	11.000	1.800	0,100	0,300	4.000	520	0,100	0,250
5	35	12.000	1.500	0,100	0,300	10.000	1.100	0,100	0,300	3.200	280	0,100	0,250
5	40	10.000	1.100	0,100	0,200	9.000	990	0,100	0,200	3.000	260	0,100	0,200
5	45	9.000	850	0,100	0,100	8.000	660	0,100	0,100	3.000	200	0,100	0,100
5	50	7.500	760	0,100	0,100	7.000	610	0,100	0,100	2.800	190	0,100	0,100
6	12	20.000	5.200	0,300	0,500	16.000	3.400	0,300	0,500	13.500	2.500	0,100	0,200
6	20	16.000	3.900	0,300	0,500	12.000	3.000	0,300	0,500	8.000	1.600	0,100	0,200
6	25	12.000	3.000	0,300	0,500	10.000	2.500	0,300	0,500	6.000	1.200	0,100	0,200
6	30	10.000	2.400	0,300	0,500	9.000	2.100	0,300	0,500	4.000	740	0,100	0,200
6	35	9.000	2.100	0,200	0,400	9.000	2.000	0,200	0,400	3.500	620	0,100	0,200
6	40	9.000	1.900	0,200	0,300	9.000	1.800	0,200	0,300	3.000	480	0,100	0,200
6	45	8.000	1.700	0,200	0,300	8.000	1.600	0,200	0,300	2.800	440	0,100	0,200
6	50	7.000	1.500	0,200	0,300	7.000	1.400	0,200	0,300	2.500	400	0,100	0,200
Max cutting depth													
<p>Attention : sparks and/or flames can cause coolant fire. Be sure adequate fire prevention is available.</p> <ol style="list-style-type: none"> Speeds and feeds are designed to be used in conjunction with small passes on a high speed & precision machine set-up. Do not use inflammable coolant. Using worn tools may generate sparks. Use compressed air or a high quality coolant with a low co-efficient of smoke emission. <p>* Modified parameters</p>													

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-CPR

Regular milling



Ø	α°	l1 (mm)	Max. cutting depth ap							ae	~ 45 HRC SKD61 · NAK55 · NAK80 · HPMI		45 ~ 55 HRC SKD61 · STAVAX · HPM38		55 ~ 65 HRC Hardened Steel	
			R0,05	R0,1	R0,2	R0,3	R0,5	R1	ap = 120%		ae = 120%	ap = 100%	ae = 100%	ap = 60%	ae = 80%	
			S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)								
0,2	0°	0,5	0,005	-	-	-	-	-	0,060	40.000	560	36.000	460	31.500	380	
0,2	0°	1	0,004	-	-	-	-	-	0,060	38.000	530	34.000	435	30.000	355	
0,2	1°	1	0,005	-	-	-	-	-	0,060	40.000	560	40.000	510	35.000	420	
0,2	1°	2	0,004	-	-	-	-	-	0,054	40.000	505	36.000	415	31.500	340	
0,2	3°	1	0,005	-	-	-	-	-	0,060	40.000	560	40.000	510	35.000	420	
0,2	3°	2	0,005	-	-	-	-	-	0,060	40.000	560	36.000	460	31.500	380	
0,2	5°	1	0,005	-	-	-	-	-	0,060	40.000	560	40.000	510	35.000	420	
0,2	5°	2	0,005	-	-	-	-	-	0,060	40.000	560	36.000	460	31.500	380	
0,3	0°	1	0,005	-	-	-	-	-	0,090	36.500	720	32.500	545	30.500	475	
0,3	0°	2	0,002	-	-	-	-	-	0,061	30.000	510	27.000	385	25.500	340	
0,3	1°	2	0,005	-	-	-	-	-	0,090	38.500	720	34.500	545	32.500	480	
0,3	1°	3	0,004	-	-	-	-	-	0,081	36.500	645	32.500	490	30.500	430	
0,3	3°	2	0,005	-	-	-	-	-	0,090	38.500	765	34.500	580	32.500	510	
0,3	3°	3	0,005	-	-	-	-	-	0,090	36.500	720	32.500	545	30.500	475	
0,3	5°	2	0,005	-	-	-	-	-	0,090	38.500	765	32.500	580	32.500	510	
0,3	5°	3	0,005	-	-	-	-	-	0,090	38.500	720	32.500	545	30.500	475	
0,4	0°	1	0,007	-	-	-	-	-	0,120	29.500	750	26.000	580	24.500	470	
0,4	0°	1,5	0,007	-	-	-	-	-	0,120	29.500	750	26.000	580	24.500	470	
0,4	0°	2	0,005	0,008	-	-	-	-	0,102	27.500	675	24.500	520	23.000	420	
0,4	0°	3	0,002	0,003	-	-	-	-	0,075	23.000	470	20.000	360	19.000	290	
0,4	0°	4	0,001	0,002	-	-	-	-	0,036	21.000	380	18.500	290	17.500	235	
0,4	1°	3	0,006	0,009	-	-	-	-	0,120	31.000	755	27.000	580	25.500	470	
0,4	1°	4	0,005	0,007	-	-	-	-	0,108	29.500	680	26.000	520	24.500	420	
0,4	3°	3	0,007	0,01	-	-	-	-	0,120	31.000	795	27.000	610	25.500	495	
0,4	3°	4	0,007	0,01	-	-	-	-	0,120	29.500	750	26.000	580	24.500	470	
0,4	5°	3	0,007	0,01	-	-	-	-	0,120	31.000	795	27.000	610	25.500	495	
0,4	5°	4	0,007	0,01	-	-	-	-	0,120	29.500	750	26.000	580	24.500	470	
0,5	0°	1	0,007	0,01	-	-	-	-	0,150	29.000	820	26.000	670	26.000	620	
0,5	0°	2	0,007	0,01	-	-	-	-	0,150	29.000	820	26.000	670	26.000	620	
0,5	0°	3	0,003	0,005	-	-	-	-	0,105	27.500	695	24.500	570	24.500	525	
0,5	0°	4	0,002	0,003	-	-	-	-	0,090	22.500	510	20.000	420	20.000	385	
0,5	0°	5	0,001	0,002	-	-	-	-	0,045	21.000	415	18.500	340	18.500	315	
0,5	0°	6	0,001	0,001	-	-	-	-	0,030	19.500	360	17.000	295	17.000	270	
0,5	1°	3	0,007	0,01	-	-	-	-	0,150	32.500	910	28.500	745	28.500	690	
0,5	1°	5	0,005	0,007	-	-	-	-	0,150	29.000	735	26.000	605	26.000	560	
0,5	1°	8	0,003	0,004	-	-	-	-	0,052	25.500	560	22.500	460	22.500	425	
0,5	1°	10	0,002	0,003	-	-	-	-	0,022	22.500	475	20.000	390	20.000	360	
0,5	1°	12	0,001	0,002	-	-	-	-	0,016	21.000	415	18.500	340	18.500	315	
0,5	3°	3	0,007	0,01	-	-	-	-	0,150	32.500	910	28.500	745	28.500	690	
0,5	3°	5	0,007	0,01	-	-	-	-	0,150	29.000	820	26.000	670	26.000	620	
0,5	3°	8	0,006	0,009	-	-	-	-	0,067	25.500	710	22.500	580	22.500	535	
0,5	3°	10	0,001	0,002	-	-	-	-	0,037	22.500	575	20.000	470	20.000	435	
0,5	3°	12	0,001	0,002	-	-	-	-	0,031	21.000	475	18.500	390	18.500	360	
0,5	5°	3	0,007	0,01	-	-	-	-	0,150	32.500	910	28.500	745	28.500	690	
0,5	5°	5	0,007	0,01	-	-	-	-	0,150	29.000	820	26.000	670	26.000	620	
0,5	5°	8	0,006	0,009	-	-	-	-	0,142	25.500	710	22.500	580	22.500	535	
0,5	5°	10	0,005	0,007	-	-	-	-	0,112	22.500	635	20.000	520	20.000	480	
0,6	0°	2	-	0,012	-	-	-	-	0,180	29.000	980	26.000	805	21.500	620	
0,6	0°	4	-	0,005	-	-	-	-	0,122	24.500	695	21.500	570	18.000	440	
0,6	0°	6	-	0,002	-	-	-	-	0,054	21.000	495	18.500	410	15.500	315	
0,8	0°	4	-	0,016	0,032	-	-	-	0,240	23.500	1.000	20.500	800	17.000	565	
0,8	0°	6	-	0,007	0,014	-	-	-	0,240	19.500	700	16.500	555	14.000	390	
0,8	0°	8	-	-	0,008	-	-	-	0,216	18.000	570	15.500	450	13.000	320	
0,8	1°	5	0,01	0,02	0,04	-	-	-	0,240	26.500	1.150	26.500	1.050	26.500	905	
0,8	1°	8	0,007	0,015	0,03	-	-	-	0,240	25.000	1.000	25.000	940	25.000	795	
0,8	3°	5	0,01	0,02	0,04	-	-	-	0,240	26.500	1.200	26.500	1.100	26.500	940	
0,8	3°	8	0,01	0,02	0,04	-	-	-	0,240	25.000	1.100	25.000	1.050	25.000	880	
1	0°	4	0,01	0,02	0,04	0,05	-	-	0,300	23.000	1.300	20.000	1.050	17.000	755	
1	0°	6	0,005	0,01	0,02	0,025	-	-	0,210	20.500	1.050	18.000	835	15.500	605	
1	0°	8	0,003	0,006	0,012	0,015	-	-	0,180	18.000	800	15.500	650	13.500	470	
1	0°	10	0,002	0,004	0,008	0,01	-	-	0,090	16.500	650	14.500	530	12.500	380	
1	0°	12	0,001	0,003	0,006	0,007	-	-	0,060	15.500	565	13.500	460	11.500	335	
1	0°	16	-	-	0,004	-	-	-	0,030	12.000	400	10.500	325	9.150	235	
1	0°	20	-	-	0,003	-	-	-	0,024	10.000	285	8.900	230	7.650	170	
1	1°	6	0,01	0,02	0,04	0,05	-	-	0,300	25.500	1.250	22.500	1.150	19.000	840	
1	1°	10	0,007	0,015	0,03	0,037	-	-	0,270	23.000	1.150	20.000	940	17.000	680	
1	1°	15	0,005	0,01	0,02	0,025	-	-	0,120	20.500	915	18.000	740	15.500	540	
1	1°	20	0,003	0,006	0,012	0,015	-	-	0,045	18.000	750	15.500	610	13.500	440	
1	1°	25	0,002	0,002	0,004	0,005	-	-	0,030	16.500	650	14.500	530	12.500	380	
1	1°	30	0,002	0,001	0,002	0,003	-	-	0,021	12.500	465	11.000	380	9.550	275	
1	1°	35	0,002	0,001	0,002	0,002	-	-	0,015	11.500	385	10.000	315	8.600	230	
1	3°	6	0,01	0,02	0,04	0,05	-	-	0,300	25.500	1.450	22.500	1.150	19.000	840	
1	3°	10	0,01	0,02	0,04	0,05	-	-	0,300	23.000	1.300	20.000	1.050	17.000	755	
1,2	0°	6	-	-	0,032	0,04	-	-	0,360	19.000	1.200	18.000	1.050	14.500	735	
1,2	0°	8	-	-	0,018	0,022	-	-	0,252	17.000	965	16.000	845	13.000	580	
1,2	0°	10	-	-	0,011	0,014	-	-	0,216	16.000	850	15.000	740	12.000	510	
1,5	0°	6	-	-	0,04	0,06	-	-	0,450	17.000	1.450	16.000	1.250	13.500	880	
1,5	0°	8	-	-	0,026	0,039	-	-	0,382	16.000	1.250	15.500	1.100	12.500	750	
1,5	0°	10	-	-	0,018	0,027	-	-	0,292	14.500	1.000	13.500	900	11.000	625	

Milling | Endmills


Cutting conditions

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-CPR

Regular milling



Ø	α°	l1 (mm)	ap							ae	~ 45 HRC SKD61 • NAK55 • NAK80 • HPMI		45 ~ 55 HRC SKD61 • STAVAX • HPM38		55 ~ 65 HRC Hardened Steel	
			R0,05	R0,1	R0,2	R0,3	R0,5	R1	ap = 120%		ae = 120%	ap = 100%	ae = 100%	ap = 60%	ae = 80%	
									S (min ⁻¹)		F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	
1,5	0°	12	-	-	0,012	0,018	-	-	0,270	13.500	900	12.500	790	10.500	550	
1,5	0°	16	-	-	0,007	0,01	-	-	0,112	9.150	525	8.650	460	7.150	320	
1,5	1°	10	-	0,019	0,039	0,049	-	-	0,450	18.500	1.500	17.500	1.300	14.500	905	
1,5	1°	15	-	0,015	0,03	0,037	-	-	0,405	17.000	1.150	16.000	1.000	13.500	705	
1,5	1°	20	-	0,01	0,02	0,025	-	-	0,270	15.500	1.100	15.000	970	12.000	675	
1,5	1°	25	-	0,008	0,008	0,01	-	-	0,135	14.500	950	13.500	835	11.500	580	
1,5	1°	30	-	0,003	0,006	0,007	-	-	0,067	13.500	840	12.500	740	10.500	515	
1,5	3°	10	-	0,02	0,04	0,05	-	-	0,450	18.500	1.550	17.500	1.350	14.500	940	
1,5	3°	15	-	0,02	0,04	0,05	-	-	0,450	17.000	1.450	16.000	1.250	13.500	880	
2	0°	8	-	0,02	0,04	0,06	0,075	-	0,600	13.000	1.450	13.000	1.300	11.500	1.000	
2	0°	10	-	0,016	0,032	0,048	0,06	-	0,510	12.000	1.300	12.000	1.150	11.000	905	
2	0°	12	-	0,01	0,02	0,03	0,037	-	0,420	11.500	1.150	11.500	1.050	10.000	810	
2	0°	16	-	0,006	0,012	0,018	0,022	-	0,360	10.000	900	10.000	800	8.900	630	
2	0°	20	-	0,004	0,008	0,012	0,015	-	0,180	9.300	730	9.300	650	8.250	510	
2	0°	25	-	0,002	0,004	0,007	0,009	-	0,120	8.600	625	8.600	560	7.650	440	
2	1°	15	-	0,018	0,036	0,046	0,064	-	0,600	13.500	1.450	13.500	1.300	12.000	1.000	
2	1°	20	-	0,015	0,03	0,037	0,052	-	0,540	13.000	1.300	13.000	1.150	11.500	910	
2	1°	25	-	0,012	0,024	0,03	0,04	-	0,390	12.000	1.150	12.000	1.050	11.000	810	
2	1°	30	-	0,01	0,02	0,025	0,03	-	0,240	11.500	1.050	11.500	920	10.000	720	
2	1°	40	-	0,006	0,012	0,015	0,02	-	0,090	10.000	840	10.000	750	8.900	590	
2	1°	50	-	0,005	0,01	0,01	0,01	-	0,060	9.300	730	9.300	650	8.250	510	
2	3°	15	-	0,02	0,04	0,06	0,075	-	0,600	13.500	1.500	13.500	1.350	12.000	1.050	
2	3°	20	-	0,02	0,04	0,06	0,075	-	0,600	13.000	1.450	13.000	1.300	11.500	1.000	
2,5	0°	10	-	-	0,04	-	0,075	-	0,750	11.500	1.600	10.500	1.200	9.150	1.000	
2,5	0°	20	-	-	0,02	-	0,037	-	0,450	8.900	1.000	8.000	740	7.150	630	
2,5	0°	30	-	-	0,006	-	0,011	-	0,150	7.650	700	6.850	520	6.100	445	
3	0°	8	-	-	0,04	-	-	-	0,900	9.550	1.500	8.600	1.150	7.650	825	
3	0°	12	-	-	0,04	0,06	0,075	-	0,900	9.550	1.500	8.600	1.150	7.650	825	
3	0°	16	-	-	0,028	0,042	0,052	-	0,720	8.500	1.200	7.650	910	6.800	660	
3	0°	20	-	-	0,018	0,027	0,033	-	0,612	7.400	985	6.700	750	5.950	545	
3	0°	25	-	-	0,012	0,018	0,022	-	0,540	7.100	830	6.400	635	5.700	460	
3	0°	30	-	-	0,008	0,012	0,015	-	0,270	6.900	755	6.200	575	5.500	420	
3	0°	35	-	-	0,006	0,009	0,011	-	0,180	6.350	655	5.700	500	5.100	365	
3	1°	15	-	-	0,04	-	0,075	-	0,900	10.500	1.650	9.550	1.250	8.500	920	
3	1°	20	-	-	0,039	-	0,07	-	0,900	9.950	1.500	8.950	1.150	7.950	830	
3	1°	30	-	-	0,03	-	0,05	-	0,810	9.550	1.350	8.600	1.000	7.650	745	
3	1°	40	-	-	0,022	-	0,04	-	0,522	8.900	1.150	8.000	890	7.150	650	
3	1°	50	-	-	0,016	-	0,03	-	0,297	8.050	980	7.250	750	6.450	545	
3	1°	60	-	-	0,012	-	0,02	-	0,135	7.400	870	6.700	660	5.950	480	
4	0°	16	-	-	0,04	0,06	0,075	0,12	1,200	7.150	2.050	6.450	1.550	5.000	965	
4	0°	20	-	-	0,032	0,048	0,06	0,2	1,020	6.750	1.950	6.100	1.450	4.750	910	
4	0°	25	-	-	0,02	0,03	0,037	0,06	0,816	5.950	1.700	5.350	1.300	4.150	800	
4	0°	30	-	-	0,014	0,021	0,026	0,04	0,744	5.550	1.600	5.000	1.200	3.900	750	
4	0°	40	-	-	0,008	0,012	0,015	0,024	0,360	5.150	1.500	4.650	1.100	3.600	695	
4	0°	50	-	-	0,004	0,007	0,009	0,014	0,216	4.550	1.300	4.100	980	3.150	610	


1. Use a rigid and precise machine and holder.
2. When machining carbon steels or hardened steels, using MQL (Minimum Quantity Lubrication/mist coolant) is recommended.
3. The above condition shows an approximate standard for contouring operation (side milling) with a low machining load. If abnormal cutting sounds, vibration or chattering occur depending on the machineshape, cutting amount, rigidity of the machine or work holding condition etc., please adjust the speed, feed and the depth of cut.
4. Adjust the speed, feed rate, and depth of cut if chattering, vibration or abnormal grinding sounds occur.
5. Helical or ramp milling is recommended during the approach of a Z cut.
6. Adjust the speed, feed rate, and the depth of the cut according to the shape of the work, rigidity of the machine, and how the work is held.

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-CPR

Side milling (Contour line finish)



Ø	α°	l1 (mm)	Max. cutting depth ap							ae	~ 45 HRC SKD61 · NAK55 · NAK80 · HPMI		45 ~ 55 HRC SKD61 · STAVAX · HPM38		55 ~ 65 HRC Hardened Steel	
			R0,05	R0,1	R0,2	R0,3	R0,5	R1	ap = 120%		ae = 120%	ap = 100%	ae = 100%	ap = 60%	ae = 80%	
			S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)		F (mm/min)	S (min ⁻¹)	F (mm/min)			
0,2	0°	0,5	0,005	-	-	-	-	-	0,006	50.000	700	43.000	550	43.000	515	
0,2	0°	1	0,005	-	-	-	-	-	0,006	47.500	665	40.500	520	40.500	485	
0,2	1°	1	0,005	-	-	-	-	-	0,006	50.000	700	47.500	610	47.500	575	
0,2	1°	2	0,005	-	-	-	-	-	0,005	50.000	630	43.000	495	43.000	465	
0,2	3°	1	0,005	-	-	-	-	-	0,006	50.000	700	47.500	610	47.500	575	
0,2	3°	2	0,005	-	-	-	-	-	0,006	50.000	700	43.000	550	43.000	515	
0,2	5°	1	0,005	-	-	-	-	-	0,006	50.000	700	47.500	610	47.500	575	
0,2	5°	2	0,005	-	-	-	-	-	0,006	50.000	700	43.000	550	43.000	515	
0,3	0°	1	0,005	-	-	-	-	-	0,009	43.000	850	38.000	690	33.500	520	
0,3	0°	2	0,004	-	-	-	-	-	0,008	36.000	605	32.000	485	28.000	370	
0,3	1°	2	0,005	-	-	-	-	-	0,009	46.000	855	40.500	690	35.500	525	
0,3	1°	3	0,005	-	-	-	-	-	0,009	43.000	765	38.000	620	33.500	470	
0,3	3°	2	0,005	-	-	-	-	-	0,009	46.000	910	40.500	735	35.500	555	
0,3	3°	3	0,005	-	-	-	-	-	0,009	43.000	850	38.000	690	33.500	520	
0,3	5°	2	0,005	-	-	-	-	-	0,009	46.000	910	40.500	735	35.500	555	
0,3	5°	3	0,005	-	-	-	-	-	0,009	43.000	850	38.000	690	33.500	520	
0,4	0°	1	0,006	-	-	-	-	-	0,012	39.500	1.000	32.000	775	28.500	550	
0,4	0°	1,5	0,006	-	-	-	-	-	0,012	39.500	1.000	32.000	775	28.500	550	
0,4	0°	2	0,006	0,01	-	-	-	-	0,012	37.000	905	30.500	695	27.000	495	
0,4	0°	3	0,004	0,007	-	-	-	-	0,008	30.500	630	25.500	480	22.500	340	
0,4	0°	4	0,002	0,004	-	-	-	-	0,006	28.500	510	23.500	390	20.500	280	
0,4	1°	3	0,006	0,01	-	-	-	-	0,012	41.500	1.000	34.000	775	30.000	550	
0,4	1°	4	0,006	0,01	-	-	-	-	0,012	39.500	910	32.000	695	28.500	495	
0,4	3°	3	0,006	0,01	-	-	-	-	0,012	41.500	1.050	34.000	815	30.000	580	
0,4	3°	4	0,006	0,01	-	-	-	-	0,012	39.500	1.000	32.000	775	28.500	550	
0,4	5°	3	0,006	0,01	-	-	-	-	0,012	41.500	1.050	34.000	815	30.000	580	
0,4	5°	4	0,006	0,01	-	-	-	-	0,012	39.500	1.000	32.000	775	28.500	550	
0,5	0°	1	0,006	0,01	-	-	-	-	0,015	34.500	965	28.500	775	24.000	580	
0,5	0°	2	0,006	0,01	-	-	-	-	0,015	34.500	965	28.500	775	24.000	580	
0,5	0°	3	0,006	0,01	-	-	-	-	0,013	32.500	820	27.000	660	22.500	490	
0,5	0°	4	0,003	0,006	-	-	-	-	0,010	26.500	600	22.500	480	18.500	360	
0,5	0°	5	0,002	0,004	-	-	-	-	0,007	25.000	490	20.500	390	17.500	290	
0,5	0°	6	0,001	0,003	-	-	-	-	0,006	23.000	425	19.000	340	16.000	255	
0,5	1°	3	0,006	0,01	-	-	-	-	0,015	38.000	1.050	32.000	860	26.500	640	
0,5	1°	5	0,006	0,01	-	-	-	-	0,015	34.500	865	28.500	695	24.000	520	
0,5	1°	8	0,004	0,007	-	-	-	-	0,010	30.000	660	25.000	530	21.000	395	
0,5	1°	10	0,003	0,005	-	-	-	-	0,009	26.500	560	22.500	450	18.500	340	
0,5	1°	12	0,002	0,004	-	-	-	-	0,006	25.000	490	20.500	390	17.500	290	
0,5	3°	3	0,006	0,01	-	-	-	-	0,015	38.000	1.050	32.000	860	26.500	640	
0,5	3°	5	0,006	0,01	-	-	-	-	0,015	34.500	965	28.500	775	24.000	580	
0,5	3°	8	0,004	0,008	-	-	-	-	0,015	30.000	835	25.000	670	21.000	500	
0,5	3°	10	0,003	0,005	-	-	-	-	0,012	26.500	675	22.500	540	18.500	400	
0,5	3°	12	0,002	0,004	-	-	-	-	0,010	25.000	555	20.500	450	17.500	335	
0,5	5°	3	0,006	0,01	-	-	-	-	0,015	38.000	1.050	32.000	860	26.500	640	
0,5	5°	5	0,006	0,01	-	-	-	-	0,015	34.500	965	28.500	775	24.000	580	
0,5	5°	8	0,006	0,01	-	-	-	-	0,015	30.000	835	25.000	670	21.000	500	
0,5	5°	10	0,004	0,008	-	-	-	-	0,012	26.500	750	22.500	600	18.500	450	
0,6	0°	2	-	0,012	-	-	-	-	0,018	31.000	1.050	26.500	850	24.000	690	
0,6	0°	4	-	0,009	-	-	-	-	0,012	26.000	740	22.000	600	20.000	490	
0,6	0°	6	-	0,004	-	-	-	-	0,009	22.500	530	19.000	430	17.000	350	
0,8	0°	4	-	0,015	0,02	-	-	-	0,020	29.000	1.200	25.500	1.050	23.500	790	
0,8	0°	6	-	0,012	0,016	-	-	-	0,014	23.500	850	21.000	720	19.500	550	
0,8	0°	8	-	-	0,008	-	-	-	0,010	22.000	690	19.500	590	18.000	445	
0,8	1°	5	0,006	0,015	0,02	-	-	-	0,020	26.500	1.150	26.500	1.100	26.500	905	
0,8	1°	8	0,006	0,015	0,02	-	-	-	0,020	25.000	1.000	25.000	975	25.000	795	
0,8	3°	5	0,006	0,015	0,02	-	-	-	0,020	26.500	1.200	26.500	1.150	26.500	940	
0,8	3°	8	0,006	0,015	0,02	-	-	-	0,020	25.000	1.100	25.000	1.100	25.000	880	
1	0°	4	0,006	0,015	0,02	0,03	-	-	0,030	27.000	1.500	24.500	1.250	22.500	995	
1	0°	6	0,006	0,015	0,02	0,03	-	-	0,027	24.000	1.200	21.500	1.000	20.000	800	
1	0°	8	0,003	0,009	0,012	0,018	-	-	0,021	21.000	950	19.000	790	17.500	620	
1	0°	10	0,003	0,006	0,008	0,012	-	-	0,015	19.500	770	17.500	640	16.500	505	
1	0°	12	0,003	0,004	0,006	0,009	-	-	0,013	18.000	670	16.000	560	15.000	440	
1	0°	16	-	-	0,004	-	-	-	0,010	14.500	470	13.000	390	12.000	310	
1	0°	20	-	-	0,003	-	-	-	0,009	12.000	340	11.000	280	10.000	220	
1	1°	6	0,006	0,015	0,02	0,03	-	-	0,030	30.000	1.700	27.000	1.400	25.000	1.100	
1	1°	10	0,006	0,015	0,02	0,03	-	-	0,030	27.000	1.350	24.500	1.150	22.500	895	
1	1°	15	0,004	0,01	0,014	0,021	-	-	0,021	24.000	1.100	21.500	900	20.000	710	
1	1°	20	0,003	0,007	0,01	0,015	-	-	0,018	21.000	890	19.000	740	17.500	580	
1	1°	25	0,002	0,006	0,008	0,012	-	-	0,012	19.500	770	17.500	640	16.500	505	
1	1°	30	0,002	0,003	0,004	0,006	-	-	0,009	15.000	550	13.500	460	12.500	360	
1	1°	35	0,002	0,001	0,002	0,003	-	-	0,007	13.500	460	12.000	380	11.500	300	
1	3°	6	0,006	0,015	0,02	0,03	-	-	0,030	30.000	1.700	27.000	1.400	25.000	1.100	
1	3°	10	0,006	0,015	0,2	0,3	-	-	0,015	27.000	1.500	24.500	1.250	22.500	995	
1,2	0°	6	-	-	0,016	0,024	-	-	0,036	22.500	1.450	21.000	1.250	19.000	960	
1,2	0°	8	-	-	0,009	0,013	-	-	0,028	20.000	1.150	18.500	980	17.000	760	
1,2	0°	10	-	-	0,005	0,008	-	-	0,021	18.500	1.000	17.500	860	16.000	670	
1,5	0°	6	-	-	0,02	0,03	-	-	0,045	21.000	1.750	18.500	1.450	16.000	1.050	
1,5	0°	8	-	-	0,02	0,03	-	-	0,045	20.000	1.500	17.500	1.250	15.500	910	
1,5	0°	10	-	-	0,018	0,027	-	-	0,036	17.500	1.250	15.500	1.050	13.500	760	

Milling | Endmills


Cutting conditions

CUTTING CONDITIONS

Milling | Endmills | Cutting conditions

WXS-CPR

Side milling (Contour line finish)




Ø	α°	l1 (mm)	ap							ae	~ 45 HRC SKD61 • NAK55 • NAK80 • HPMI		45 ~ 55 HRC SKD61 • STAVAX • HPM38		55 ~ 65 HRC Hardened Steel	
			R0,05	R0,1	R0,2	R0,3	R0,5	R1	ap = 120%		ae = 120%	ap = 100%	ae = 100%	ap = 60%	ae = 80%	
									S (min ⁻¹)		F (mm/min)	S (min ⁻¹)	F (mm/min)	S (min ⁻¹)	F (mm/min)	
1,5	0°	12	-	-	0,012	0,018	-	-	0,031	16.500	1.100	14.500	910	12.500	670	
1,5	0°	16	-	-	0,008	0,012	-	-	0,022	11.000	640	10.000	530	8.650	390	
1,5	1°	10	-	0,015	0,02	0,03	-	-	0,045	22.500	1.800	20.000	1.500	17.500	1.100	
1,5	1°	15	-	0,015	0,02	0,03	-	-	0,045	21.000	1.400	18.500	1.150	16.000	860	
1,5	1°	20	-	0,012	0,016	0,024	-	-	0,036	19.000	1.350	17.000	1.100	15.000	820	
1,5	1°	25	-	0,01	0,014	0,021	-	-	0,031	17.500	1.150	16.000	960	13.500	705	
1,5	1°	30	-	0,007	0,01	0,015	-	-	0,027	16.500	1.050	14.500	850	12.500	625	
1,5	3°	10	-	0,015	0,02	0,03	-	-	0,045	22.500	1.900	20.000	1.550	17.500	1.150	
1,5	3°	15	-	0,015	0,02	0,03	-	-	0,045	21.000	1.750	18.500	1.450	16.000	1.050	
2	0°	8	-	0,015	0,02	0,03	0,05	-	0,060	16.500	1.850	16.000	1.600	15.000	1.350	
2	0°	10	-	0,015	0,02	0,03	0,05	-	0,060	15.500	1.650	15.500	1.450	14.500	1.200	
2	0°	12	-	0,015	0,02	0,03	0,05	-	0,054	14.500	1.500	14.500	1.300	13.500	1.050	
2	0°	16	-	0,009	0,012	0,018	0,03	-	0,042	13.000	1.150	12.500	1.000	12.000	830	
2	0°	20	-	0,006	0,008	0,012	0,02	-	0,030	12.000	935	11.500	820	11.000	675	
2	0°	25	-	0,004	0,006	0,009	0,015	-	0,027	11.000	800	11.000	700	10.000	580	
2	1°	15	-	0,015	0,02	0,03	0,05	-	0,060	17.500	1.850	17.000	1.600	16.000	1.350	
2	1°	20	-	0,015	0,02	0,03	0,05	-	0,060	16.500	1.650	16.000	1.450	15.000	1.200	
2	1°	25	-	0,012	0,017	0,025	0,042	-	0,054	15.500	1.500	15.500	1.300	14.500	1.050	
2	1°	30	-	0,012	0,016	0,024	0,04	-	0,048	14.500	1.300	14.500	1.150	13.500	950	
2	1°	40	-	0,007	0,01	0,015	0,025	-	0,036	13.000	1.100	12.500	945	12.000	780	
2	1°	50	-	0,006	0,008	0,012	0,02	-	0,024	12.000	935	11.500	820	11.000	675	
2	3°	15	-	0,015	0,02	0,03	0,05	-	0,060	17.500	1.950	17.000	1.700	16.000	1.400	
2	3°	20	-	0,015	0,02	0,03	0,05	-	0,060	16.500	1.850	16.000	1.600	15.000	1.350	
2,5	0°	10	-	-	0,02	-	0,05	-	0,075	13.000	1.850	13.000	1.400	12.000	1.350	
2,5	0°	20	-	-	0,012	-	0,03	-	0,052	10.000	1.150	10.000	885	9.450	830	
2,5	0°	30	-	-	0,006	-	0,015	-	0,033	8.800	800	8.650	630	8.100	590	
3	0°	8	-	-	0,02	-	-	-	0,080	12.000	2.000	11.000	1.400	10.000	1.100	
3	0°	12	-	-	0,02	0,03	0,05	-	0,080	12.000	2.000	11.000	1.400	10.000	1.100	
3	0°	16	-	-	0,02	0,03	0,05	-	0,080	10.500	1.600	9.600	1.150	9.000	875	
3	0°	20	-	-	0,02	0,03	0,05	-	0,064	9.300	1.350	8.400	940	7.850	725	
3	0°	25	-	-	0,012	0,018	0,03	-	0,048	8.900	1.100	8.050	795	7.550	610	
3	0°	30	-	-	0,008	0,012	0,02	-	0,040	8.600	1.000	7.800	720	7.300	555	
3	0°	35	-	-	0,006	0,009	0,015	-	0,036	7.950	880	7.200	630	6.750	480	
3	1°	15	-	-	0,02	-	0,05	-	0,080	13.500	2.250	12.000	1.600	11.000	1.200	
3	1°	20	-	-	0,02	-	0,05	-	0,080	12.500	2.000	11.500	1.450	10.500	1.100	
3	1°	30	-	-	0,02	-	0,05	-	0,080	12.000	1.800	11.000	1.300	10.000	985	
3	1°	40	-	-	0,018	-	0,045	-	0,064	11.000	1.550	10.000	1.100	9.450	860	
3	1°	50	-	-	0,014	-	0,035	-	0,056	10.000	1.300	9.100	940	8.550	720	
3	1°	60	-	-	0,01	-	0,025	-	0,048	9.300	1.150	8.400	830	7.850	640	
4	0°	16	-	-	0,02	0,03	0,05	0,08	0,080	7.900	2.500	7.150	2.050	6.450	1.450	
4	0°	20	-	-	0,02	0,03	0,05	0,08	0,080	7.450	2.400	6.750	1.950	6.100	1.350	
4	0°	25	-	-	0,02	0,03	0,05	0,08	0,072	6.550	2.000	5.950	1.650	5.350	1.150	
4	0°	30	-	-	0,014	0,021	0,035	0,056	0,056	6.100	1.650	5.550	1.350	5.000	955	
4	0°	40	-	-	0,008	0,012	0,02	0,032	0,040	5.700	1.300	5.150	1.050	4.650	730	
4	0°	50	-	-	0,006	0,009	0,015	0,024	0,036	5.000	960	4.450	785	4.100	550	

1. Use a rigid and precise machine and holder.
2. When machining carbon steels or hardened steels, using MQL (Minimum Quantity Lubrication/mist coolant) is recommended.
3. The above condition shows an approximate standard for contouring operation (side milling) with a low machining load. If abnormal cutting sounds, vibration or chattering occur depending on the machineshape, cutting amount, rigidity of the machine or work holding condition etc., please adjust the speed, feed and the depth of cut.
4. Adjust the speed, feed rate, and depth of cut if chattering, vibration or abnormal grinding sounds occur.
5. Helical or ramp milling is recommended during the approach of a Z cut.
6. Adjust the speed, feed rate, and the depth of the cut according to the shape of the work, rigidity of the machine, and how the work is held.

Approximate offset (mm)

R	Target surface roughness (µm)														
	0,1	0,25	0,5	0,75	1	1,25	1,5	1,75	2	2,5	3	3,5	4	5	
R 0,05	0,006	0,01	0,014	0,017	0,02	0,022	0,024	0,026	0,028	-	-	-	-	-	
R 0,1	0,009	0,014	0,02	0,024	0,028	0,032	0,035	0,037	0,04	0,045	0,049	-	-	-	
R 0,2	0,012	0,02	0,028	0,035	0,04	0,045	0,049	0,053	0,057	0,063	0,07	0,075	0,08	0,9	
R 0,3	0,015	0,025	0,035	0,042	0,049	0,055	0,06	0,065	0,07	0,077	0,085	0,092	0,098	0,11	
R 0,5	0,02	0,032	0,045	0,055	0,065	0,07	0,078	0,084	0,09	0,1	0,11	0,118	0,125	0,141	
R 1	0,028	0,045	0,063	0,078	0,09	0,1	0,11	0,118	0,125	0,142	0,155	0,168	0,18	0,2	



SWEDEN

Branch office of OSG SCANDINAVIA
Singelgatan 7
212 28 Malmö
Sweden
Tel: +46 40 41 22 55
osg@osg-scandinavia.com

OSG SCANDINAVIA

(For Scandinavian countries)
Langebjergvaenget 16
4000 Roskilde
Denmark
Tel: +45 46 75 65 55
osg@osg-scandinavia.com

OSG NETHERLANDS

Bedrijfsweg 5
3481 MG Harmelen
The Netherlands
Tel: +31 348 44 2764
info@osg-nl.com

OSG UK

Kelsey Close, Attleborough Fields Ind Est,
CV11 6RS, Nuneaton
United Kingdom
Tel: +44 (0) 1827 720 013
uk_sales@osg-uk.com

OSG EUROPE LOGISTICS

Avenue Lavoisier 1
B-1300 Z.I. Wavre - Nord
Belgium
Tel: +32 10 23 05 07
info@osgeurope.com

OSG BELUX

Avenue Lavoisier 1
B-1300 Z.I. Wavre - Nord
Belgium
Tel: +32 10 23 05 11
info@osg-belgium.com

OSG IBÉRICA

Bekolarra 4
E - 01010 Vitoria-Gasteiz
Spain
Tel: +34 945 242 400
osg.iberica@osg-ib.com

OSG FRANCE

Parc Icade, Paris Nord 2
Immeuble "Le Rimbaud"
22 Avenue des Nations
CS66191 - 93420 Villepinte
France
Tel: +33 1 49 90 10 10
sales@osg-france.com

OSG ITALY

Via Ferrero, 65 A/B
I - 10098 Rivoli
Italy
Tel: +39 0117705211
info@osg-italia.it



OSG IN EUROPE

CZECH REPUBLIC, SLOVAKIA, HUNGARY

OSG Europe Logistics S.A.
Slovakia, organizačná zložka
Račianska 22/A, Bratislava 831 02
Slovakia
Tel.: +421 24 32 91 295
info@osgeurope.com

OSG POLAND

ul. Spółdzielcza 57
05-074 Halinów
Polska
Tel: +22 760 82 71
Mob. +48 570 677 711
osg@osg-poland.com

OSG ROMANIA SRL

25C, Bucuresti-Magurele Street (Sector 5)
051431 Bucuresti
România
Tel: +40 21 322 07 47
info@osgromania.ro

OSG TURKEY

Rami Kişla Cad.No:56 Eyüp
Istanbul 34056
Turkey
Tel: +90 212 565 24 00
Fax: +90 212 565 44 00
info@osg-turkey.com

Vischer & Bolli AG

Machining and Workholding
Im Schossacher 17
CH-8600 Dübendorf
Switzerland
Tel.: +41 44 802 15 15
info@vb-tools.com

OSG GERMANY

Karl-Ehmann-Str. 25
D - 73037 Göppingen
Germany
Tel: +49 7161 6064 - 0
Fax: +49 7161 6064 - 444
info@osg-germany.de



shaping your dreams

OSG EUROPE LOGISTICS

Avenue Lavoisier 1
B-1300 Z.I. Wavre - Nord - Belgium
Tel: +32 10 23 05 07
info@osgeurope.com

OSG POLAND Sp. z o.o.

Spółdzielcza 57
05-074 Halinów - Poland
Tel: +22 760 82 71
osg@osg-poland.com

OSG ROMANIA SRL

25C, Bucuresti-Magurele Street (Sector 5)
051431 Bucuresti - România
Tel: +40 21 322 07 47
info@osgromania.ro

OSG BELUX

Avenue Lavoisier 1
B-1300 Z.I. Wavre - Nord - Belgium
Tel: +32 10 23 05 11
info@osg-belgium.com

OSG GERMANY

Karl-Ehmann-Str. 25
D - 73037 Göppingen - Germany
Tel: +49 7161 6064 - 0
Fax: +49 7161 6064 - 444
info@osg-germany.de

AUSTRIA

Branch office of OSG GERMANY
Messestraße 11
A-6850 Dornbirn
Tel: +49 7161 6064-0
info@osg-germany.de

OSG FRANCE

Parc Icade, Paris Nord 2
Immeuble "Le Rimbaud"
22 Avenue des Nations
CS66191 - 93420 Villepinte - France
Tel: +33 1 49 90 10 10
sales@osg-france.com

OSG SCANDINAVIA

(For Scandinavian countries)
Langebjergvaenget 16
4000 Roskilde - Denmark
Tel: +45 46 75 65 55
osg@osg-scandinavia.com

OSG ITALIA

Via Ferrero, 65 A/B3
I - 10098 Rivoli - Italy
Tel: +39 0117705211
info@osg-italia.it

OSG NETHERLANDS

Bedrijfsweg 5 - 3481 MG Harmelen
Tel: +31 348 44 2764
info@osg-nl.com

SWEDEN

Branch office of OSG SCANDINAVIA
Singelgatan 7
212 28 Malmö - Sweden
Tel: +46 40 41 22 55
osg@osg-scandinavia.com

Vischer & Bolli AG

Machining and Workholding
Im Schossacher 17
CH-8600 Dübendorf
T +41 44 802 15 15
info@vb-tools.com

OSG UK

Kelsey Close, Attleborough Fields Ind Est,
CV11 6RS, Nuneaton, United Kingdom.
Tel: +44 1827 720 013
uk_sales@osg-uk.com

OSG IBERICA

Bekolarra 4
E - 01010 Vitoria-Gasteiz - Spain
Tel: +34 945 242 400
osg.iberica@osg-ib.com

CZECH, SLOVAKIA, HUNGARY

OSG Europe Logistics S.A.
Slovakia organizacna zlozka
Racianská 22/A, SK-83102 Bratislava
Slovakia
Tel. +421 24 32 91 295
Orders-osgsvk@osgeurope.com

OSG TURKEY

Rami Kışla Cad.No:56 Eyüp
Istanbul 34056 - Turkey
Tel+90 212 565 24 00
Fax: +90 212 565 44 00
info@osg-turkey.com

OSG EUROPE LOGISTICS S.A.

01/2018 - All rights reserved. © OSG Europe 2018.

The contents of this catalogue are provided to you for viewing only. They are not intended for reproduction either in part or in whole in this or other medium. They cannot be copied, used to create derivation work or used for any reason, by means without the express, written permission of the copyright owner. If prices are stated, they are netto unit-prices and any eventual tax(es) have to be added. The company is not responsible for any printing error in technical, price and/or any other data.

Tool specifications subject to change without notice.

www.osgeurope.com

